Deployit IBM WebSphere Application Server Plugin Manual

Version 3.8.2

Table of Contents

Table of Contents 2
Preface 4
Overview 4
Features 4
Requirements 4
Usage in Deployment Packages 4
Using the deployables and deployeds 5
Deployable vs. containers table 5
Deployed actions table 5
Discovering WAS middleware 6
Create a Configuration Item starting point 6
Start discovery passing a Configuration Item 7
Store the CIs in the repository 7
Complete discovered middleware CIs 7
Adding CIs to Environments 7
Extending the WAS plugin 8
Extending using XML and Python scripts 8
Adding a property 9
Fixing a property 9
Inspection 10
Execution order 10
Extending the plugin with custom control task 10
CI Reference 11
Configuration Item Overview 11
Deployables 11
Deployeds 12
Containers 13
Other Configuration Items 14
Configuration Item Details 16
was.BaseCell 16
was.Cluster 17
was.DB2Datasource 17
was.DB2Type2Datasource 19
was.DB2Type2DatasourceSpec 22
was.DB2Type4Datasource 22
was.DB2Type4DatasourceSpec 25
was.Datasource 25
was.Deployable 27
was.DeploymentManager 28
was.Ear 28
was.EarModule 29
was.EjbJar 30
was.EjbModule 31
was.ExtensibleDeployed 32
was.ExtensibleDeployedArtifact 33
was.ExtensibleDeployedResource 35
was.JaasAlias 36
was.JaasAliasSpec 38
was.JdbcProvider 39
was.JdbcProviderSpec 40
was.JmsResource 41
was.ManagedServer 42
was.ManagedWebServer 43
was.Module 43
was.NodeAgent 44
was.OracleDatasource 45
was.OracleDatasourceSpec 46

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

was.OracleJdbcProvider 47
was.OracleJdbcProviderSpec 49
was.OracleXaJdbcProvider 49
was.OracleXaJdbcProviderSpec 50
was.Resource 51
was.SharedLibrary 52
was.SharedLibrarySpec 54
was.SibConnectionFactory 55
was.SibDestination 56
was.SibQueue 58
was.SibQueueConnectionFactory 60
was.SibQueueConnectionFactorySpec 62
was.SibQueueDestination 63
was.SibQueueDestinationSpec 64
was.SibQueueSpec 65
was.SibTopic 65
was.SibTopicConnectionFactory 66
was.SibTopicConnectionFactorySpec 68
was.SibTopicSpaceDestination 69
was.SibTopicSpaceDestinationSpec 70
was.SibTopicSpec 71
was.UnmanagedServer 71
was.V5DefaultQueue 72
was.V5DefaultQueueConnectionFactory 73
was.V5DefaultQueueConnectionFactorySpec 75
was.V5DefaultQueueSpec 76
was.V5DefaultTopic 76
was.V5DefaultTopicConnectionFactory 77
was.V5DefaultTopicConnectionFactorySpec 79
was.V5DefaultTopicSpec 80
was.VirtualHost 80
was.VirtualHostSpec 81
was.War 82
was.WarModule 82
was.WmqQueue 84
was.WmqQueueConnectionFactory 86
was.WmqQueueConnectionFactorySpec 88
was.WmqQueueSpec 89
was.WmqTopic 89
was.WmqTopicConnectionFactory 90
was.WmqTopicConnectionFactorySpec 92
was.WmqTopicSpec 93

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Preface

This document describes the functionality provided by the IBM WebSphere Application Server (WAS) plugin.

Refer to **Deployit Reference Manual** for background information on Deployit and deployment concepts.

Overview

The WAS plugin is a Deployit plugin that adds capability for managing deployments and resources on an existing WebSphere application server. It offers out of the box support for deploying/undeploying application artifacts, datasources, JMS resources and other Java EE resources and WAS configurations. See the **Features** section below for details. It can easily be extended to support more deployment options or management of new artifacts/resources on WAS.

Features

- Deploys and undeploys Java EE application artifacts:
  - Enterprise applications (EAR)
  - Web applications (WAR)
  - Enterprise JavaBeans (EJB JAR)
  - Creates and removes Java EE resources:
    - Oracle datasources
    - DB2 datasources (type 2 and type 4)
    - V5 default JMS resources: queues, topics and connection factories.
    - WebSphere MQ JMS resources: queues, topics and connection factories.
    - SIB JMS resources: queues, topics, connection factories and destinations.
- Creates and removes WAS configuration elements:
  - Shared libraries
  - Virtual hosts
- Discovers WAS topologies: cells, nodes, clusters, server, web servers.

Requirements

- **Deployit requirements**
  - **Deployit**: version 3.6+
  - **IBM WebSphere Application Server Standard and Network Deployment**: 6.1, 7.0, 8.0 and 8.5 (Unix and Windows)
  - **Other Deployit Plugins**: None

Usage in Deployment Packages

The plugin works with the standard deployment package of DAR format. Please see the *Packaging Manual* for more details about the DAR format and the ways to compose one.

The following is a sample MANIFEST.MF file that can be used to create a WebSphere specific deployment package. It contain declarations for an Ear, an Oracle datasource spec and a couple of JMS resources.

```
Manifest-Version: 1.0
Deployit-Package-Format-Version: 1.3
CI-Application: PetClinic-ear
CI-Version: 1.0-was

Name: PetClinic-1.0.ear
CI-Name: PetClinic
CI-Type: jee.Ear

Name: sampleOracleDatasource
CI-Type: was.OracleDatasourceSpec
CI-jndiName: jdbc/sampleOracleDatasource
CI-jdbcProvider: Oracle JDBC Driver
CI-datasourceHelperClassname: com.ibm.websphere.rsadapter.Oracle10gDataStoreHelper
```

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

```
CI-username: {{DATABASE_USERNAME}}
CI-password: {{DATABASE_PASSWORD}}

Name: sampleSibQueueDestination
CI-Type: was.SibQueueDestinationSpec
CI-busName: sampleSIBus

Name: sampleSibQueue
CI-Type: was.SibQueueSpec
CI-queueName: sampleSibQueueDestination
CI-busName: sampleSIBus
CI-description: sample sib queue
```

Using the deployables and deployeds

The following table shows the possible containers a deployable can be targeted to and the deployed that will be created as a result of that.

Deployable vs. containers table

Deployable	Containers	Deployed
jee.Ear or was.Ear jee.War or was.War jee.EjbJar or was.EjbJar	was.UnmanagedServer was.ManagedServer was.Cluster	was.EarModule was.WarModule was.EjbJarModule
was.SharedLibrarySpec	was.UnmanagedServer was.ManagedServer was.Cluster was.NodeAgent was.DeploymentManager	was.SharedLibrary
was.VirtualHostSpec	was.UnmanagedServer was.DeploymentManager	was.VirtualHost
was.V5DefaultQueueSpec was.V5DefaultQueueConnectionFactorySpec was.V5DefaultTopicSpec was.V5DefaultTopicConnectionFactorySpec	was.UnmanagedServer was.ManagedServer was.Cluster was.NodeAgent was.DeploymentManager	was.V5DefaultQueue was.V5DefaultTopic was.V5DefaultQueueConnectionFactory was.V5DefaultTopicConnectionFactory
was.WmqQueueSpec was.WmqQueueConnectionFactorySpec was.WmqTopicSpec was.WmqTopicConnectionFactorySpec	was.UnmanagedServer was.ManagedServer was.Cluster was.NodeAgent was.DeploymentManager	was.WmqQueue was.WmqQueueConnectionFactory was.WmqTopic was.WmqTopicConnectionFactory
was.SibQueueSpec was.SibQueueConnectionFactorySpec was.SibQueueDestinationSpec was.SibTopicSpec was.SibTopicConnectionFactorySpec was.SibTopicSpaceDestinationSpec	was.UnmanagedServer was.ManagedServer was.Cluster was.NodeAgent was.DeploymentManager	was.SibQueue was.SibQueueConnectionFactory was.SibQueueDestination was.SibTopic was.SibTopicConnectionFactory was.SibTopicSpaceDestination

Deployed actions table

The following table shows the actions taken when creating, modifying or destroying a deployed.

Deployed	Create	Modify	Destroy
was.EarModule was.WarModule was.EjbJarModule	• deploy application • WAS ND only: synchronize applicable nodes • start application	• stop application • undeploy application • WAS ND only: synchronize applicable nodes • deploy application • WAS ND only: synchronize applicable nodes • start application	• stop application • undeploy application • WAS ND only: synchronize applicable nodes
was.SharedLibrary	• create shared library • WAS ND only: synchronize applicable nodes	• destroy shared library • WAS ND only: synchronize applicable nodes • create shared library • WAS ND only: synchronize applicable nodes	• destroy shared library • WAS ND only: synchronize applicable nodes
was.VirtualHost	• create virtual host • WAS ND only: synchronize applicable nodes	• destroy virtual host • WAS ND only: synchronize applicable nodes	• destroy virtual host • WAS ND only: synchronize applicable nodes

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

		• create virtual host • WAS ND only: synchronize applicable nodes	
was.V5DefaultQueue was.V5DefaultTopic was.V5DefaultQueueConnectionFactory was.V5DefaultTopicConnectionFactory	• create V5 JMS resource • WAS ND only: synchronize applicable nodes	• destroy V5 JMS resource • WAS ND only: synchronize applicable nodes • create V5 JMS resource • WAS ND only: synchronize applicable nodes	• destroy V5 JMS resource • WAS ND only: synchronize applicable nodes
was.WmqQueue was.WmqQueueConnectionFactory was.WmqTopic was.WmqTopicConnectionFactory	• create WebSphere MQ JMS resource • WAS ND only: synchronize applicable nodes	• destroy WebSphere MQ JMS resource • WAS ND only: synchronize applicable nodes • create WebSphere MQ JMS resource • WAS ND only: synchronize applicable nodes	• destroy WebSphere MQ JMS resource • WAS ND only: synchronize applicable nodes
was.SibQueue was.SibQueueConnectionFactory was.SibQueueDestination was.SibTopic was.SibTopicConnectionFactory was.SibTopicSpaceDestination	• create WebSphere SIB JMS resource • WAS ND only: synchronize applicable nodes	• destroy WebSphere MQ JMS resource • WAS ND only: synchronize applicable nodes • create WebSphere SIB JMS resource • WAS ND only: synchronize applicable nodes	• destroy WebSphere SIB JMS resource • WAS ND only: synchronize applicable nodes

Discovering WAS middleware

Deployit can scan your environment for as far as possible and create Configuration Items in its repository based on the configurations it encounters during the scan. This process is knows as *discovery*.

The CIs discovered during discovery will help you in setting up your infrastructure in an easy way. However, they need not be complete: some CIs contain properties that can not be automatically discovered, like passwords. These specific kind of properties will still need to be entered manually.

Because discovery is part of the Deployit plugin suite, the exact discovery functionality available varies depending on the middleware platforms present in your environment.

The following steps comprehend discovery:

1. Create a CI representing the starting point for discovery (often a *Host* CI).
2. Start discovery passing this CI.
3. Store the discoverd CIs in the repository.
4. Complete the discovered CIs manually by providing missing needed properties.
5. Add the discovered CIs to an environment.

Note however that the last step of discovery is optional. The discovered CIs will be stored under the `Infrastructure` root node in the repository and may be added to an environment at some later time.

Create a Configuration Item starting point

The first step taken in discovery is to create a starting point to kick off the process from. This starting point consists of a Configuration Item specifying at least the host that discovery should start at. Depending on the middleware you are trying to discover, additional

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

parameters may be needed.

Following is an example of how to start discovery for a WebSphere Application Server (WAS). First a CI is created for the host itself and next a Configuration Item is created for the deployment manager running on that ost. The deployment manager CI will be the starting point for discovery.

```
    # Create a CI with the required discovery parameters filled in
    wasHost = factory.configurationItem('Infrastructure/rs94asob.k94.corp.com', 'overthere.SshHost', {
            'address':'was-61',
            'username':'root',
            'password':'rootpwd',
            'os':'UNIX',
            'accessMethod':'SSH_SFTP'
        })

    repository.create(wasHost)

    # Now create a WAS deployment manager
    dmManager = factory.configurationItem(wasHost.id + '/wasDM', 'was.DeploymentManager', {
            'host':'Infrastructure/rs94asob.k94.corp.com',
            'version':'WAS_61',
            'wasHome':'/opt/ws/6.1/profiles/dmgr',
            'username':'wsadmin',
            'password':'wsadmin'})
```

Note 1: Right now possible values for *version* are: *WAS_61*, *WAS_70*, *WAS_80*, *WAS_85*.

Note 2: Last segment of Configuration Item id ("wasDM" in this example) should match your WebSphere cell name.

Start discovery passing a Configuration Item

After the CI starting point has been created, it can be used to perform discovery. The Deployit CLI discovery functionality is synchronous, which means that the CLI will wait until the discovery process finishes.

The process of discovery works exactly like a regular task:

```
deployit> taskId = deployit.createDiscoveryTask(dmManager)
deployit> deployit.startTaskAndWait(taskId)
deployit> discoveredCIs = deployit.retrieveDiscoveryResults(taskId)
```

Note there are no single- or double quotes around `dmManager`, because it's an object and not a string. The result of this command will be an object containing a list of discovered CIs.

Store the CIs in the repository

Deployit returns a list of discovered middleware CIs. Note that these are not yet persisted. To store them in the repository, use the following code:

```
    repository.create(discoveredCIs)
```

Complete discovered middleware CIs

The easiest way to find out which of the discovered CIs require additional information is by printing them. Any CIs that contain passwords (displayed as '********') will need to be completed. To print the stored CIs, the following code can be used:

```
    for ci in discoveredCIs: deployit.print(repository.read(ci.id));
```

Note: the created CIs can also be edited in the GUI using the Repository Browser.

Adding CIs to Environments

Middleware that is used as a deployment target must be grouped together in an environment. Environments are CIs and like all CIs, they can be created from the CLI. The following command can be used for this:

```
    env = factory.configurationItem('Environments/DiscoveredEnv', 'udm.Environment')
```

Add the discovered CIs to the environment:

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

```
env.values['members'] = [ci.id for ci in discoveredCIs]
```

Note that not all of the discovered CIs should necessarily be stored in an environment. For example, in the case of WAS, some nested CIs may be discovered of which only the top-level one must and can be stored.

Store the new environment:

```
repository.create(env)
```

The newly created environment can now be used as a deployment target.

Note: the user needs specific permission to store CIs in the database. See the *Deployit System Administration Manual*.

Extending the WAS plugin

The WAS plugin is designed to be extended through Deployit's Plugin API type system and through the use of custom, user defined WAS Python scripts.

The WAS plugin associates **Create**, **Modify**, **Destroy** and **Inspect** operations received from Deployit with WAS Python scripts that need to be executed for the specific operation to be performed. The operation specific script is given a Python object representation of the `Deployed` that triggered the operation. The script is then executed using **wsadmin**.

There also exists an advanced method to extend the WAS plugin, but the implementation of this form of extension needs to be written in the Java programming language and consists of writing so-called `Deployed contributors`, `PlanPreProcessors` and `Contributors`.

Please refer to the *Customization Manual* for a detailed explanation of the type system and advanced methods of customization of plugins.

Extending using XML and Python scripts

The easiest way of extending the WAS plugin is by using XML and Python scripts. In this way no Java code needs to be written. Extending the behaviour of the plugin is done by simply defining the necessary deployables and deployeds for the specific environment. When Deployit starts up, it reads a file called `synthetic.xml` from the server class-path, i.e. the `ext` directory of the server.

This file contains the type definitions of the deployables and the deployeds, i.e. the information about the types and their properties. In addition to that, it defines which Python scripts should be executed for a particular operation, as mentioned above. The scripts have all the information from the `Deployed` at their disposal to perform their work.

As an example, this is the type definition of a virtual host as it appears in `synthetic.xml`:

```
<type type="was.VirtualHost" extends="was.Resource" deployable-type="was.VirtualHostSpec" container-
type="was.Cell">
    <generate-deployable type="was.VirtualHostSpec" extends="was.Deployable" />
    <property name="createScript" default="was/virtualhost/create-virtual-host.py" hidden="true" />
    <property name="destroyScript" default="was/virtualhost/destroy-virtual-host.py" hidden="true" />
    <property name="inspectScript" default="was/virtualhost/inspect-virtual-host.py" hidden="true" />
    <property name="aliases" kind="set_of_string" description="Virtual host aliases - enter alias as:
hostname:port" />
</type>
```

Looking at this type definition more closely, it indicates that a virtual host, the type of which is `was.VirtualHost` will be created on its target infrastructure, called container, with a `container-type` of `was.Cell`; On WAS a virtual host may be created on a cell and that is exactly what this definition means.

The attribute `extends` tells the plugin what resource is extended by this definition. In this case it's a simple basic resource so it extends the type `was.Resource`. Since multiple virtual hosts may be created this way, each with its own set of properties, a specification of what will be deployed is created, a so-called `deployable-type`, and is itself of type `was.VirtualHostSpec`.

Within the type definition, there is the possibility of specifying properties of exactly how the virtual host is to be created. The first property is called `createScript` and specifies the script to be executed by **wsadmin** for the creation of the virtual host. An extension of this

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

plugin could specify a different creation script. The plugin comes with a default creation script (`createScript`):

create-virtual-host.py

```
import re

pattern = re.compile('^[^:]+:\d{,5}')
virtualHostParent = AdminConfig.getid('/Cell:%s/' % (deployed.container.cellName))
attributes = [['name', deployed.name]]
attributes.append(['aliases', [[['hostname', alias.split(':')[0]], ['port', alias.split(':')[1]]]
                    for alias in deployed.aliases if pattern.match(alias) != None]])
re.purge()

print "Creating virtual host %s on target scope %s with attribute(s) %s" % (deployed.name, virtualHostParent,
attributes)
AdminConfig.create('VirtualHost', virtualHostParent, attributes)
```

This script also shows that `aliases` are also created for the specified virtual host. Aliases may be specified using the property `aliases` and it takes a set of strings. An example of this property is:

```
<property name='aliases' kind='set_of_string' value='www.my-domain.com:80,www.proxy-domain.com:8443'/>
```

In addition to a creation script, a destruction script (`destroyScript`) must also be specified:

destroy-virtual-host.py

```
virtualHostContainmentPath = '/Cell:%s/VirtualHost:%s' % (deployed.container.cellName, deployed.name)
virtualHostId = validateNotEmpty(AdminConfig.getid(virtualHostContainmentPath),
"Cannot find virtual host with id: %s" % (virtualHostContainmentPath))

print "Destroying virtual host %s" % (deployed.name)
AdminConfig.remove(virtualHostId)
```

Finally, a modification script (`modifyScript`) may also be specified. If that is not present, the destruction script is invoked to remove the resource with the old settings and then the creation script is invoked to create the resource with the new settings.

Adding a property

The architecture of the WAS plugin enables the tranfer of properties from the deployed - `was.VirtualHost` in this example - to the accompanying Python scripts defined with the properties `createScript` and `destroyScript`. In order for this to be possible, the properties are bound to an object called `deployed` and can be accessed as `deployed.<property-name>`. This can be seen in the creation script, where the property `aliases` is available as `deployed.aliases` and the name of the virtual host as `deployed.name`. Using this convention as many properties as needed by the scripts can be bound to the type definition. Care should be taken that the scripts use the same type as specified in the definition, so if a property defines a `kind=integer`, the script should also treat the value of this property as being of type `integer`.

An example of adding another property is:

```
<property name='index-range' kind='integer' value='999' description='maximum index of an array of 1000 items'/>
```

Fixing a property

In the case where it is necessary that a specific property should always contain a fixed predefined value, the attribute `hidden=true` should be used on the definition of the property. This way an end-user, who is performing the deployment using the Deployit user interface, won't be able to see this property and therefore not have the possibility of modifying it. Usually this is done for the Python scripts which once written are not allowed to be changed by an end-user.

Using the example of the previous section and wanting to fix the maximum range, the example becomes:

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

```
<property name='index-range' kind='integer' value='999' hidden='true' description='maximum index of an array of
1000 items'/>
```

Inspection

One thing left to be mentioned is the property called `inspectScript`. When the Domain manager of WAS is known, it is possible for Deployit to discover on its own most of the WAS topology automatically. This specific script is called upon by Deployit when it's trying, in our example, to discover a virtual host on a WAS cell. Following is the default script implementation shipped with the WAS plugin:

inspect-virtual-host.py

```
print "Inspecting virtual host %s" % (deployed.name)

virtualHostContainmentPath = '/Cell:%s/VirtualHost:%s' % (deployed.container.cellName, deployed.name)
virtualHostId = validateNotEmpty(AdminConfig.getid(virtualHostContainmentPath),
"Cannot find virtual host %s" % (virtualHostContainmentPath))

inspected('name', AdminConfig.showAttribute(virtualHostId, 'name'))
aliases = AdminConfig.getid(virtualHostContainmentPath + '/HostAlias:/').split()
inspected('aliases', [AdminConfig.showAttribute(alias,'hostname') + ':' +
AdminConfig.showAttribute(alias,'port') for alias in aliases if alias != ""])
```

In the above script, discovered information is handed back to the plugin by use of the `inspected` method. This method takes two parameters, the first one being the name of the discovered item or property and the second one the actual value. The value should be representable as either a string, or a list of strings. The declaration of this method can be found in the Plugin API in the file `base.py`.

More information about the process of discovery and how to use it can be found in the *Command Line Interface* (CLI) manual.

Execution order

A deployment process consists of a series of steps that are executed sequentially. Plugins offer the ability to influence the order of execution of the steps contributed to the deployment process in relation to other contributed steps and operations, not necessarily contributed by the same plugin(s), that are part of the deployment process.

The order of execution allows for the chaining of scripts or operations to create a logical sequence of events. In order to specify the order, properties with the name of `createOrder` and `destroyOrder` may be used with an attibute called `default` to specify the order ordinal. For example, the following `synthetic.xml` snippet says that creation of the virtual host, `default=60`, will happen before any step with a higher order, for example `default=70`, but after any step with a lower order, i.e. lower than `default=60`.

```
<type type="was.VirtualHost" extends="was.Resource" deployable-type="was.VirtualHostSpec" container-
type="was.Cell">
    <generate-deployable type="was.VirtualHostSpec" extends="was.Deployable" />

    <property name="createScript" default="was/virtualhost/create-virtual-host.py" hidden="true" />
    <property name="createVerb" default="Deploy" hidden="true" />
    <property name="createOrder" kind="integer" default="60" hidden="true" />

    <property name="destroyScript" default="was/virtualhost/destroy-virtual-host.py" hidden="true" />
    <property name="destroyVerb" default="Undeploy" hidden="true" />
    <property name="destroyOrder" kind="integer" default="30" hidden="true" />

    <property name="inspectScript" default="was/virtualhost/inspect-virtual-host.py" hidden="true" />
    <property name="aliases" kind="set_of_string" description="Virtual host aliases - enter alias as:
hostname:port" />
</type>
```

Notice that the `destroyOrder` has a low order, because when executing a deployment the virtual host should be destroyed before it can be created again.

Extending the plugin with custom control task

The plugin has the capability to add control tasks to ExtensibleDeployed or PythonManagedContainer. The control task can be specified as a python script that will be executed using wsadmin on the target host or as an OS shell script that will be run on the target host. The OS shell script is first processed with FreeMarker before being executed.

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Creating a python script control task to test datasources

Synthetic.xml snippet

```
<type-modification type="was.Datasource">
  <method name="testDatasource" script="was/resources/ds/test-ds.py" language="python"/>
</type>
```

test-ds.py snippet

```
datasource = AdminConfig.getid("%s/JDBCProvider:%s/DataSource:%s/" %
 (deployed.container.containmentPath, deployed.jdbcProvider, deployed.name))
if datasource == '':
  print "WARN: No JDBC DataSource '%s' found. Nothing to do" % (deployed.name)
else:
  print "Testing JDBC DataSource '%s' (config ID '%s')" % (deployed.name, datasource)
  AdminControl.testConnection(datasource)
```

Creating an os script control task to start the DeploymentManager

Synthetic.xml snippet

```
<type-modification type="was.DeploymentManager">
  <method name="start" script="was/container/start-dm" language="os"/>
</type-modification>
```

start-dm.sh snippet for *nix

```
${container.wasHome}/bin/startManager.sh
```

start-dm.bat snippet for windows

```
${container.wasHome}\bin\startManager.bat
```

CI Reference

Configuration Item Overview

Deployables

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

CI	Description
was.DB2Type2DatasourceSpec	Specification for a DB2 type 2 data source
was.DB2Type4DatasourceSpec	Specification for a DB2 type 4 data source
was.Deployable	Base class for all deployable configutation items
was.Ear	Java EE EAR archive
was.EjbJar	Java EE EJB archive
was.JaasAliasSpec	Description unavailable (deployable)
was.JdbcProviderSpec	Description unavailable (deployable)
was.OracleDatasourceSpec	Specification for an Oracle datasource
was.OracleJdbcProviderSpec	Description unavailable (deployable)
was.OracleXaJdbcProviderSpec	Specification of an Oracle XA JDBC Driver
was.SharedLibrarySpec	Specification of a shared library
was.SibQueueConnectionFactorySpec	Specification of a SIB queue connection factory
was.SibQueueDestinationSpec	Specification of a SIB queue destination
was.SibQueueSpec	Specification of a SIB queue
was.SibTopicConnectionFactorySpec	Specification of a SIB topic connection factory
was.SibTopicSpaceDestinationSpec	Specification of a SIB topic space destination
was.SibTopicSpec	Specification of a SIB topic
was.V5DefaultQueueConnectionFactorySpec	Specification of a V5 default queue connection factory
was.V5DefaultQueueSpec	Specification of a V5 default queue
was.V5DefaultTopicConnectionFactorySpec	Specification of a V5 default topic connection factory
was.V5DefaultTopicSpec	Specification of a V5 default topic
was.VirtualHostSpec	Specification of a virtual host
was.War	Java EE WAR archive
was.WmqQueueConnectionFactorySpec	Specification of a WMQ queue connection factory
was.WmqQueueSpec	Specification of a WMQ queue
was.WmqTopicConnectionFactorySpec	Specification of a WMQ topic connection factory
was.WmqTopicSpec	Specification of a WMQ topic

Deployeds

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

CI	Description
was.DB2Datasource	Base class for all deployed DB2 data source configuration items
was.DB2Type2Datasource	DB2 type 2 data source object supplies your application with connections for accessing the database
was.DB2Type4Datasource	DB2 type 4 data source object supplies your application with connections for accessing the database
was.Datasource	Base class for all deployed data source configuration items
was.EarModule	EAR with values configured for a deployment
was.EjbModule	EJB with values configured for a deployment
was.ExtensibleDeployed	Base class for all extensible deployed configuration items
was.ExtensibleDeployedArtifact	Base class for all extensible deployed artifact configuration items
was.ExtensibleDeployedResource	Base class for all extensible deployed resource configuration items
was.JaasAlias	Description unavailable
was.JdbcProvider	Description unavailable
was.JmsResource	Base class for all deployed JMS resource configuration items
was.Module	Base class for all deployed JEE module configuration items
was.OracleDatasource	Oracle data source object supplies your application with connections for accessing the database
was.OracleJdbcProvider	Description unavailable
was.OracleXaJdbcProvider	Description unavailable
was.Resource	Base class for all deployed JEE resource configuration items
was.SharedLibrary	Container-wide shared library that can be used by deployed applications
was.SibConnectionFactory	Description unavailable
was.SibDestination	Base class for all deployed SIB destionation configuration items
was.SibQueue	JMS queue is used as a destination for point-to-point messaging
was.SibQueueConnectionFactory	JMS queue connection factory is used to create connections to the associated JMS provider of JMS queues, for point-to-point messaging
was.SibQueueDestination	Queue for point-to-point messaging
was.SibTopic	JMS topic is used as a destination for publish/subscribe messaging
was.SibTopicConnectionFactory	JMS topic connection factory is used to create connections to the associated JMS provider of JMS topics, for publish/subscribe messaging
was.SibTopicSpaceDestination	Topic space is a location for publish/subscribe messaging
was.V5DefaultQueue	Queue destinations provided for point-to-point messaging by the internal WebSphere JMS provider
was.V5DefaultQueueConnectionFactory	Specifies a topic connection factory, which is used to create connections to the associated JMS provider of JMS queue destinations for point-to-point messaging
was.V5DefaultTopic	Specifies the topic destinations for publish and subscribe messaging by the internal WebSphere JMS provider
was.V5DefaultTopicConnectionFactory	Specifies a topic connection factory, which is used to create connections to the associated JMS provider of JMS topic destinations for publish and subscribe messaging
was.VirtualHost	Virtual host with a unique set of Web access ports
was.WarModule	WAR with values configured for a deployment
was.WmqQueue	Queue destinations provided for point-to-point messaging by the WebSphere MQ JMS provider
was.WmqQueueConnectionFactory	Queue connection factory is used to create connections to the associated JMS provider of JMS queue destinations, for point-to-point messaging
was.WmqTopic	Topic destinations provided for publish and subscribe messaging by the WebSphere MQ JMS provider
was.WmqTopicConnectionFactory	Topic connection factory is used to create connections to the associated JMS provider of JMS topic destinations, for publish and subscribe messaging

Containers

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

CI	Description
was.BaseCell	Base class for a Webshpere Cell
was.Cluster	A WebSphere cluster managed by a deployment manager (WAS ND)
was.DeploymentManager	A WebSphere Application Server deployment manager (WAS ND)
was.ManagedServer	A WebSphere server managed by a node that is part of a deployment manager (WAS ND)
was.NodeAgent	A WebSphere node agent
was.UnmanagedServer	An unmanaged WebSphere Applicaton Server (WAS Base/SA)

Other Configuration Items

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

CI	Description
was.BaseCell	Base class for a Webshpere Cell
was.Cluster	A WebSphere cluster managed by a deployment manager (WAS ND)
was.DB2Datasource	Base class for all deployed DB2 data source configuration items
was.DB2Type2Datasource	DB2 type 2 data source object supplies your application with connections for accessing the database
was.DB2Type2DatasourceSpec	Specification for a DB2 type 2 data source
was.DB2Type4Datasource	DB2 type 4 data source object supplies your application with connections for accessing the database
was.DB2Type4DatasourceSpec	Specification for a DB2 type 4 data source
was.Datasource	Base class for all deployed data source configuration items
was.Deployable	Base class for all deployable configutation items
was.DeploymentManager	A WebSphere Application Server deployment manager (WAS ND)
was.Ear	Java EE EAR archive
was.EarModule	EAR with values configured for a deployment
was.EjbJar	Java EE EJB archive
was.EjbModule	EJB with values configured for a deployment
was.ExtensibleDeployed	Base class for all extensible deployed configuration items
was.ExtensibleDeployedArtifact	Base class for all extensible deployed artifact configuration items
was.ExtensibleDeployedResource	Base class for all extensible deployed resource configuration items
was.JaasAlias	Description unavailable
was.JaasAliasSpec	Description unavailable (deployable)
was.JdbcProvider	Description unavailable
was.JdbcProviderSpec	Description unavailable (deployable)
was.JmsResource	Base class for all deployed JMS resource configuration items
was.ManagedServer	A WebSphere server managed by a node that is part of a deployment manager (WAS ND)
was.ManagedWebServer	An HTTP server managed by a node that is part of a deployment manager (WAS ND)
was.Module	Base class for all deployed JEE module configuration items
was.NodeAgent	A WebSphere node agent
was.OracleDatasource	Oracle data source object supplies your application with connections for accessing the database
was.OracleDatasourceSpec	Specification for an Oracle datasource
was.OracleJdbcProvider	Description unavailable
was.OracleJdbcProviderSpec	Description unavailable (deployable)
was.OracleXaJdbcProvider	Description unavailable
was.OracleXaJdbcProviderSpec	Specification of an Oracle XA JDBC Driver
was.Resource	Base class for all deployed JEE resource configuration items
was.SharedLibrary	Container-wide shared library that can be used by deployed applications
was.SharedLibrarySpec	Specification of a shared library
was.SibConnectionFactory	Description unavailable
was.SibDestination	Base class for all deployed SIB destionation configuration items
was.SibQueue	JMS queue is used as a destination for point-to-point messaging
was.SibQueueConnectionFactory	JMS queue connection factory is used to create connections to the associated JMS provider of JMS queues, for point-to-point messaging
was.SibQueueConnectionFactorySpec	Specification of a SIB queue connection factory
was.SibQueueDestination	Queue for point-to-point messaging
was.SibQueueDestinationSpec	Specification of a SIB queue destination
was.SibQueueSpec	Specification of a SIB queue
was.SibTopic	JMS topic is used as a destination for publish/subscribe messaging
was.SibTopicConnectionFactory	JMS topic connection factory is used to create connections to the associated JMS provider of JMS topics, for publish/subscribe messaging
was.SibTopicConnectionFactorySpec	Specification of a SIB topic connection factory

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

was.SibTopicSpaceDestination	Topic space is a location for publish/subscribe messaging
was.SibTopicSpaceDestinationSpec	Specification of a SIB topic space destination
was.SibTopicSpec	Specification of a SIB topic
was.UnmanagedServer	An unmanaged WebSphere Applicaton Server (WAS Base/SA)
was.V5DefaultQueue	Queue destinations provided for point-to-point messaging by the internal WebSphere JMS provider
was.V5DefaultQueueConnectionFactory	Specifies a topic connection factory, which is used to create connections to the associated JMS provider of JMS queue destinations for point-to-point messaging
was.V5DefaultQueueConnectionFactorySpec	Specification of a V5 default queue connection factory
was.V5DefaultQueueSpec	Specification of a V5 default queue
was.V5DefaultTopic	Specifies the topic destinations for publish and subscribe messaging by the internal WebSphere JMS provider
was.V5DefaultTopicConnectionFactory	Specifies a topic connection factory, which is used to create connections to the associated JMS provider of JMS topic destinations for publish and subscribe messaging
was.V5DefaultTopicConnectionFactorySpec	Specification of a V5 default topic connection factory
was.V5DefaultTopicSpec	Specification of a V5 default topic
was.VirtualHost	Virtual host with a unique set of Web access ports
was.VirtualHostSpec	Specification of a virtual host
was.War	Java EE WAR archive
was.WarModule	WAR with values configured for a deployment
was.WmqQueue	Queue destinations provided for point-to-point messaging by the WebSphere MQ JMS provider
was.WmqQueueConnectionFactory	Queue connection factory is used to create connections to the associated JMS provider of JMS queue destinations, for point-to-point messaging
was.WmqQueueConnectionFactorySpec	Specification of a WMQ queue connection factory
was.WmqQueueSpec	Specification of a WMQ queue
was.WmqTopic	Topic destinations provided for publish and subscribe messaging by the WebSphere MQ JMS provider
was.WmqTopicConnectionFactory	Topic connection factory is used to create connections to the associated JMS provider of JMS topic destinations, for publish and subscribe messaging
was.WmqTopicConnectionFactorySpec	Specification of a WMQ topic connection factory
was.WmqTopicSpec	Specification of a WMQ topic

Configuration Item Details

was.BaseCell

Virtual Type	
Type Hierarchy	udm.BaseContainer >> udm.BaseConfigurationItem
Interfaces	udm.Taggable, python.PythonManagingContainer, python.PythonManagedContainer, was.WasContainer, udm.ConfigurationItem, was.Cell, udm.Container, overthere.HostContainer

Base class for a Webshpere Cell

Parent
host : CI<overthere.Host> Host on which the unmanaged WAS server runs

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Public Properties

- * **version** : ENUM [WAS_61, WAS_70, WAS_80, WAS_85]
  Version of WebSphere Application Server.
- * **wasHome** : STRING
  Root path of the WebSphere installation path. e.g. /opt/ws/6.1/appserver/profiles/AppSrv01
- **password** : STRING
  Password which is used to login to the WebSphere Administration.
- **port** : INTEGER
  TCP port which is used to login to the WebSphere Administration, default is 8880
- **tags** : SET_OF_STRING
  If set, only deployables with the same tag will be automatically mapped to this container.
- **username** : STRING
  Username which is used to login to the WebSphere Administration.

Hidden Properties

- * **deployedsToDiscover** : SET_OF_STRING = [was.VirtualHost, was.SharedLibrary]
  Deployeds To Discover
- * **inspectScript** : STRING = was/container/discover-inspect-topology.py
  Inspect script for Cell
- **libraryScripts** : LIST_OF_STRING = [was/container/discover-inspect-topology-lib.py]
  List of scripts to appended to runtime script
- **runWithDaemon** : BOOLEAN = true
  Set to true to execute commands with the Python daemon

was.Cluster

Type Hierarchy	udm.BaseContainer >> udm.BaseConfigurationItem
Interfaces	udm.Taggable, was.WasAppContainer, python.PythonManagedContainer, was.WasContainer, udm.ConfigurationItem, udm.Container, overthere.HostContainer

A WebSphere cluster managed by a deployment manager (WAS ND)

Parent

- * **cell** : CI<was.DeploymentManager >
  Deployment manager that manages this this cluster

Public Properties

- **servers** : SET_OF_CI<was.ManagedServer >
  Servers that are part of this cluster
- **tags** : SET_OF_STRING
  If set, only deployables with the same tag will be automatically mapped to this container.

was.DB2Datasource

Virtual Type	
Type Hierarchy	was.Datasource >> was.Resource >> was.ExtensibleDeployedResource >> was.ExtensibleDeployed >> python.PythonManagedDeployed >> udm.BaseDeployed >> udm.BaseConfigurationItem
Interfaces	udm.Deployed, udm.ConfigurationItem

Base class for all deployed DB2 data source configuration items.

Parent

- * **container** : CI<udm.Container>
  The container on which this deployed runs.

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Public Properties	
*	**databaseName** : STRING This is an actual database name, and its not the locally catalogued database name. The Universal JDBC Driver does not rely on information catalogued in the DB2 database directory.
*	**datasourceHelperClassname** : STRING Specifies the data source helper class
*	**jdbcProvider** : STRING Name of the JDBC Provider for this data source
*	**jndiName** : STRING JNDI name of the data source
*	**password** : STRING Password to use when connecting to the data source
*	**username** : STRING Username to use when connecting to the data source
	ConnectionPool_connectionTimeout : INTEGER Connection timeout value for a JDBC data source.
	ConnectionPool_maxConnections : INTEGER Maximum number of connections for a JDBC data source.
	ConnectionPool_minConnections : INTEGER Minimum number of connections for a JDBC data source.
	deployable : CI<udm.Deployable> The deployable that this deployed is derived from.
	description : STRING Description of this data source

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Hidden Properties
* **additionalPropertiesNotToExpose** : STRING = jndiName, jdbcProvider, datasourceHelperClassname, username, password, ConnectionPool Properties that are not exposed to any python wsadmin script.
* **createOrder** : INTEGER = 60 The order in which a create step will be executed.
* **createScript** : STRING = was/datasource/create-datasource.py Python wsadmin script invoked to create a JDBC data source.
* **createVerb** : STRING = Create The word that is used to prefix a step description for the create operation.
* **destroyOrder** : INTEGER = 40 The order in which a destroy step will be executed.
* **destroyScript** : STRING = was/datasource/destroy-datasource.py Python wsadmin script invoked to destroy a JDBC data source.
* **destroyVerb** : STRING = Destroy The word that is used to prefix a step description for the destroy operation.
* **discoverOrder** : INTEGER = 50 The order in which a discover step will be executed.
* **libraryScripts** : LIST_OF_STRING = [was/datasource/discover-inspect-datasource-lib.py] Additional scripts to be included in the runtime
* **modifyOrder** : INTEGER = 60 The order in which a modify step will be executed.
* **modifyVerb** : STRING = Modify The word that is used to prefix a step description for the modify operation.
* **standardPropertiesNotToExpose** : STRING = id, type, properties, deployable, container, createOrder, createScript, createVerb, syncAfterCreateOrder, modifyOrder, modifyScript, modifyVerb, syncAfterModifyOrder, destroyOrder, destroyScript, securityPermissions, inheritPermissions, exposeDeployedApplication, destroyVerb, syncAfterDestroyOrder, startOrder, startScript, startVerb, stopOrder, stopScript, stopVerb, discoverScript, inspectScript, discoverOrder, libraryScripts Standard properties that are not exposed to any python wsadmin script.
* **startOrder** : INTEGER = 50 The order in which a start step will be executed.
* **startVerb** : STRING = Start The word that is used to prefix a step description for the start operation.
* **stopOrder** : INTEGER = 50 The order in which a stop step will be executed.
* **stopVerb** : STRING = Stop The word that is used to prefix a step description for the stop operation.
* **syncAfterCreateOrder** : INTEGER = 65 The order in which a synchronize after create step will be executed.
* **syncAfterDestroyOrder** : INTEGER = 45 The order in which a synchronize after destroy step will be executed.
* **syncAfterModifyOrder** : INTEGER = 65 The order in which a synchronize after modify step will be executed.
exposeDeployedApplication : BOOLEAN = false flag to indicate whether the deployed application CI is to be injected to the python script execution context.
modifyScript : STRING Python script invoked to upgrade a Java EE artifact or modify a Java EE resource
startScript : STRING Python script invoked to start a Java EE artifact or Java EE resource
stopScript : STRING Python script invoked to stop a Java EE artifact or Java EE resource

was.DB2Type2Datasource

Type Hierarchy	was.DB2Datasource >> was.Datasource >> was.Resource >> was.ExtensibleDeployedResource >> was.ExtensibleDeployed >> python.PythonManagedDeployed >> udm.BaseDeployed >> udm.BaseConfigurationItem
Interfaces	udm.Deployed, udm.ConfigurationItem

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

DB2 type 2 data source object supplies your application with connections for accessing the database.

Parent	
*	**container** : CI<udm.Container> The container on which this deployed runs.
Public Properties	
*	**databaseName** : STRING This is an actual database name, and its not the locally catalogued database name. The Universal JDBC Driver does not rely on information catalogued in the DB2 database directory.
*	**datasourceHelperClassname** : STRING Specifies the data source helper class
*	**jdbcProvider** : STRING Name of the JDBC Provider for this data source
*	**jndiName** : STRING JNDI name of the data source
*	**password** : STRING Password to use when connecting to the data source
*	**username** : STRING Username to use when connecting to the data source
	ConnectionPool_connectionTimeout : INTEGER Connection timeout value for a JDBC data source.
	ConnectionPool_maxConnections : INTEGER Maximum number of connections for a JDBC data source.
	ConnectionPool_minConnections : INTEGER Minimum number of connections for a JDBC data source.
	deployable : CI<udm.Deployable> The deployable that this deployed is derived from.
	description : STRING Description of this data source

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Hidden Properties

* **additionalPropertiesNotToExpose** : STRING = jndiName, jdbcProvider, datasourceHelperClassname, username, password, ConnectionPool
  Properties that are not exposed to any python wsadmin script.

* **createOrder** : INTEGER = 60
  The order in which a create step will be executed.

* **createScript** : STRING = was/datasource/create-datasource.py
  Python wsadmin script invoked to create a JDBC data source.

* **createVerb** : STRING = Create
  The word that is used to prefix a step description for the create operation.

* **destroyOrder** : INTEGER = 40
  The order in which a destroy step will be executed.

* **destroyScript** : STRING = was/datasource/destroy-datasource.py
  Python wsadmin script invoked to destroy a JDBC data source.

* **destroyVerb** : STRING = Destroy
  The word that is used to prefix a step description for the destroy operation.

* **discoverOrder** : INTEGER = 50
  The order in which a discover step will be executed.

* **discoverScript** : STRING = was/datasource/discover-inspect-db2-type2-datasources.py
  Python wsadmin script invoked to discover a JDBC data sources.

* **driverType** : STRING = 2
  JDBC connectivity-type of a data source. If you want to use type 4 driver, set the value to 4. If you want to use type 2 driver, set the value to 2. On WebSphere Application Server for Z/OS, driverType 2 uses RRS and supports 2-phase commit processing.

* **libraryScripts** : LIST_OF_STRING = [was/datasource/discover-inspect-datasource-lib.py]
  Additional scripts to be included in the runtime

* **modifyOrder** : INTEGER = 60
  The order in which a modify step will be executed.

* **modifyVerb** : STRING = Modify
  The word that is used to prefix a step description for the modify operation.

* **standardPropertiesNotToExpose** : STRING = id, type, properties, deployable, container, createOrder, createScript, createVerb, syncAfterCreateOrder, modifyOrder, modifyScript, modifyVerb, syncAfterModifyOrder, destroyOrder, destroyScript, securityPermissions, inheritPermissions, exposeDeployedApplication, destroyVerb, syncAfterDestroyOrder, startOrder, startScript, startVerb, stopOrder, stopScript, stopVerb, discoverScript, inspectScript, discoverOrder, libraryScripts
  Standard properties that are not exposed to any python wsadmin script.

* **startOrder** : INTEGER = 50
  The order in which a start step will be executed.

* **startVerb** : STRING = Start
  The word that is used to prefix a step description for the start operation.

* **stopOrder** : INTEGER = 50
  The order in which a stop step will be executed.

* **stopVerb** : STRING = Stop
  The word that is used to prefix a step description for the stop operation.

* **syncAfterCreateOrder** : INTEGER = 65
  The order in which a synchronize after create step will be executed.

* **syncAfterDestroyOrder** : INTEGER = 45
  The order in which a synchronize after destroy step will be executed.

* **syncAfterModifyOrder** : INTEGER = 65
  The order in which a synchronize after modify step will be executed.

exposeDeployedApplication : BOOLEAN = false
flag to indicate whether the deployed application CI is to be injected to the python script execution context.

modifyScript : STRING
Python script invoked to upgrade a Java EE artifact or modify a Java EE resource

startScript : STRING
Python script invoked to start a Java EE artifact or Java EE resource

stopScript : STRING
Python script invoked to stop a Java EE artifact or Java EE resource

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

was.DB2Type2DatasourceSpec

Type Hierarchy	jee.DataSourceSpec >> jee.JndiResourceSpec >> jee.ResourceSpec >> udm.BaseDeployable >> udm.BaseConfigurationItem
Interfaces	udm.Taggable, udm.Deployable, udm.ConfigurationItem

Specification for a DB2 type 2 data source. On WebSphere Application Server for Z/OS, driverType 2 uses RRS and supports 2-phase commit processing.

Public Properties

ConnectionPool_connectionTimeout : STRING
Connection timeout value for a JDBC data source. (integer)

ConnectionPool_maxConnections : STRING
Maximum number of connections for a JDBC data source. (integer)

ConnectionPool_minConnections : STRING
Minimum number of connections for a JDBC data source. (integer)

databaseName : STRING
This is an actual database name, and its not the locally catalogued database name. The Universal JDBC Driver does not rely on information catalogued in the DB2 database directory. (string)

datasourceHelperClassname : STRING
Specifies the data source helper class (string)

description : STRING
Description of this data source (string)

jdbcProvider : STRING
Name of the JDBC Provider for this data source (string)

jndiName : STRING
JNDI name of the data source (string)

password : STRING
Password to use when connecting to the data source (string)

tags : SET_OF_STRING
If set, this deployable will only be mapped automatically to containers with the same tag.

username : STRING
Username to use when connecting to the data source (string)

was.DB2Type4Datasource

Type Hierarchy	was.DB2Datasource >> was.Datasource >> was.Resource >> was.ExtensibleDeployedResource >> was.ExtensibleDeployed >> python.PythonManagedDeployed >> udm.BaseDeployed >> udm.BaseConfigurationItem
Interfaces	udm.Deployed, udm.ConfigurationItem

DB2 type 4 data source object supplies your application with connections for accessing the database.

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Public Properties
* **databaseName** : STRING This is an actual database name, and its not the locally catalogued database name. The Universal JDBC Driver does not rely on information catalogued in the DB2 database directory.
* **datasourceHelperClassname** : STRING Specifies the data source helper class
* **jdbcProvider** : STRING Name of the JDBC Provider for this data source
* **jndiName** : STRING JNDI name of the data source
* **password** : STRING Password to use when connecting to the data source
* **portNumber** : INTEGER = 50000 The TCP/IP port number where the DRDA server resides. If property driverType is set to 4, this property is required.
* **serverName** : STRING The TCP/IP address or host name for the DRDA server. If property driverType is set to 4, this property is required.
* **username** : STRING Username to use when connecting to the data source
ConnectionPool_connectionTimeout : INTEGER Connection timeout value for a JDBC data source.
ConnectionPool_maxConnections : INTEGER Maximum number of connections for a JDBC data source.
ConnectionPool_minConnections : INTEGER Minimum number of connections for a JDBC data source.
deployable : CI<udm.Deployable> The deployable that this deployed is derived from.
description : STRING Description of this data source

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Hidden Properties

* **additionalPropertiesNotToExpose** : STRING = jndiName, jdbcProvider, datasourceHelperClassname, username, password, ConnectionPool
  Properties that are not exposed to any python wsadmin script.

* **createOrder** : INTEGER = 60
  The order in which a create step will be executed.

* **createScript** : STRING = was/datasource/create-datasource.py
  Python wsadmin script invoked to create a JDBC data source.

* **createVerb** : STRING = Create
  The word that is used to prefix a step description for the create operation.

* **destroyOrder** : INTEGER = 40
  The order in which a destroy step will be executed.

* **destroyScript** : STRING = was/datasource/destroy-datasource.py
  Python wsadmin script invoked to destroy a JDBC data source.

* **destroyVerb** : STRING = Destroy
  The word that is used to prefix a step description for the destroy operation.

* **discoverOrder** : INTEGER = 50
  The order in which a discover step will be executed.

* **discoverScript** : STRING = was/datasource/discover-inspect-db2-type4-datasources.py
  Python wsadmin script invoked to discover a JDBC data sources.

* **driverType** : STRING = 4
  JDBC connectivity-type of a data source. If you want to use type 4 driver, set the value to 4. If you want to use type 2 driver, set the value to 2. On WebSphere Application Server for Z/OS, driverType 2 uses RRS and supports 2-phase commit processing.

* **libraryScripts** : LIST_OF_STRING = [was/datasource/discover-inspect-datasource-lib.py]
  Additional scripts to be included in the runtime

* **modifyOrder** : INTEGER = 60
  The order in which a modify step will be executed.

* **modifyVerb** : STRING = Modify
  The word that is used to prefix a step description for the modify operation.

* **standardPropertiesNotToExpose** : STRING = id, type, properties, deployable, container, createOrder, createScript, createVerb, syncAfterCreateOrder, modifyOrder, modifyScript, modifyVerb, syncAfterModifyOrder, destroyOrder, destroyScript, securityPermissions, inheritPermissions, exposeDeployedApplication, destroyVerb, syncAfterDestroyOrder, startOrder, startScript, startVerb, stopOrder, stopScript, stopVerb, discoverScript, inspectScript, discoverOrder, libraryScripts
  Standard properties that are not exposed to any python wsadmin script.

* **startOrder** : INTEGER = 50
  The order in which a start step will be executed.

* **startVerb** : STRING = Start
  The word that is used to prefix a step description for the start operation.

* **stopOrder** : INTEGER = 50
  The order in which a stop step will be executed.

* **stopVerb** : STRING = Stop
  The word that is used to prefix a step description for the stop operation.

* **syncAfterCreateOrder** : INTEGER = 65
  The order in which a synchronize after create step will be executed.

* **syncAfterDestroyOrder** : INTEGER = 45
  The order in which a synchronize after destroy step will be executed.

* **syncAfterModifyOrder** : INTEGER = 65
  The order in which a synchronize after modify step will be executed.

exposeDeployedApplication : BOOLEAN = false
flag to indicate whether the deployed application CI is to be injected to the python script execution context.

modifyScript : STRING
Python script invoked to upgrade a Java EE artifact or modify a Java EE resource

startScript : STRING
Python script invoked to start a Java EE artifact or Java EE resource

stopScript : STRING
Python script invoked to stop a Java EE artifact or Java EE resource

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

was.DB2Type4DatasourceSpec

Type Hierarchy	jee.DataSourceSpec >> jee.JndiResourceSpec >> jee.ResourceSpec >> udm.BaseDeployable >> udm.BaseConfigurationItem
Interfaces	udm.Taggable, udm.Deployable, udm.ConfigurationItem

Specification for a DB2 type 4 data source.

Public Properties
ConnectionPool_connectionTimeout : STRING Connection timeout value for a JDBC data source. (integer)
ConnectionPool_maxConnections : STRING Maximum number of connections for a JDBC data source. (integer)
ConnectionPool_minConnections : STRING Minimum number of connections for a JDBC data source. (integer)
databaseName : STRING This is an actual database name, and its not the locally catalogued database name. The Universal JDBC Driver does not rely on information catalogued in the DB2 database directory. (string)
datasourceHelperClassname : STRING Specifies the data source helper class (string)
description : STRING Description of this data source (string)
jdbcProvider : STRING Name of the JDBC Provider for this data source (string)
jndiName : STRING JNDI name of the data source (string)
password : STRING Password to use when connecting to the data source (string)
portNumber : STRING The TCP/IP port number where the DRDA server resides. If property driverType is set to 4, this property is required. (integer)
serverName : STRING The TCP/IP address or host name for the DRDA server. If property driverType is set to 4, this property is required. (string)
tags : SET_OF_STRING If set, this deployable will only be mapped automatically to containers with the same tag.
username : STRING Username to use when connecting to the data source (string)

was.Datasource

Virtual Type	
Type Hierarchy	was.Resource >> was.ExtensibleDeployedResource >> was.ExtensibleDeployed >> python.PythonManagedDeployed >> udm.BaseDeployed >> udm.BaseConfigurationItem
Interfaces	udm.Deployed, udm.ConfigurationItem

Base class for all deployed data source configuration items.

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Public Properties
* **datasourceHelperClassname** : STRING Specifies the data source helper class
* **jdbcProvider** : STRING Name of the JDBC Provider for this data source
* **jndiName** : STRING JNDI name of the data source
* **password** : STRING Password to use when connecting to the data source
* **username** : STRING Username to use when connecting to the data source
ConnectionPool_connectionTimeout : INTEGER Connection timeout value for a JDBC data source.
ConnectionPool_maxConnections : INTEGER Maximum number of connections for a JDBC data source.
ConnectionPool_minConnections : INTEGER Minimum number of connections for a JDBC data source.
deployable : CI<udm.Deployable> The deployable that this deployed is derived from.
description : STRING Description of this data source

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Hidden Properties

* **additionalPropertiesNotToExpose** : STRING = jndiName, jdbcProvider, datasourceHelperClassname, username, password, ConnectionPool
  Properties that are not exposed to any python wsadmin script.
* **createOrder** : INTEGER = 60
  The order in which a create step will be executed.
* **createScript** : STRING = was/datasource/create-datasource.py
  Python wsadmin script invoked to create a JDBC data source.
* **createVerb** : STRING = Create
  The word that is used to prefix a step description for the create operation.
* **destroyOrder** : INTEGER = 40
  The order in which a destroy step will be executed.
* **destroyScript** : STRING = was/datasource/destroy-datasource.py
  Python wsadmin script invoked to destroy a JDBC data source.
* **destroyVerb** : STRING = Destroy
  The word that is used to prefix a step description for the destroy operation.
* **discoverOrder** : INTEGER = 50
  The order in which a discover step will be executed.
* **libraryScripts** : LIST_OF_STRING = [was/datasource/discover-inspect-datasource-lib.py]
  Additional scripts to be included in the runtime
* **modifyOrder** : INTEGER = 60
  The order in which a modify step will be executed.
* **modifyVerb** : STRING = Modify
  The word that is used to prefix a step description for the modify operation.
* **standardPropertiesNotToExpose** : STRING = id, type, properties, deployable, container, createOrder, createScript, createVerb, syncAfterCreateOrder, modifyOrder, modifyScript, modifyVerb, syncAfterModifyOrder, destroyOrder, destroyScript, securityPermissions, inheritPermissions, exposeDeployedApplication, destroyVerb, syncAfterDestroyOrder, startOrder, startScript, startVerb, stopOrder, stopScript, stopVerb, discoverScript, inspectScript, discoverOrder, libraryScripts
  Standard properties that are not exposed to any python wsadmin script.
* **startOrder** : INTEGER = 50
  The order in which a start step will be executed.
* **startVerb** : STRING = Start
  The word that is used to prefix a step description for the start operation.
* **stopOrder** : INTEGER = 50
  The order in which a stop step will be executed.
* **stopVerb** : STRING = Stop
  The word that is used to prefix a step description for the stop operation.
* **syncAfterCreateOrder** : INTEGER = 65
  The order in which a synchronize after create step will be executed.
* **syncAfterDestroyOrder** : INTEGER = 45
  The order in which a synchronize after destroy step will be executed.
* **syncAfterModifyOrder** : INTEGER = 65
  The order in which a synchronize after modify step will be executed.

exposeDeployedApplication : BOOLEAN = false
flag to indicate whether the deployed application CI is to be injected to the python script execution context.

modifyScript : STRING
Python script invoked to upgrade a Java EE artifact or modify a Java EE resource

startScript : STRING
Python script invoked to start a Java EE artifact or Java EE resource

stopScript : STRING
Python script invoked to stop a Java EE artifact or Java EE resource

was.Deployable

Virtual Type	
Type Hierarchy	udm.BaseDeployable >> udm.BaseConfigurationItem
Interfaces	udm.Taggable, udm.Deployable, udm.ConfigurationItem

Base class for all deployable configutation items.

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Public Properties	
	tags : SET_OF_STRING If set, this deployable will only be mapped automatically to containers with the same tag.

was.DeploymentManager

Type Hierarchy	was.BaseCell >> udm.BaseContainer >> udm.BaseConfigurationItem
Interfaces	udm.Taggable, python.PythonManagingContainer, python.PythonManagedContainer, was.WasContainer, udm.ConfigurationItem, was.Cell, udm.Container, overthere.HostContainer

A WebSphere Application Server deployment manager (WAS ND)

Parent	
*	**host** : CI<overthere.Host> Host on which the unmanaged WAS server runs
Children	
*	**nodeAgents** : SET_OF_CI<was.NodeAgent > WebSphere nodes in the cell
	clusters : SET_OF_CI<was.Cluster > WebSphere clusters in the cell
Public Properties	
*	**version** : ENUM [WAS_61, WAS_70, WAS_80, WAS_85] Version of WebSphere Application Server.
*	**wasHome** : STRING Root path of the WebSphere installation path. e.g. /opt/ws/6.1/appserver/profiles/AppSrv01
	password : STRING Password which is used to login to the WebSphere Administration.
	port : INTEGER TCP port which is used to login to the WebSphere Administration, default is 8880
	tags : SET_OF_STRING If set, only deployables with the same tag will be automatically mapped to this container.
	username : STRING Username which is used to login to the WebSphere Administration.
Hidden Properties	
*	**deployedsToDiscover** : SET_OF_STRING = [was.VirtualHost, was.SharedLibrary] Deployeds To Discover
*	**inspectScript** : STRING = was/container/discover-inspect-topology.py Inspect script for Cell
	libraryScripts : LIST_OF_STRING = [was/container/discover-inspect-topology-lib.py] List of scripts to appended to runtime script
	runWithDaemon : BOOLEAN = true Set to true to execute commands with the Python daemon

was.Ear

Type Hierarchy	jee.Ear >> udm.BaseDeployableArchiveArtifact >> udm.BaseDeployableFileArtifact >> udm.BaseDeployableArtifact >> udm.BaseDeployable >> udm.BaseConfigurationItem
Interfaces	udm.Taggable, udm.Deployable, udm.SourceArtifact, udm.ArchiveArtifact, udm.Artifact, udm.DeployableArtifact, udm.ConfigurationItem, udm.FileArtifact

Java EE EAR archive

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Public Properties	
	excludeFileNamesRegex : STRING Regular expression that matches file names that must be excluded from scanning
	placeholders : SET_OF_STRING Placeholders detected in this artifact
	preCompileJsps : STRING Specify whether to precompile JavaServer Pages (JSP) files as a part of installation. The default is not to precompile JSP files. (boolean)
	roleMappings : MAP_STRING_STRING Security role to user/group mapping (map_string_string)
	scanPlaceholders : BOOLEAN = false Whether to scan this artifact for placeholders when it is imported
	startingWeight : STRING Specifies the order in which modules are started when the server starts. The module with the lowest starting weight is started first. (integer)
	tags : SET_OF_STRING If set, this deployable will only be mapped automatically to containers with the same tag.
Hidden Properties	
*	**textFileNamesRegex** : STRING = .+\.(cfg | conf | config | ini | properties | props | txt | asp | aspx | htm | html | jsf | jsp | xht | xhtml | sql | xml | xsd | xsl | xslt) Regular expression that matches file names of text files

was.EarModule

Type Hierarchy was.Module >> was.ExtensibleDeployedArtifact >> was.ExtensibleDeployed >> python.PythonManagedDeployed >> udm.BaseDeployed >> udm.BaseConfigurationItem

Interfaces udm.Artifact, udm.Deployed, udm.ConfigurationItem, udm.DerivedArtifact

EAR with values configured for a deployment.

Parent	
*	**container** : CI<udm.Container> The container on which this deployed runs.
Public Properties	
	deployable : CI<udm.Deployable> The deployable that this deployed is derived from.
	placeholders : MAP_STRING_STRING A Map containing all the placeholders mapped to their values. Special values are or
	preCompileJsps : BOOLEAN = false Specify whether to precompile JavaServer Pages (JSP) files as a part of installation. The default is not to precompile JSP files.
	roleMappings : MAP_STRING_STRING Security role to user/group mapping
	sharedLibraries : SET_OF_CI<was.SharedLibrary > Shared libraries used by this application
	startingWeight : INTEGER = 1 Specifies the order in which modules are started when the server starts. The module with the lowest starting weight is started first.
	virtualHost : CI<was.VirtualHost > Virtual host this application should be mapped to
	webServers : SET_OF_CI<was.ManagedWebServer > Web servers this application should be mapped to

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Hidden Properties

* **createOrder** : INTEGER = 70
  The order in which a create step will be executed.
* **createScript** : STRING = was/application/deploy-application.py
  Python wsadmin script invoked to create a Java EE artifact.
* **createVerb** : STRING = Deploy
  The word is used to prefix a step description for the create operation.
* **destroyOrder** : INTEGER = 30
  The order in which a destroy step will be executed.
* **destroyScript** : STRING = was/application/undeploy-application.py
  Python wsadmin script invoked to destroy a Java EE artifact.
* **destroyVerb** : STRING = Undeploy
  The word is used to prefix a step description for the destroy operation.
* **discoverOrder** : INTEGER = 50
  The order in which a discover step will be executed.
* **discoverScript** : STRING = was/application/discover-inspect-ear-module.py
  Python wsadmin script invoked to inspect a JMS resource.
* **libraryScripts** : LIST_OF_STRING = [was/application/discover-app-module-lib.py]
  Additional scripts to be included in the runtime
* **modifyOrder** : INTEGER = 70
  The order in which a modify step will be executed.
* **modifyVerb** : STRING = Upgrade
  The word is used to prefix a step description for the modify operation.
* **standardPropertiesNotToExpose** : STRING = id, type, properties, deployable, container, createOrder, createScript, createVerb, syncAfterCreateOrder, modifyOrder, modifyScript, modifyVerb, syncAfterModifyOrder, destroyOrder, destroyScript, securityPermissions, inheritPermissions, exposeDeployedApplication, destroyVerb, syncAfterDestroyOrder, startOrder, startScript, startVerb, stopOrder, stopScript, stopVerb, discoverScript, inspectScript, discoverOrder, libraryScripts
  Standard properties that are not exposed to any python wsadmin script.
* **startOrder** : INTEGER = 90
  The order in which a start step will be executed.
* **startScript** : STRING = was/application/start-application.py
  Python wsadmin script invoked to start running a Java EE artifact
* **startVerb** : STRING = Start
  The word that is used to prefix a step description for the start operation.
* **stopOrder** : INTEGER = 10
  The order in which a stop step will be executed.
* **stopScript** : STRING = was/application/stop-application.py
  Python wsadmin script invoked to stop running a Java EE artifact.
* **stopVerb** : STRING = Stop
  The word that is used to prefix a step description for the stop operation.
* **syncAfterCreateOrder** : INTEGER = 75
  The order in which a synchronize after create step will be executed.
* **syncAfterDestroyOrder** : INTEGER = 35
  Sync After Destroy Order
* **syncAfterModifyOrder** : INTEGER = 75
  The order in which a synchronize after modify step will be executed.

exposeDeployedApplication : BOOLEAN = false
flag to indicate whether the deployed application CI is to be injected to the python script execution context.

modifyScript : STRING
Python script invoked to upgrade a Java EE artifact or modify a Java EE resource

was.EjbJar

Type Hierarchy	jee.EjbJar >> udm.BaseDeployableArchiveArtifact >> udm.BaseDeployableFileArtifact >> udm.BaseDeployableArtifact >> udm.BaseDeployable >> udm.BaseConfigurationItem
Interfaces	udm.Taggable, udm.Deployable, udm.SourceArtifact, udm.ArchiveArtifact, udm.Artifact, udm.DeployableArtifact, udm.ConfigurationItem, udm.FileArtifact

Java EE EJB archive

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Public Properties	
	excludeFileNamesRegex : STRING Regular expression that matches file names that must be excluded from scanning
	placeholders : SET_OF_STRING Placeholders detected in this artifact
	roleMappings : MAP_STRING_STRING Security role to user/group mapping (map_string_string)
	scanPlaceholders : BOOLEAN = false Whether to scan this artifact for placeholders when it is imported
	startingWeight : STRING Specifies the order in which modules are started when the server starts. The module with the lowest starting weight is started first. (integer)
	tags : SET_OF_STRING If set, this deployable will only be mapped automatically to containers with the same tag.
Hidden Properties	
*	**textFileNamesRegex** : STRING = .+\.(cfg | conf | config | ini | properties | props | txt | asp | aspx | htm | html | jsf | jsp | xht | xhtml | sql | xml | xsd | xsl | xslt) Regular expression that matches file names of text files

was.EjbModule

Type Hierarchy	was.Module >> was.ExtensibleDeployedArtifact >> was.ExtensibleDeployed >> python.PythonManagedDeployed >> udm.BaseDeployed >> udm.BaseConfigurationItem
Interfaces	udm.Artifact, udm.Deployed, udm.ConfigurationItem, udm.DerivedArtifact

EJB with values configured for a deployment.

Parent	
*	**container** : CI<udm.Container> The container on which this deployed runs.

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Hidden Properties

* **createOrder** : INTEGER = 70
  The order in which a create step will be executed.
* **createScript** : STRING = was/application/deploy-application.py
  Python wsadmin script invoked to create a Java EE artifact.
* **createVerb** : STRING = Deploy
  The word is used to prefix a step description for the create operation.
* **destroyOrder** : INTEGER = 30
  The order in which a destroy step will be executed.
* **destroyScript** : STRING = was/application/undeploy-application.py
  Python wsadmin script invoked to destroy a Java EE artifact.
* **destroyVerb** : STRING = Undeploy
  The word is used to prefix a step description for the destroy operation.
* **discoverOrder** : INTEGER = 50
  The order in which a discover step will be executed.
* **discoverScript** : STRING = was/application/discover-inspect-ejb-module.py
  Python wsadmin script invoked to inspect a JMS resource.
* **libraryScripts** : LIST_OF_STRING = [was/application/discover-app-module-lib.py]
  Additional scripts to be included in the runtime
* **modifyOrder** : INTEGER = 70
  The order in which a modify step will be executed.
* **modifyVerb** : STRING = Upgrade
  The word is used to prefix a step description for the modify operation.
* **standardPropertiesNotToExpose** : STRING = id, type, properties, deployable, container, createOrder, createScript, createVerb, syncAfterCreateOrder, modifyOrder, modifyScript, modifyVerb, syncAfterModifyOrder, destroyOrder, destroyScript, securityPermissions, inheritPermissions, exposeDeployedApplication, destroyVerb, syncAfterDestroyOrder, startOrder, startScript, startVerb, stopOrder, stopScript, stopVerb, discoverScript, inspectScript, discoverOrder, libraryScripts
  Standard properties that are not exposed to any python wsadmin script.
* **startOrder** : INTEGER = 90
  The order in which a start step will be executed.
* **startScript** : STRING = was/application/start-application.py
  Python wsadmin script invoked to start running a Java EE artifact
* **startVerb** : STRING = Start
  The word that is used to prefix a step description for the start operation.
* **stopOrder** : INTEGER = 10
  The order in which a stop step will be executed.
* **stopScript** : STRING = was/application/stop-application.py
  Python wsadmin script invoked to stop running a Java EE artifact.
* **stopVerb** : STRING = Stop
  The word that is used to prefix a step description for the stop operation.
* **syncAfterCreateOrder** : INTEGER = 75
  The order in which a synchronize after create step will be executed.
* **syncAfterDestroyOrder** : INTEGER = 35
  Sync After Destroy Order
* **syncAfterModifyOrder** : INTEGER = 75
  The order in which a synchronize after modify step will be executed.

exposeDeployedApplication : BOOLEAN = false
flag to indicate whether the deployed application CI is to be injected to the python script execution context.

modifyScript : STRING
Python script invoked to upgrade a Java EE artifact or modify a Java EE resource

was.ExtensibleDeployed

Virtual Type	
Type Hierarchy	python.PythonManagedDeployed >> udm.BaseDeployed >> udm.BaseConfigurationItem
Interfaces	udm.Deployed, udm.ConfigurationItem

Base class for all extensible deployed configuration items.

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Parent

* **container** : CI<udm.Container>
The container on which this deployed runs.

Public Properties

deployable : CI<udm.Deployable>
The deployable that this deployed is derived from.

Hidden Properties

* **createOrder** : INTEGER = 60
The order in which a create step will be executed.

* **createVerb** : STRING = Create
The word that is used to prefix a step description for the create operation.

* **destroyOrder** : INTEGER = 40
The order in which a destroy step will be executed.

* **destroyVerb** : STRING = Destroy
The word that is used to prefix a step description for the destroy operation.

* **discoverOrder** : INTEGER = 50
The order in which a discover step will be executed.

* **modifyOrder** : INTEGER = 60
The order in which a modify step will be executed.

* **modifyVerb** : STRING = Modify
The word that is used to prefix a step description for the modify operation.

* **standardPropertiesNotToExpose** : STRING = id, type, properties, deployable, container, createOrder, createScript, createVerb, syncAfterCreateOrder, modifyOrder, modifyScript, modifyVerb, syncAfterModifyOrder, destroyOrder, destroyScript, securityPermissions, inheritPermissions, exposeDeployedApplication, destroyVerb, syncAfterDestroyOrder, startOrder, startScript, startVerb, stopOrder, stopScript, stopVerb, discoverScript, inspectScript, discoverOrder, libraryScripts
Standard properties that are not exposed to any python wsadmin script.

* **startOrder** : INTEGER = 50
The order in which a start step will be executed.

* **startVerb** : STRING = Start
The word that is used to prefix a step description for the start operation.

* **stopOrder** : INTEGER = 50
The order in which a stop step will be executed.

* **stopVerb** : STRING = Stop
The word that is used to prefix a step description for the stop operation.

* **syncAfterCreateOrder** : INTEGER = 65
The order in which a synchronize after create step will be executed.

* **syncAfterDestroyOrder** : INTEGER = 45
The order in which a synchronize after destroy step will be executed.

* **syncAfterModifyOrder** : INTEGER = 65
The order in which a synchronize after modify step will be executed.

createScript : STRING
Python script invoked to deploy a Java EE artifact or create a Java EE resource

destroyScript : STRING
Python script invoked to undeploy a Java EE artifact or destroy a Java EE resource

exposeDeployedApplication : BOOLEAN = false
flag to indicate whether the deployed application CI is to be injected to the python script execution context.

libraryScripts : LIST_OF_STRING
List of scripts to appended to the the deployeds runtime script

modifyScript : STRING
Python script invoked to upgrade a Java EE artifact or modify a Java EE resource

startScript : STRING
Python script invoked to start a Java EE artifact or Java EE resource

stopScript : STRING
Python script invoked to stop a Java EE artifact or Java EE resource

was.ExtensibleDeployedArtifact

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Virtual Type	
Type Hierarchy	was.ExtensibleDeployed >> python.PythonManagedDeployed >> udm.BaseDeployed >> udm.BaseConfigurationItem
Interfaces	udm.Artifact, udm.Deployed, udm.ConfigurationItem, udm.DerivedArtifact

Base class for all extensible deployed artifact configuration items.

Parent	
*	**container** : CI<udm.Container> The container on which this deployed runs.
Public Properties	
	deployable : CI<udm.Deployable> The deployable that this deployed is derived from.
	placeholders : MAP_STRING_STRING A Map containing all the placeholders mapped to their values. Special values are or

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Hidden Properties

* **createOrder** : INTEGER = 60
  The order in which a create step will be executed.

* **createVerb** : STRING = Create
  The word that is used to prefix a step description for the create operation.

* **destroyOrder** : INTEGER = 40
  The order in which a destroy step will be executed.

* **destroyVerb** : STRING = Destroy
  The word that is used to prefix a step description for the destroy operation.

* **discoverOrder** : INTEGER = 50
  The order in which a discover step will be executed.

* **modifyOrder** : INTEGER = 60
  The order in which a modify step will be executed.

* **modifyVerb** : STRING = Modify
  The word that is used to prefix a step description for the modify operation.

* **standardPropertiesNotToExpose** : STRING = id, type, properties, deployable, container, createOrder, createScript, createVerb, syncAfterCreateOrder, modifyOrder, modifyScript, modifyVerb, syncAfterModifyOrder, destroyOrder, destroyScript, securityPermissions, inheritPermissions, exposeDeployedApplication, destroyVerb, syncAfterDestroyOrder, startOrder, startScript, startVerb, stopOrder, stopScript, stopVerb, discoverScript, inspectScript, discoverOrder, libraryScripts
  Standard properties that are not exposed to any python wsadmin script.

* **startOrder** : INTEGER = 50
  The order in which a start step will be executed.

* **startVerb** : STRING = Start
  The word that is used to prefix a step description for the start operation.

* **stopOrder** : INTEGER = 50
  The order in which a stop step will be executed.

* **stopVerb** : STRING = Stop
  The word that is used to prefix a step description for the stop operation.

* **syncAfterCreateOrder** : INTEGER = 65
  The order in which a synchronize after create step will be executed.

* **syncAfterDestroyOrder** : INTEGER = 45
  The order in which a synchronize after destroy step will be executed.

* **syncAfterModifyOrder** : INTEGER = 65
  The order in which a synchronize after modify step will be executed.

createScript : STRING
Python script invoked to deploy a Java EE artifact or create a Java EE resource

destroyScript : STRING
Python script invoked to undeploy a Java EE artifact or destroy a Java EE resource

exposeDeployedApplication : BOOLEAN = false
flag to indicate whether the deployed application CI is to be injected to the python script execution context.

libraryScripts : LIST_OF_STRING
List of scripts to appended to the the deployeds runtime script

modifyScript : STRING
Python script invoked to upgrade a Java EE artifact or modify a Java EE resource

startScript : STRING
Python script invoked to start a Java EE artifact or Java EE resource

stopScript : STRING
Python script invoked to stop a Java EE artifact or Java EE resource

was.ExtensibleDeployedResource

Virtual Type	
Type Hierarchy	was.ExtensibleDeployed >> python.PythonManagedDeployed >> udm.BaseDeployed >> udm.BaseConfigurationItem
Interfaces	udm.Deployed, udm.ConfigurationItem

Base class for all extensible deployed resource configuration items.

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Parent

* **container** : CI<udm.Container>
The container on which this deployed runs.

Public Properties

deployable : CI<udm.Deployable>
The deployable that this deployed is derived from.

Hidden Properties

* **createOrder** : INTEGER = 60
The order in which a create step will be executed.

* **createVerb** : STRING = Create
The word that is used to prefix a step description for the create operation.

* **destroyOrder** : INTEGER = 40
The order in which a destroy step will be executed.

* **destroyVerb** : STRING = Destroy
The word that is used to prefix a step description for the destroy operation.

* **discoverOrder** : INTEGER = 50
The order in which a discover step will be executed.

* **modifyOrder** : INTEGER = 60
The order in which a modify step will be executed.

* **modifyVerb** : STRING = Modify
The word that is used to prefix a step description for the modify operation.

* **standardPropertiesNotToExpose** : STRING = id, type, properties, deployable, container, createOrder, createScript, createVerb, syncAfterCreateOrder, modifyOrder, modifyScript, modifyVerb, syncAfterModifyOrder, destroyOrder, destroyScript, securityPermissions, inheritPermissions, exposeDeployedApplication, destroyVerb, syncAfterDestroyOrder, startOrder, startScript, startVerb, stopOrder, stopScript, stopVerb, discoverScript, inspectScript, discoverOrder, libraryScripts
Standard properties that are not exposed to any python wsadmin script.

* **startOrder** : INTEGER = 50
The order in which a start step will be executed.

* **startVerb** : STRING = Start
The word that is used to prefix a step description for the start operation.

* **stopOrder** : INTEGER = 50
The order in which a stop step will be executed.

* **stopVerb** : STRING = Stop
The word that is used to prefix a step description for the stop operation.

* **syncAfterCreateOrder** : INTEGER = 65
The order in which a synchronize after create step will be executed.

* **syncAfterDestroyOrder** : INTEGER = 45
The order in which a synchronize after destroy step will be executed.

* **syncAfterModifyOrder** : INTEGER = 65
The order in which a synchronize after modify step will be executed.

createScript : STRING
Python script invoked to deploy a Java EE artifact or create a Java EE resource

destroyScript : STRING
Python script invoked to undeploy a Java EE artifact or destroy a Java EE resource

exposeDeployedApplication : BOOLEAN = false
flag to indicate whether the deployed application CI is to be injected to the python script execution context.

libraryScripts : LIST_OF_STRING
List of scripts to appended to the the deployeds runtime script

modifyScript : STRING
Python script invoked to upgrade a Java EE artifact or modify a Java EE resource

startScript : STRING
Python script invoked to start a Java EE artifact or Java EE resource

stopScript : STRING
Python script invoked to stop a Java EE artifact or Java EE resource

was.JaasAlias

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Type Hierarchy was.Resource >> was.ExtensibleDeployedResource >> was.ExtensibleDeployed >> python.PythonManagedDeployed >> udm.BaseDeployed >> udm.BaseConfigurationItem

Interfaces udm.Deployed, udm.ConfigurationItem

Description unavailable

Parent	
*	**container** : CI<udm.Container> The container on which this deployed runs.
Public Properties	
*	**password** : STRING Password
*	**username** : STRING Username
	deployable : CI<udm.Deployable> The deployable that this deployed is derived from.

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Hidden Properties

* **createOrder** : INTEGER = 58
  The order in which a create step will be executed.
* **createScript** : STRING = was/jaas/create-jaas-alias.py
  Create Script
* **createVerb** : STRING = Create
  The word that is used to prefix a step description for the create operation.
* **destroyOrder** : INTEGER = 41
  The order in which a destroy step will be executed.
* **destroyScript** : STRING = was/jaas/destroy-jaas-alias.py
  Destroy Script
* **destroyVerb** : STRING = Destroy
  The word that is used to prefix a step description for the destroy operation.
* **discoverOrder** : INTEGER = 50
  The order in which a discover step will be executed.
* **discoverScript** : STRING = was/jaas/discover-jaas-alias.py
  Discover Script
* **modifyOrder** : INTEGER = 60
  The order in which a modify step will be executed.
* **modifyVerb** : STRING = Modify
  The word that is used to prefix a step description for the modify operation.
* **standardPropertiesNotToExpose** : STRING = id, type, properties, deployable, container, createOrder, createScript, createVerb, syncAfterCreateOrder, modifyOrder, modifyScript, modifyVerb, syncAfterModifyOrder, destroyOrder, destroyScript, securityPermissions, inheritPermissions, exposeDeployedApplication, destroyVerb, syncAfterDestroyOrder, startOrder, startScript, startVerb, stopOrder, stopScript, stopVerb, discoverScript, inspectScript, discoverOrder, libraryScripts
  Standard properties that are not exposed to any python wsadmin script.
* **startOrder** : INTEGER = 50
  The order in which a start step will be executed.
* **startVerb** : STRING = Start
  The word that is used to prefix a step description for the start operation.
* **stopOrder** : INTEGER = 50
  The order in which a stop step will be executed.
* **stopVerb** : STRING = Stop
  The word that is used to prefix a step description for the stop operation.
* **syncAfterCreateOrder** : INTEGER = 65
  The order in which a synchronize after create step will be executed.
* **syncAfterDestroyOrder** : INTEGER = 45
  The order in which a synchronize after destroy step will be executed.
* **syncAfterModifyOrder** : INTEGER = 65
  The order in which a synchronize after modify step will be executed.

exposeDeployedApplication : BOOLEAN = false
flag to indicate whether the deployed application CI is to be injected to the python script execution context.

libraryScripts : LIST_OF_STRING
List of scripts to appended to the the deployeds runtime script

modifyScript : STRING
Python script invoked to upgrade a Java EE artifact or modify a Java EE resource

startScript : STRING
Python script invoked to start a Java EE artifact or Java EE resource

stopScript : STRING
Python script invoked to stop a Java EE artifact or Java EE resource

was.JaasAliasSpec

Type Hierarchy was.Deployable >> udm.BaseDeployable >> udm.BaseConfigurationItem
Interfaces udm.Taggable, udm.Deployable, udm.ConfigurationItem

Description unavailable (deployable)

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Public Properties	
	password : STRING Password (string)
	tags : SET_OF_STRING If set, this deployable will only be mapped automatically to containers with the same tag.
	username : STRING Username (string)

was.JdbcProvider

Type Hierarchy	was.Resource >> was.ExtensibleDeployedResource >> was.ExtensibleDeployed >> python.PythonManagedDeployed >> udm.BaseDeployed >> udm.BaseConfigurationItem
Interfaces	udm.Deployed, udm.ConfigurationItem

Description unavailable

Parent	
*	**container** : CI<udm.Container> The container on which this deployed runs.
Public Properties	
*	**classpath** : STRING A list of paths or JAR file names which together form the location for the resource provider classes
	deployable : CI<udm.Deployable> The deployable that this deployed is derived from.
	description : STRING A description of the resource adapter.
	implementationClassName : STRING Specifies the Java class name of the JDBC driver's datasource implementation
	isolatedClassLoader : BOOLEAN If selected, this resource provider will be loaded in its own class loader
	nativepath : STRING An optional path to any native libraries
	providerType : STRING You can select the Show Deprecated option as an alternative to the specific provider type choices
	xa : BOOLEAN Select XA datasource if your application requires two-phase commit transactions.

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Hidden Properties

* **additionalPropertiesNotToExpose** : STRING = containerRestartRequired
  Additional Properties Not To Expose
* **createOrder** : INTEGER = 58
  The order in which a create step will be executed.
* **createScript** : STRING = was/JdbcProvider/create-jdbc-provider.py
  Create Script
* **createVerb** : STRING = Create
  The word that is used to prefix a step description for the create operation.
* **destroyOrder** : INTEGER = 42
  The order in which a destroy step will be executed.
* **destroyScript** : STRING = was/JdbcProvider/destroy-jdbc-provider.py
  Destroy Script
* **destroyVerb** : STRING = Destroy
  The word that is used to prefix a step description for the destroy operation.
* **discoverOrder** : INTEGER = 45
  Discover Order
* **discoverScript** : STRING = was/JdbcProvider/discover-inspect-jdbc-provider.py
  Discover Script
* **modifyOrder** : INTEGER = 60
  The order in which a modify step will be executed.
* **modifyVerb** : STRING = Modify
  The word that is used to prefix a step description for the modify operation.
* **standardPropertiesNotToExpose** : STRING = id, type, properties, deployable, container, createOrder, createScript, createVerb, syncAfterCreateOrder, modifyOrder, modifyScript, modifyVerb, syncAfterModifyOrder, destroyOrder, destroyScript, securityPermissions, inheritPermissions, exposeDeployedApplication, destroyVerb, syncAfterDestroyOrder, startOrder, startScript, startVerb, stopOrder, stopScript, stopVerb, discoverScript, inspectScript, discoverOrder, libraryScripts
  Standard properties that are not exposed to any python wsadmin script.
* **startOrder** : INTEGER = 50
  The order in which a start step will be executed.
* **startVerb** : STRING = Start
  The word that is used to prefix a step description for the start operation.
* **stopOrder** : INTEGER = 50
  The order in which a stop step will be executed.
* **stopVerb** : STRING = Stop
  The word that is used to prefix a step description for the stop operation.
* **syncAfterCreateOrder** : INTEGER = 65
  The order in which a synchronize after create step will be executed.
* **syncAfterDestroyOrder** : INTEGER = 45
  The order in which a synchronize after destroy step will be executed.
* **syncAfterModifyOrder** : INTEGER = 65
  The order in which a synchronize after modify step will be executed.

containerRestartRequired : BOOLEAN = true
Container Restart Required

exposeDeployedApplication : BOOLEAN = false
flag to indicate whether the deployed application CI is to be injected to the python script execution context.

libraryScripts : LIST_OF_STRING
List of scripts to appended to the the deployeds runtime script

modifyScript : STRING
Python script invoked to upgrade a Java EE artifact or modify a Java EE resource

startScript : STRING
Python script invoked to start a Java EE artifact or Java EE resource

stopScript : STRING
Python script invoked to stop a Java EE artifact or Java EE resource

was.JdbcProviderSpec

Type Hierarchy was.Deployable >> udm.BaseDeployable >> udm.BaseConfigurationItem
Interfaces udm.Taggable, udm.Deployable, udm.ConfigurationItem

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Description unavailable (deployable)

Public Properties
classpath : STRING A list of paths or JAR file names which together form the location for the resource provider classes (string)
description : STRING A description of the resource adapter. (string)
implementationClassName : STRING Specifies the Java class name of the JDBC driver's datasource implementation (string)
isolatedClassLoader : STRING If selected, this resource provider will be loaded in its own class loader (boolean)
nativepath : STRING An optional path to any native libraries (string)
providerType : STRING You can select the Show Deprecated option as an alternative to the specific provider type choices (string)
tags : SET_OF_STRING If set, this deployable will only be mapped automatically to containers with the same tag.
xa : STRING Select XA datasource if your application requires two-phase commit transactions. (boolean)

was.JmsResource

Virtual Type	
Type Hierarchy	was.Resource >> was.ExtensibleDeployedResource >> was.ExtensibleDeployed >> python.PythonManagedDeployed >> udm.BaseDeployed >> udm.BaseConfigurationItem
Interfaces	udm.Deployed, udm.ConfigurationItem

Base class for all deployed JMS resource configuration items.

Parent
* **container** : CI<udm.Container> The container on which this deployed runs.

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Hidden Properties

* **additionalPropertiesNotToExpose** : STRING = jmsProvider, wasType
  Properties that are not exposed to any python wsadmin script.
* **createOrder** : INTEGER = 60
  The order in which a create step will be executed.
* **createScript** : STRING = was/jms/create-jms-object.py
  Python wsadmin script invoked to create a JMS resource.
* **createVerb** : STRING = Create
  The word that is used to prefix a step description for the create operation.
* **destroyOrder** : INTEGER = 40
  The order in which a destroy step will be executed.
* **destroyScript** : STRING = was/jms/destroy-jms-object.py
  Python wsadmin script invoked to destroy a JMS resource.
* **destroyVerb** : STRING = Destroy
  The word that is used to prefix a step description for the destroy operation.
* **discoverOrder** : INTEGER = 50
  The order in which a discover step will be executed.
* **discoverScript** : STRING = was/jms/discover-inspect-jms-objects.py
  Python wsadmin script invoked to inspect a JMS resource.
* **libraryScripts** : LIST_OF_STRING = [was/jms/discover-inspect-jms-objects-lib.py]
  Additional scripts to be included in the runtime
* **modifyOrder** : INTEGER = 60
  The order in which a modify step will be executed.
* **modifyVerb** : STRING = Modify
  The word that is used to prefix a step description for the modify operation.
* **standardPropertiesNotToExpose** : STRING = id, type, properties, deployable, container, createOrder, createScript, createVerb, syncAfterCreateOrder, modifyOrder, modifyScript, modifyVerb, syncAfterModifyOrder, destroyOrder, destroyScript, securityPermissions, inheritPermissions, exposeDeployedApplication, destroyVerb, syncAfterDestroyOrder, startOrder, startScript, startVerb, stopOrder, stopScript, stopVerb, discoverScript, inspectScript, discoverOrder, libraryScripts
  Standard properties that are not exposed to any python wsadmin script.
* **startOrder** : INTEGER = 50
  The order in which a start step will be executed.
* **startVerb** : STRING = Start
  The word that is used to prefix a step description for the start operation.
* **stopOrder** : INTEGER = 50
  The order in which a stop step will be executed.
* **stopVerb** : STRING = Stop
  The word that is used to prefix a step description for the stop operation.
* **syncAfterCreateOrder** : INTEGER = 65
  The order in which a synchronize after create step will be executed.
* **syncAfterDestroyOrder** : INTEGER = 45
  The order in which a synchronize after destroy step will be executed.
* **syncAfterModifyOrder** : INTEGER = 65
  The order in which a synchronize after modify step will be executed.

exposeDeployedApplication : BOOLEAN = false
flag to indicate whether the deployed application CI is to be injected to the python script execution context.

modifyScript : STRING
Python script invoked to upgrade a Java EE artifact or modify a Java EE resource

startScript : STRING
Python script invoked to start a Java EE artifact or Java EE resource

stopScript : STRING
Python script invoked to stop a Java EE artifact or Java EE resource

was.ManagedServer

Type Hierarchy	udm.BaseContainer >> udm.BaseConfigurationItem
Interfaces	udm.Taggable, was.WasAppContainer, was.Server, python.PythonManagedContainer, was.WasContainer, udm.ConfigurationItem, udm.Container, overthere.HostContainer

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

A WebSphere server managed by a node that is part of a deployment manager (WAS ND)

Parent	
*	**node** : CI<was.NodeAgent > Node on which the server runs
Public Properties	
	tags : SET_OF_STRING If set, only deployables with the same tag will be automatically mapped to this container.

was.ManagedWebServer

Type Hierarchy	udm.BaseConfigurationItem
Interfaces	udm.ConfigurationItem

An HTTP server managed by a node that is part of a deployment manager (WAS ND)

Parent	
*	**node** : CI<was.Node> Node on which the http server runs

was.Module

Virtual Type	
Type Hierarchy	was.ExtensibleDeployedArtifact >> was.ExtensibleDeployed >> python.PythonManagedDeployed >> udm.BaseDeployed >> udm.BaseConfigurationItem
Interfaces	udm.Artifact, udm.Deployed, udm.ConfigurationItem, udm.DerivedArtifact

Base class for all deployed JEE module configuration items.

Parent	
*	**container** : CI<udm.Container> The container on which this deployed runs.
Public Properties	
	deployable : CI<udm.Deployable> The deployable that this deployed is derived from.
	placeholders : MAP_STRING_STRING A Map containing all the placeholders mapped to their values. Special values are or
	roleMappings : MAP_STRING_STRING Security role to user/group mapping
	sharedLibraries : SET_OF_CI<was.SharedLibrary > Shared libraries used by this application
	startingWeight : INTEGER = 1 Specifies the order in which modules are started when the server starts. The module with the lowest starting weight is started first.

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Hidden Properties

* **createOrder** : INTEGER = 70
  The order in which a create step will be executed.
* **createScript** : STRING = was/application/deploy-application.py
  Python wsadmin script invoked to create a Java EE artifact.
* **createVerb** : STRING = Deploy
  The word is used to prefix a step description for the create operation.
* **destroyOrder** : INTEGER = 30
  The order in which a destroy step will be executed.
* **destroyScript** : STRING = was/application/undeploy-application.py
  Python wsadmin script invoked to destroy a Java EE artifact.
* **destroyVerb** : STRING = Undeploy
  The word is used to prefix a step description for the destroy operation.
* **discoverOrder** : INTEGER = 50
  The order in which a discover step will be executed.
* **libraryScripts** : LIST_OF_STRING = [was/application/discover-app-module-lib.py]
  Additional scripts to be included in the runtime
* **modifyOrder** : INTEGER = 70
  The order in which a modify step will be executed.
* **modifyVerb** : STRING = Upgrade
  The word is used to prefix a step description for the modify operation.
* **standardPropertiesNotToExpose** : STRING = id, type, properties, deployable, container, createOrder, createScript, createVerb, syncAfterCreateOrder, modifyOrder, modifyScript, modifyVerb, syncAfterModifyOrder, destroyOrder, destroyScript, securityPermissions, inheritPermissions, exposeDeployedApplication, destroyVerb, syncAfterDestroyOrder, startOrder, startScript, startVerb, stopOrder, stopScript, stopVerb, discoverScript, inspectScript, discoverOrder, libraryScripts
  Standard properties that are not exposed to any python wsadmin script.
* **startOrder** : INTEGER = 90
  The order in which a start step will be executed.
* **startScript** : STRING = was/application/start-application.py
  Python wsadmin script invoked to start running a Java EE artifact
* **startVerb** : STRING = Start
  The word that is used to prefix a step description for the start operation.
* **stopOrder** : INTEGER = 10
  The order in which a stop step will be executed.
* **stopScript** : STRING = was/application/stop-application.py
  Python wsadmin script invoked to stop running a Java EE artifact.
* **stopVerb** : STRING = Stop
  The word that is used to prefix a step description for the stop operation.
* **syncAfterCreateOrder** : INTEGER = 75
  The order in which a synchronize after create step will be executed.
* **syncAfterDestroyOrder** : INTEGER = 35
  Sync After Destroy Order
* **syncAfterModifyOrder** : INTEGER = 75
  The order in which a synchronize after modify step will be executed.

exposeDeployedApplication : BOOLEAN = false
flag to indicate whether the deployed application CI is to be injected to the python script execution context.

modifyScript : STRING
Python script invoked to upgrade a Java EE artifact or modify a Java EE resource

was.NodeAgent

Type Hierarchy	udm.BaseContainer >> udm.BaseConfigurationItem
Interfaces	udm.Taggable, python.PythonManagedContainer, was.WasContainer, udm.ConfigurationItem, was.Node, udm.Container, overthere.HostContainer

A WebSphere node agent.

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Parent	
*	**cell** : CI<was.DeploymentManager > Deployment manager that manages this node agent
Children	
	servers : SET_OF_CI<was.ManagedServer > WebSphere servers in the node
	webServers : SET_OF_CI<was.ManagedWebServer > WebSphere web servers in the node
Public Properties	
	tags : SET_OF_STRING If set, only deployables with the same tag will be automatically mapped to this container.
Hidden Properties	
*	**synchronizeScript** : STRING = was/base/synchronize-node.py Synchronize Script

was.OracleDatasource

Type Hierarchy	was.Datasource >> was.Resource >> was.ExtensibleDeployedResource >> was.ExtensibleDeployed >> python.PythonManagedDeployed >> udm.BaseDeployed >> udm.BaseConfigurationItem
Interfaces	udm.Deployed, udm.ConfigurationItem

Oracle data source object supplies your application with connections for accessing the database.

Parent	
*	**container** : CI<udm.Container> The container on which this deployed runs.
Public Properties	
*	**URL** : STRING JDBC URL
*	**datasourceHelperClassname** : STRING = com.ibm.websphere.rsadapter.OracleDataStoreHelper Datasource Helper Classname
*	**jdbcProvider** : STRING Name of the JDBC Provider for this data source
*	**jndiName** : STRING JNDI name of the data source
*	**password** : STRING Password to use when connecting to the data source
*	**username** : STRING Username to use when connecting to the data source
	ConnectionPool_connectionTimeout : INTEGER Connection timeout value for a JDBC data source.
	ConnectionPool_maxConnections : INTEGER Maximum number of connections for a JDBC data source.
	ConnectionPool_minConnections : INTEGER Minimum number of connections for a JDBC data source.
	deployable : CI<udm.Deployable> The deployable that this deployed is derived from.
	description : STRING Description of this data source

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Hidden Properties	
*	**additionalPropertiesNotToExpose** : STRING = jndiName, jdbcProvider, datasourceHelperClassname, username, password, ConnectionPool Properties that are not exposed to any python wsadmin script.
*	**createOrder** : INTEGER = 60 The order in which a create step will be executed.
*	**createScript** : STRING = was/datasource/create-datasource.py Python wsadmin script invoked to create a JDBC data source.
*	**createVerb** : STRING = Create The word that is used to prefix a step description for the create operation.
*	**destroyOrder** : INTEGER = 40 The order in which a destroy step will be executed.
*	**destroyScript** : STRING = was/datasource/destroy-datasource.py Python wsadmin script invoked to destroy a JDBC data source.
*	**destroyVerb** : STRING = Destroy The word that is used to prefix a step description for the destroy operation.
*	**discoverOrder** : INTEGER = 50 The order in which a discover step will be executed.
*	**discoverScript** : STRING = was/datasource/discover-inspect-ora-datasources.py Python wsadmin script invoked to discover a JDBC data sources.
*	**libraryScripts** : LIST_OF_STRING = [was/datasource/discover-inspect-datasource-lib.py] Additional scripts to be included in the runtime
*	**modifyOrder** : INTEGER = 60 The order in which a modify step will be executed.
*	**modifyVerb** : STRING = Modify The word that is used to prefix a step description for the modify operation.
*	**standardPropertiesNotToExpose** : STRING = id, type, properties, deployable, container, createOrder, createScript, createVerb, syncAfterCreateOrder, modifyOrder, modifyScript, modifyVerb, syncAfterModifyOrder, destroyOrder, destroyScript, securityPermissions, inheritPermissions, exposeDeployedApplication, destroyVerb, syncAfterDestroyOrder, startOrder, startScript, startVerb, stopOrder, stopScript, stopVerb, discoverScript, inspectScript, discoverOrder, libraryScripts Standard properties that are not exposed to any python wsadmin script.
*	**startOrder** : INTEGER = 50 The order in which a start step will be executed.
*	**startVerb** : STRING = Start The word that is used to prefix a step description for the start operation.
*	**stopOrder** : INTEGER = 50 The order in which a stop step will be executed.
*	**stopVerb** : STRING = Stop The word that is used to prefix a step description for the stop operation.
*	**syncAfterCreateOrder** : INTEGER = 65 The order in which a synchronize after create step will be executed.
*	**syncAfterDestroyOrder** : INTEGER = 45 The order in which a synchronize after destroy step will be executed.
*	**syncAfterModifyOrder** : INTEGER = 65 The order in which a synchronize after modify step will be executed.
	exposeDeployedApplication : BOOLEAN = false flag to indicate whether the deployed application CI is to be injected to the python script execution context.
	modifyScript : STRING Python script invoked to upgrade a Java EE artifact or modify a Java EE resource
	startScript : STRING Python script invoked to start a Java EE artifact or Java EE resource
	stopScript : STRING Python script invoked to stop a Java EE artifact or Java EE resource

was.OracleDatasourceSpec

Type Hierarchy	jee.DataSourceSpec >> jee.JndiResourceSpec >> jee.ResourceSpec >> udm.BaseDeployable >> udm.BaseConfigurationItem
Interfaces	udm.Taggable, udm.Deployable, udm.ConfigurationItem

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Specification for an Oracle datasource

Public Properties
ConnectionPool_connectionTimeout : STRING Connection timeout value for a JDBC data source. (integer)
ConnectionPool_maxConnections : STRING Maximum number of connections for a JDBC data source. (integer)
ConnectionPool_minConnections : STRING Minimum number of connections for a JDBC data source. (integer)
URL : STRING JDBC URL (string)
datasourceHelperClassname : STRING Datasource Helper Classname (string)
description : STRING Description of this data source (string)
jdbcProvider : STRING Name of the JDBC Provider for this data source (string)
jndiName : STRING JNDI name of the data source (string)
password : STRING Password to use when connecting to the data source (string)
tags : SET_OF_STRING If set, this deployable will only be mapped automatically to containers with the same tag.
username : STRING Username to use when connecting to the data source (string)

was.OracleJdbcProvider

Type Hierarchy	was.JdbcProvider >> was.Resource >> was.ExtensibleDeployedResource >> was.ExtensibleDeployed >> python.PythonManagedDeployed >> udm.BaseDeployed >> udm.BaseConfigurationItem
Interfaces	udm.Deployed, udm.ConfigurationItem

Description unavailable

Parent
* **container** : CI<udm.Container> The container on which this deployed runs.

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Hidden Properties

* **additionalPropertiesNotToExpose** : STRING = containerRestartRequired
  Additional Properties Not To Expose

* **createOrder** : INTEGER = 58
  The order in which a create step will be executed.

* **createScript** : STRING = was/JdbcProvider/create-jdbc-provider.py
  Create Script

* **createVerb** : STRING = Create
  The word that is used to prefix a step description for the create operation.

* **destroyOrder** : INTEGER = 42
  The order in which a destroy step will be executed.

* **destroyScript** : STRING = was/JdbcProvider/destroy-jdbc-provider.py
  Destroy Script

* **destroyVerb** : STRING = Destroy
  The word that is used to prefix a step description for the destroy operation.

* **discoverOrder** : INTEGER = 45
  Discover Order

* **discoverScript** : STRING = was/JdbcProvider/discover-inspect-jdbc-provider.py
  Discover Script

* **modifyOrder** : INTEGER = 60
  The order in which a modify step will be executed.

* **modifyVerb** : STRING = Modify
  The word that is used to prefix a step description for the modify operation.

* **standardPropertiesNotToExpose** : STRING = id, type, properties, deployable, container, createOrder, createScript, createVerb, syncAfterCreateOrder, modifyOrder, modifyScript, modifyVerb, syncAfterModifyOrder, destroyOrder, destroyScript, securityPermissions, inheritPermissions, exposeDeployedApplication, destroyVerb, syncAfterDestroyOrder, startOrder, startScript, startVerb, stopOrder, stopScript, stopVerb, discoverScript, inspectScript, discoverOrder, libraryScripts
  Standard properties that are not exposed to any python wsadmin script.

* **startOrder** : INTEGER = 50
  The order in which a start step will be executed.

* **startVerb** : STRING = Start
  The word that is used to prefix a step description for the start operation.

* **stopOrder** : INTEGER = 50
  The order in which a stop step will be executed.

* **stopVerb** : STRING = Stop
  The word that is used to prefix a step description for the stop operation.

* **syncAfterCreateOrder** : INTEGER = 65
  The order in which a synchronize after create step will be executed.

* **syncAfterDestroyOrder** : INTEGER = 45
  The order in which a synchronize after destroy step will be executed.

* **syncAfterModifyOrder** : INTEGER = 65
  The order in which a synchronize after modify step will be executed.

containerRestartRequired : BOOLEAN = true
Container Restart Required

exposeDeployedApplication : BOOLEAN = false
flag to indicate whether the deployed application CI is to be injected to the python script execution context.

libraryScripts : LIST_OF_STRING
List of scripts to appended to the the deployeds runtime script

modifyScript : STRING
Python script invoked to upgrade a Java EE artifact or modify a Java EE resource

startScript : STRING
Python script invoked to start a Java EE artifact or Java EE resource

stopScript : STRING
Python script invoked to stop a Java EE artifact or Java EE resource

xa : BOOLEAN = false
Connection Pool datasource if your application does not require connections that support two-phase commit transactions

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

was.OracleJdbcProviderSpec

Type Hierarchy was.JdbcProviderSpec >> was.Deployable >> udm.BaseDeployable >> udm.BaseConfigurationItem
Interfaces udm.Taggable, udm.Deployable, udm.ConfigurationItem

Description unavailable (deployable)

Public Properties

classpath : STRING
A list of paths or JAR file names which together form the location for the resource provider classes (string)

description : STRING
A description of the resource adapter. (string)

implementationClassName : STRING
Specifies the Java class name of the JDBC driver's datasource implementation (string)

isolatedClassLoader : STRING
If selected, this resource provider will be loaded in its own class loader (boolean)

nativepath : STRING
An optional path to any native libraries (string)

providerType : STRING
You can select the Show Deprecated option as an alternative to the specific provider type choices (string)

tags : SET_OF_STRING
If set, this deployable will only be mapped automatically to containers with the same tag.

xa : STRING
Select XA datasource if your application requires two-phase commit transactions. (boolean)

was.OracleXaJdbcProvider

Type Hierarchy was.JdbcProvider >> was.Resource >> was.ExtensibleDeployedResource >> was.ExtensibleDeployed >> python.PythonManagedDeployed >> udm.BaseDeployed >> udm.BaseConfigurationItem
Interfaces udm.Deployed, udm.ConfigurationItem

Description unavailable

Parent

* **container** : CI<udm.Container>
The container on which this deployed runs.

Public Properties

* **classpath** : STRING = ${ORACLE_JDBC_DRIVER_PATH}/ojdbc6.jar
A list of paths or JAR file names which together form the location for the resource provider classes

deployable : CI<udm.Deployable>
The deployable that this deployed is derived from.

description : STRING = Oracle JDBC Driver (XA)
A description of the resource adapter.

implementationClassName : STRING = oracle.jdbc.xa.client.OracleXADataSource
Specifies the Java class name of the JDBC driver's datasource implementation

isolatedClassLoader : BOOLEAN
If selected, this resource provider will be loaded in its own class loader

nativepath : STRING
An optional path to any native libraries

providerType : STRING = Oracle JDBC Driver (XA)
You can select the Show Deprecated option as an alternative to the specific provider type choices

xa : BOOLEAN = true
XA datasource if your application requires two-phase commit transactions.

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Hidden Properties

* **additionalPropertiesNotToExpose** : STRING = containerRestartRequired
  Additional Properties Not To Expose
* **createOrder** : INTEGER = 58
  The order in which a create step will be executed.
* **createScript** : STRING = was/JdbcProvider/create-jdbc-provider.py
  Create Script
* **createVerb** : STRING = Create
  The word that is used to prefix a step description for the create operation.
* **destroyOrder** : INTEGER = 42
  The order in which a destroy step will be executed.
* **destroyScript** : STRING = was/JdbcProvider/destroy-jdbc-provider.py
  Destroy Script
* **destroyVerb** : STRING = Destroy
  The word that is used to prefix a step description for the destroy operation.
* **discoverOrder** : INTEGER = 45
  Discover Order
* **discoverScript** : STRING = was/JdbcProvider/discover-inspect-jdbc-provider.py
  Discover Script
* **modifyOrder** : INTEGER = 60
  The order in which a modify step will be executed.
* **modifyVerb** : STRING = Modify
  The word that is used to prefix a step description for the modify operation.
* **standardPropertiesNotToExpose** : STRING = id, type, properties, deployable, container, createOrder, createScript, createVerb, syncAfterCreateOrder, modifyOrder, modifyScript, modifyVerb, syncAfterModifyOrder, destroyOrder, destroyScript, securityPermissions, inheritPermissions, exposeDeployedApplication, destroyVerb, syncAfterDestroyOrder, startOrder, startScript, startVerb, stopOrder, stopScript, stopVerb, discoverScript, inspectScript, discoverOrder, libraryScripts
  Standard properties that are not exposed to any python wsadmin script.
* **startOrder** : INTEGER = 50
  The order in which a start step will be executed.
* **startVerb** : STRING = Start
  The word that is used to prefix a step description for the start operation.
* **stopOrder** : INTEGER = 50
  The order in which a stop step will be executed.
* **stopVerb** : STRING = Stop
  The word that is used to prefix a step description for the stop operation.
* **syncAfterCreateOrder** : INTEGER = 65
  The order in which a synchronize after create step will be executed.
* **syncAfterDestroyOrder** : INTEGER = 45
  The order in which a synchronize after destroy step will be executed.
* **syncAfterModifyOrder** : INTEGER = 65
  The order in which a synchronize after modify step will be executed.

containerRestartRequired : BOOLEAN = true
Container Restart Required

exposeDeployedApplication : BOOLEAN = false
flag to indicate whether the deployed application CI is to be injected to the python script execution context.

libraryScripts : LIST_OF_STRING
List of scripts to appended to the the deployeds runtime script

modifyScript : STRING
Python script invoked to upgrade a Java EE artifact or modify a Java EE resource

startScript : STRING
Python script invoked to start a Java EE artifact or Java EE resource

stopScript : STRING
Python script invoked to stop a Java EE artifact or Java EE resource

was.OracleXaJdbcProviderSpec

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Type Hierarchy	was.JdbcProviderSpec >> was.Deployable >> udm.BaseDeployable >> udm.BaseConfigurationItem
Interfaces	udm.Taggable, udm.Deployable, udm.ConfigurationItem

Specification of an Oracle XA JDBC Driver.

Public Properties

classpath : STRING
A list of paths or JAR file names which together form the location for the resource provider classes (string)

description : STRING
A description of the resource adapter. (string)

implementationClassName : STRING
Specifies the Java class name of the JDBC driver's datasource implementation (string)

isolatedClassLoader : STRING
If selected, this resource provider will be loaded in its own class loader (boolean)

nativepath : STRING
An optional path to any native libraries (string)

providerType : STRING
You can select the Show Deprecated option as an alternative to the specific provider type choices (string)

tags : SET_OF_STRING
If set, this deployable will only be mapped automatically to containers with the same tag.

xa : STRING
XA datasource if your application requires two-phase commit transactions. (boolean)

was.Resource

Virtual Type	
Type Hierarchy	was.ExtensibleDeployedResource >> was.ExtensibleDeployed >> python.PythonManagedDeployed >> udm.BaseDeployed >> udm.BaseConfigurationItem
Interfaces	udm.Deployed, udm.ConfigurationItem

Base class for all deployed JEE resource configuration items.

Parent

* **container** : CI<udm.Container>
The container on which this deployed runs.

Public Properties

deployable : CI<udm.Deployable>
The deployable that this deployed is derived from.

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Hidden Properties

* **createOrder** : INTEGER = 60
  The order in which a create step will be executed.

* **createVerb** : STRING = Create
  The word that is used to prefix a step description for the create operation.

* **destroyOrder** : INTEGER = 40
  The order in which a destroy step will be executed.

* **destroyVerb** : STRING = Destroy
  The word that is used to prefix a step description for the destroy operation.

* **discoverOrder** : INTEGER = 50
  The order in which a discover step will be executed.

* **modifyOrder** : INTEGER = 60
  The order in which a modify step will be executed.

* **modifyVerb** : STRING = Modify
  The word that is used to prefix a step description for the modify operation.

* **standardPropertiesNotToExpose** : STRING = id, type, properties, deployable, container, createOrder, createScript, createVerb, syncAfterCreateOrder, modifyOrder, modifyScript, modifyVerb, syncAfterModifyOrder, destroyOrder, destroyScript, securityPermissions, inheritPermissions, exposeDeployedApplication, destroyVerb, syncAfterDestroyOrder, startOrder, startScript, startVerb, stopOrder, stopScript, stopVerb, discoverScript, inspectScript, discoverOrder, libraryScripts
  Standard properties that are not exposed to any python wsadmin script.

* **startOrder** : INTEGER = 50
  The order in which a start step will be executed.

* **startVerb** : STRING = Start
  The word that is used to prefix a step description for the start operation.

* **stopOrder** : INTEGER = 50
  The order in which a stop step will be executed.

* **stopVerb** : STRING = Stop
  The word that is used to prefix a step description for the stop operation.

* **syncAfterCreateOrder** : INTEGER = 65
  The order in which a synchronize after create step will be executed.

* **syncAfterDestroyOrder** : INTEGER = 45
  The order in which a synchronize after destroy step will be executed.

* **syncAfterModifyOrder** : INTEGER = 65
  The order in which a synchronize after modify step will be executed.

createScript : STRING
Python script invoked to deploy a Java EE artifact or create a Java EE resource

destroyScript : STRING
Python script invoked to undeploy a Java EE artifact or destroy a Java EE resource

exposeDeployedApplication : BOOLEAN = false
flag to indicate whether the deployed application CI is to be injected to the python script execution context.

libraryScripts : LIST_OF_STRING
List of scripts to appended to the the deployeds runtime script

modifyScript : STRING
Python script invoked to upgrade a Java EE artifact or modify a Java EE resource

startScript : STRING
Python script invoked to start a Java EE artifact or Java EE resource

stopScript : STRING
Python script invoked to stop a Java EE artifact or Java EE resource

was.SharedLibrary

Type Hierarchy	was.Resource >> was.ExtensibleDeployedResource >> was.ExtensibleDeployed >> python.PythonManagedDeployed >> udm.BaseDeployed >> udm.BaseConfigurationItem
Interfaces	udm.Deployed, udm.ConfigurationItem

Container-wide shared library that can be used by deployed applications

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Parent	
*	**container** : CI<udm.Container> The container on which this deployed runs.
Public Properties	
*	**classPath** : STRING Classpath that contains the JAR files and directories
	deployable : CI<udm.Deployable> The deployable that this deployed is derived from.
	nativePath : STRING Optional path to any native libraries (DLL or SO)

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Hidden Properties

* **createOrder** : INTEGER = 60
  The order in which a create step will be executed.
* **createScript** : STRING = was/sharedlibrary/create-shared-library.py
  Python wsadmin script invoked to create a shared library.
* **createVerb** : STRING = Create
  The word that is used to prefix a step description for the create operation.
* **destroyOrder** : INTEGER = 40
  The order in which a destroy step will be executed.
* **destroyScript** : STRING = was/sharedlibrary/destroy-shared-library.py
  Python wsadmin script invoked to destroy a shared library.
* **destroyVerb** : STRING = Destroy
  The word that is used to prefix a step description for the destroy operation.
* **discoverOrder** : INTEGER = 45
  Discover Order
* **discoverScript** : STRING = was/sharedlibrary/discover-inspect-shared-library.py
  Python wsadmin script invoked to inspect a shared library.
* **modifyOrder** : INTEGER = 60
  The order in which a modify step will be executed.
* **modifyVerb** : STRING = Modify
  The word that is used to prefix a step description for the modify operation.
* **standardPropertiesNotToExpose** : STRING = id, type, properties, deployable, container, createOrder, createScript, createVerb, syncAfterCreateOrder, modifyOrder, modifyScript, modifyVerb, syncAfterModifyOrder, destroyOrder, destroyScript, securityPermissions, inheritPermissions, exposeDeployedApplication, destroyVerb, syncAfterDestroyOrder, startOrder, startScript, startVerb, stopOrder, stopScript, stopVerb, discoverScript, inspectScript, discoverOrder, libraryScripts
  Standard properties that are not exposed to any python wsadmin script.
* **startOrder** : INTEGER = 50
  The order in which a start step will be executed.
* **startVerb** : STRING = Start
  The word that is used to prefix a step description for the start operation.
* **stopOrder** : INTEGER = 50
  The order in which a stop step will be executed.
* **stopVerb** : STRING = Stop
  The word that is used to prefix a step description for the stop operation.
* **syncAfterCreateOrder** : INTEGER = 65
  The order in which a synchronize after create step will be executed.
* **syncAfterDestroyOrder** : INTEGER = 45
  The order in which a synchronize after destroy step will be executed.
* **syncAfterModifyOrder** : INTEGER = 65
  The order in which a synchronize after modify step will be executed.

exposeDeployedApplication : BOOLEAN = false
flag to indicate whether the deployed application CI is to be injected to the python script execution context.

libraryScripts : LIST_OF_STRING
List of scripts to appended to the the deployeds runtime script

modifyScript : STRING
Python script invoked to upgrade a Java EE artifact or modify a Java EE resource

startScript : STRING
Python script invoked to start a Java EE artifact or Java EE resource

stopScript : STRING
Python script invoked to stop a Java EE artifact or Java EE resource

was.SharedLibrarySpec

Type Hierarchy was.Deployable >> udm.BaseDeployable >> udm.BaseConfigurationItem
Interfaces udm.Taggable, udm.Deployable, udm.ConfigurationItem

Specification of a shared library.

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Public Properties	
	classPath : STRING Classpath that contains the JAR files and directories (string)
	nativePath : STRING Optional path to any native libraries (DLL or SO) (string)
	tags : SET_OF_STRING If set, this deployable will only be mapped automatically to containers with the same tag.

was.SibConnectionFactory

Virtual Type	
Type Hierarchy	was.JmsResource >> was.Resource >> was.ExtensibleDeployedResource >> was.ExtensibleDeployed >> python.PythonManagedDeployed >> udm.BaseDeployed >> udm.BaseConfigurationItem
Interfaces	udm.Deployed, udm.ConfigurationItem

Description unavailable

Parent	
*	**container** : CI<udm.Container> The container on which this deployed runs.
Public Properties	
*	**busName** : STRING Name of the bus on which the queue connection factory resides
*	**jndiName** : STRING JNDI name for the resource
	deployable : CI<udm.Deployable> The deployable that this deployed is derived from.

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Hidden Properties

* **additionalPropertiesNotToExpose** : STRING = sibType, wasType
  Properties that are not exposed to any python wsadmin script.
* **createOrder** : INTEGER = 60
  The order in which a create step will be executed.
* **createScript** : STRING = was/jms/create-sib-connection-factory.py
  Python wsadmin script invoked to create a JMS SIB queue connection factory.
* **createVerb** : STRING = Create
  The word that is used to prefix a step description for the create operation.
* **destroyOrder** : INTEGER = 40
  The order in which a destroy step will be executed.
* **destroyScript** : STRING = was/jms/destroy-sib-connection-factory.py
  Python wsadmin script invoked to destroy a JMS SIB queue connection factory.
* **destroyVerb** : STRING = Destroy
  The word that is used to prefix a step description for the destroy operation.
* **discoverOrder** : INTEGER = 50
  The order in which a discover step will be executed.
* **discoverScript** : STRING = was/jms/discover-inspect-sib-connection-factory.py
  Python wsadmin script invoked to inspect a JMS SIB queue connection factory.
* **libraryScripts** : LIST_OF_STRING = [was/jms/discover-inspect-sib-lib.py]
  Library Scripts
* **modifyOrder** : INTEGER = 60
  The order in which a modify step will be executed.
* **modifyVerb** : STRING = Modify
  The word that is used to prefix a step description for the modify operation.
* **standardPropertiesNotToExpose** : STRING = id, type, properties, deployable, container, createOrder, createScript, createVerb, syncAfterCreateOrder, modifyOrder, modifyScript, modifyVerb, syncAfterModifyOrder, destroyOrder, destroyScript, securityPermissions, inheritPermissions, exposeDeployedApplication, destroyVerb, syncAfterDestroyOrder, startOrder, startScript, startVerb, stopOrder, stopScript, stopVerb, discoverScript, inspectScript, discoverOrder, libraryScripts
  Standard properties that are not exposed to any python wsadmin script.
* **startOrder** : INTEGER = 50
  The order in which a start step will be executed.
* **startVerb** : STRING = Start
  The word that is used to prefix a step description for the start operation.
* **stopOrder** : INTEGER = 50
  The order in which a stop step will be executed.
* **stopVerb** : STRING = Stop
  The word that is used to prefix a step description for the stop operation.
* **syncAfterCreateOrder** : INTEGER = 65
  The order in which a synchronize after create step will be executed.
* **syncAfterDestroyOrder** : INTEGER = 45
  The order in which a synchronize after destroy step will be executed.
* **syncAfterModifyOrder** : INTEGER = 65
  The order in which a synchronize after modify step will be executed.

exposeDeployedApplication : BOOLEAN = false
flag to indicate whether the deployed application CI is to be injected to the python script execution context.

modifyScript : STRING
Python script invoked to upgrade a Java EE artifact or modify a Java EE resource

startScript : STRING
Python script invoked to start a Java EE artifact or Java EE resource

stopScript : STRING
Python script invoked to stop a Java EE artifact or Java EE resource

was.SibDestination

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Virtual Type

Type Hierarchy was.Resource >> was.ExtensibleDeployedResource >> was.ExtensibleDeployed >> python.PythonManagedDeployed >> udm.BaseDeployed >> udm.BaseConfigurationItem

Interfaces udm.Deployed, udm.ConfigurationItem

Base class for all deployed SIB destionation configuration items.

Parent

* **container** : CI<udm.Container>
The container on which this deployed runs.

Public Properties

deployable : CI<udm.Deployable>
The deployable that this deployed is derived from.

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Hidden Properties

* **additionalPropertiesNotToExpose** : STRING = sibType, busName
  Properties that are not exposed to any python wsadmin script.

* **createOrder** : INTEGER = 58
  The order in which a create step will be executed.

* **createVerb** : STRING = Create
  The word that is used to prefix a step description for the create operation.

* **destroyOrder** : INTEGER = 42
  The order in which a destroy step will be executed.

* **destroyVerb** : STRING = Destroy
  The word that is used to prefix a step description for the destroy operation.

* **discoverOrder** : INTEGER = 45
  Discover Order

* **libraryScripts** : LIST_OF_STRING = [was/jms/discover-inspect-sib-lib.py]
  Library Scripts

* **modifyOrder** : INTEGER = 60
  The order in which a modify step will be executed.

* **modifyVerb** : STRING = Modify
  The word that is used to prefix a step description for the modify operation.

* **standardPropertiesNotToExpose** : STRING = id, type, properties, deployable, container, createOrder, createScript, createVerb, syncAfterCreateOrder, modifyOrder, modifyScript, modifyVerb, syncAfterModifyOrder, destroyOrder, destroyScript, securityPermissions, inheritPermissions, exposeDeployedApplication, destroyVerb, syncAfterDestroyOrder, startOrder, startScript, startVerb, stopOrder, stopScript, stopVerb, discoverScript, inspectScript, discoverOrder, libraryScripts
  Standard properties that are not exposed to any python wsadmin script.

* **startOrder** : INTEGER = 50
  The order in which a start step will be executed.

* **startVerb** : STRING = Start
  The word that is used to prefix a step description for the start operation.

* **stopOrder** : INTEGER = 50
  The order in which a stop step will be executed.

* **stopVerb** : STRING = Stop
  The word that is used to prefix a step description for the stop operation.

* **syncAfterCreateOrder** : INTEGER = 65
  The order in which a synchronize after create step will be executed.

* **syncAfterDestroyOrder** : INTEGER = 45
  The order in which a synchronize after destroy step will be executed.

* **syncAfterModifyOrder** : INTEGER = 65
  The order in which a synchronize after modify step will be executed.

createScript : STRING
Python script invoked to deploy a Java EE artifact or create a Java EE resource

destroyScript : STRING
Python script invoked to undeploy a Java EE artifact or destroy a Java EE resource

exposeDeployedApplication : BOOLEAN = false
flag to indicate whether the deployed application CI is to be injected to the python script execution context.

modifyScript : STRING
Python script invoked to upgrade a Java EE artifact or modify a Java EE resource

startScript : STRING
Python script invoked to start a Java EE artifact or Java EE resource

stopScript : STRING
Python script invoked to stop a Java EE artifact or Java EE resource

was.SibQueue

Type Hierarchy	was.JmsResource >> was.Resource >> was.ExtensibleDeployedResource >> was.ExtensibleDeployed >> python.PythonManagedDeployed >> udm.BaseDeployed >> udm.BaseConfigurationItem
Interfaces	udm.Deployed, udm.ConfigurationItem

JMS queue is used as a destination for point-to-point messaging. Use JMS queue

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

destination administrative objects to manage JMS queues for the default messaging provider.

	Parent
*	**container** : CI<udm.Container> The container on which this deployed runs.
	Public Properties
*	**deliveryMode** : STRING = Application The delivery mode for messages. Legal values are 'Application', 'NonPersistent' and 'Persistent'
*	**jndiName** : STRING JNDI name for the resource
*	**queueName** : CI<was.SibQueueDestination > Name of the underlying SIB queue to which the queue points
	busName : STRING Name of the bus on which the queue resides
	deployable : CI<udm.Deployable> The deployable that this deployed is derived from.
	description : STRING Description of the SIB JMS queue
	timeToLive : STRING The time in milliseconds to be used for message expiration

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Hidden Properties

* **additionalPropertiesNotToExpose** : STRING = jmsProvider, wasType
  Properties that are not exposed to any python wsadmin script.
* **createOrder** : INTEGER = 60
  The order in which a create step will be executed.
* **createScript** : STRING = was/jms/create-sib-queue.py
  Python wsadmin script invoked to create a JMS SIB queue.
* **createVerb** : STRING = Create
  The word that is used to prefix a step description for the create operation.
* **destroyOrder** : INTEGER = 40
  The order in which a destroy step will be executed.
* **destroyScript** : STRING = was/jms/destroy-sib-queue-or-topic.py
  Python wsadmin script invoked to destroy a JMS SIB queue.
* **destroyVerb** : STRING = Destroy
  The word that is used to prefix a step description for the destroy operation.
* **discoverOrder** : INTEGER = 50
  The order in which a discover step will be executed.
* **discoverScript** : STRING = was/jms/discover-inspect-sib-queue.py
  Python wsadmin script invoked to inspect a JMS SIB queue.
* **libraryScripts** : LIST_OF_STRING = [was/jms/discover-inspect-sib-lib.py]
  Library Scripts
* **modifyOrder** : INTEGER = 60
  The order in which a modify step will be executed.
* **modifyVerb** : STRING = Modify
  The word that is used to prefix a step description for the modify operation.
* **standardPropertiesNotToExpose** : STRING = id, type, properties, deployable, container, createOrder, createScript, createVerb, syncAfterCreateOrder, modifyOrder, modifyScript, modifyVerb, syncAfterModifyOrder, destroyOrder, destroyScript, securityPermissions, inheritPermissions, exposeDeployedApplication, destroyVerb, syncAfterDestroyOrder, startOrder, startScript, startVerb, stopOrder, stopScript, stopVerb, discoverScript, inspectScript, discoverOrder, libraryScripts
  Standard properties that are not exposed to any python wsadmin script.
* **startOrder** : INTEGER = 50
  The order in which a start step will be executed.
* **startVerb** : STRING = Start
  The word that is used to prefix a step description for the start operation.
* **stopOrder** : INTEGER = 50
  The order in which a stop step will be executed.
* **stopVerb** : STRING = Stop
  The word that is used to prefix a step description for the stop operation.
* **syncAfterCreateOrder** : INTEGER = 65
  The order in which a synchronize after create step will be executed.
* **syncAfterDestroyOrder** : INTEGER = 45
  The order in which a synchronize after destroy step will be executed.
* **syncAfterModifyOrder** : INTEGER = 65
  The order in which a synchronize after modify step will be executed.
* **wasType** : STRING = SIBJMSQueue
  WAS config type of SIB queue.

exposeDeployedApplication : BOOLEAN = false
flag to indicate whether the deployed application CI is to be injected to the python script execution context.

modifyScript : STRING
Python script invoked to upgrade a Java EE artifact or modify a Java EE resource

startScript : STRING
Python script invoked to start a Java EE artifact or Java EE resource

stopScript : STRING
Python script invoked to stop a Java EE artifact or Java EE resource

was.SibQueueConnectionFactory

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Type Hierarchy	was.SibConnectionFactory >> was.JmsResource >> was.Resource >> was.ExtensibleDeployedResource >> was.ExtensibleDeployed >> python.PythonManagedDeployed >> udm.BaseDeployed >> udm.BaseConfigurationItem
Interfaces	udm.Deployed, udm.ConfigurationItem

JMS queue connection factory is used to create connections to the associated JMS provider of JMS queues, for point-to-point messaging. Use queue connection factory administrative objects to manage JMS queue connection factories for the default messaging provider.

Parent

* **container** : CI<udm.Container>
The container on which this deployed runs.

Public Properties

* **busName** : STRING
Name of the bus on which the queue connection factory resides

* **jndiName** : STRING
JNDI name for the resource

deployable : CI<udm.Deployable>
The deployable that this deployed is derived from.

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Hidden Properties

* **additionalPropertiesNotToExpose** : STRING = sibType, wasType
  Properties that are not exposed to any python wsadmin script.
* **createOrder** : INTEGER = 60
  The order in which a create step will be executed.
* **createScript** : STRING = was/jms/create-sib-connection-factory.py
  Python wsadmin script invoked to create a JMS SIB queue connection factory.
* **createVerb** : STRING = Create
  The word that is used to prefix a step description for the create operation.
* **destroyOrder** : INTEGER = 40
  The order in which a destroy step will be executed.
* **destroyScript** : STRING = was/jms/destroy-sib-connection-factory.py
  Python wsadmin script invoked to destroy a JMS SIB queue connection factory.
* **destroyVerb** : STRING = Destroy
  The word that is used to prefix a step description for the destroy operation.
* **discoverOrder** : INTEGER = 50
  The order in which a discover step will be executed.
* **discoverScript** : STRING = was/jms/discover-inspect-sib-connection-factory.py
  Python wsadmin script invoked to inspect a JMS SIB queue connection factory.
* **libraryScripts** : LIST_OF_STRING = [was/jms/discover-inspect-sib-lib.py]
  Library Scripts
* **modifyOrder** : INTEGER = 60
  The order in which a modify step will be executed.
* **modifyVerb** : STRING = Modify
  The word that is used to prefix a step description for the modify operation.
* **sibType** : STRING = Queue
  SIB type of SIB connection factory
* **standardPropertiesNotToExpose** : STRING = id, type, properties, deployable, container, createOrder, createScript, createVerb, syncAfterCreateOrder, modifyOrder, modifyScript, modifyVerb, syncAfterModifyOrder, destroyOrder, destroyScript, securityPermissions, inheritPermissions, exposeDeployedApplication, destroyVerb, syncAfterDestroyOrder, startOrder, startScript, startVerb, stopOrder, stopScript, stopVerb, discoverScript, inspectScript, discoverOrder, libraryScripts
  Standard properties that are not exposed to any python wsadmin script.
* **startOrder** : INTEGER = 50
  The order in which a start step will be executed.
* **startVerb** : STRING = Start
  The word that is used to prefix a step description for the start operation.
* **stopOrder** : INTEGER = 50
  The order in which a stop step will be executed.
* **stopVerb** : STRING = Stop
  The word that is used to prefix a step description for the stop operation.
* **syncAfterCreateOrder** : INTEGER = 65
  The order in which a synchronize after create step will be executed.
* **syncAfterDestroyOrder** : INTEGER = 45
  The order in which a synchronize after destroy step will be executed.
* **syncAfterModifyOrder** : INTEGER = 65
  The order in which a synchronize after modify step will be executed.
* **wasType** : STRING = SIBJMSQueueConnectionFactory
  WAS config type of SIB queue connnection factory.

exposeDeployedApplication : BOOLEAN = false
flag to indicate whether the deployed application CI is to be injected to the python script execution context.

modifyScript : STRING
Python script invoked to upgrade a Java EE artifact or modify a Java EE resource

startScript : STRING
Python script invoked to start a Java EE artifact or Java EE resource

stopScript : STRING
Python script invoked to stop a Java EE artifact or Java EE resource

was.SibQueueConnectionFactorySpec

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Type Hierarchy	jee.QueueConnectionFactorySpec >> jee.JndiResourceSpec >> jee.ResourceSpec >> udm.BaseDeployable >> udm.BaseConfigurationItem
Interfaces	udm.Taggable, udm.Deployable, udm.ConfigurationItem

Specification of a SIB queue connection factory.

Public Properties

busName : STRING
Name of the bus on which the queue connection factory resides (string)

jndiName : STRING
JNDI name for the resource (string)

tags : SET_OF_STRING
If set, this deployable will only be mapped automatically to containers with the same tag.

was.SibQueueDestination

Type Hierarchy	was.SibDestination >> was.Resource >> was.ExtensibleDeployedResource >> was.ExtensibleDeployed >> python.PythonManagedDeployed >> udm.BaseDeployed >> udm.BaseConfigurationItem
Interfaces	udm.Deployed, udm.ConfigurationItem

Queue for point-to-point messaging.

Parent

* **container** : CI<udm.Container>
The container on which this deployed runs.

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Hidden Properties

* **additionalPropertiesNotToExpose** : STRING = sibType, busName
  Properties that are not exposed to any python wsadmin script.

* **createOrder** : INTEGER = 58
  The order in which a create step will be executed.

* **createScript** : STRING = was/jms/create-sib-queue-destination.py
  Python wsadmin script invoked to create a JMS SIB queue destination.

* **createVerb** : STRING = Create
  The word that is used to prefix a step description for the create operation.

* **destroyOrder** : INTEGER = 42
  The order in which a destroy step will be executed.

* **destroyScript** : STRING = was/jms/destroy-sib-destination.py
  Python wsadmin script invoked to destroy a JMS SIB queue destination.

* **destroyVerb** : STRING = Destroy
  The word that is used to prefix a step description for the destroy operation.

* **discoverOrder** : INTEGER = 45
  Discover Order

* **discoverScript** : STRING = was/jms/discover-inspect-sib-queue-destination.py
  Discover Script

* **libraryScripts** : LIST_OF_STRING = [was/jms/discover-inspect-sib-lib.py]
  Library Scripts

* **modifyOrder** : INTEGER = 60
  The order in which a modify step will be executed.

* **modifyVerb** : STRING = Modify
  The word that is used to prefix a step description for the modify operation.

* **standardPropertiesNotToExpose** : STRING = id, type, properties, deployable, container, createOrder, createScript, createVerb, syncAfterCreateOrder, modifyOrder, modifyScript, modifyVerb, syncAfterModifyOrder, destroyOrder, destroyScript, securityPermissions, inheritPermissions, exposeDeployedApplication, destroyVerb, syncAfterDestroyOrder, startOrder, startScript, startVerb, stopOrder, stopScript, stopVerb, discoverScript, inspectScript, discoverOrder, libraryScripts
  Standard properties that are not exposed to any python wsadmin script.

* **startOrder** : INTEGER = 50
  The order in which a start step will be executed.

* **startVerb** : STRING = Start
  The word that is used to prefix a step description for the start operation.

* **stopOrder** : INTEGER = 50
  The order in which a stop step will be executed.

* **stopVerb** : STRING = Stop
  The word that is used to prefix a step description for the stop operation.

* **syncAfterCreateOrder** : INTEGER = 65
  The order in which a synchronize after create step will be executed.

* **syncAfterDestroyOrder** : INTEGER = 45
  The order in which a synchronize after destroy step will be executed.

* **syncAfterModifyOrder** : INTEGER = 65
  The order in which a synchronize after modify step will be executed.

exposeDeployedApplication : BOOLEAN = false
flag to indicate whether the deployed application CI is to be injected to the python script execution context.

modifyScript : STRING
Python script invoked to upgrade a Java EE artifact or modify a Java EE resource

startScript : STRING
Python script invoked to start a Java EE artifact or Java EE resource

stopScript : STRING
Python script invoked to stop a Java EE artifact or Java EE resource

was.SibQueueDestinationSpec

Type Hierarchy	jee.QueueSpec >> jee.JndiResourceSpec >> jee.ResourceSpec >> udm.BaseDeployable >> udm.BaseConfigurationItem
Interfaces	udm.Taggable, udm.Deployable, udm.ConfigurationItem

Specification of a SIB queue destination.

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Public Properties
busName : STRING Name of the bus on which the queue resides (string)
jndiName : STRING Name used to lookup this resource in JNDI
tags : SET_OF_STRING If set, this deployable will only be mapped automatically to containers with the same tag.

was.SibQueueSpec

Type Hierarchy	jee.QueueSpec >> jee.JndiResourceSpec >> jee.ResourceSpec >> udm.BaseDeployable >> udm.BaseConfigurationItem
Interfaces	udm.Taggable, udm.Deployable, udm.ConfigurationItem

Specification of a SIB queue.

Public Properties
busName : STRING Name of the bus on which the queue resides (string)
deliveryMode : STRING The delivery mode for messages. Legal values are 'Application', 'NonPersistent' and 'Persistent' (string)
description : STRING Description of the SIB JMS queue (string)
jndiName : STRING JNDI name for the resource (string)
tags : SET_OF_STRING If set, this deployable will only be mapped automatically to containers with the same tag.
timeToLive : STRING The time in milliseconds to be used for message expiration (string)

was.SibTopic

Type Hierarchy	was.JmsResource >> was.Resource >> was.ExtensibleDeployedResource >> was.ExtensibleDeployed >> python.PythonManagedDeployed >> udm.BaseDeployed >> udm.BaseConfigurationItem
Interfaces	udm.Deployed, udm.ConfigurationItem

JMS topic is used as a destination for publish/subscribe messaging.

Parent
* **container** : CI<udm.Container> The container on which this deployed runs.

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Hidden Properties

* **additionalPropertiesNotToExpose** : STRING = jmsProvider, wasType
  Properties that are not exposed to any python wsadmin script.
* **createOrder** : INTEGER = 60
  The order in which a create step will be executed.
* **createScript** : STRING = was/jms/create-sib-topic.py
  Python wsadmin script invoked to create a JMS SIB topic.
* **createVerb** : STRING = Create
  The word that is used to prefix a step description for the create operation.
* **destroyOrder** : INTEGER = 40
  The order in which a destroy step will be executed.
* **destroyScript** : STRING = was/jms/destroy-sib-queue-or-topic.py
  Python wsadmin script invoked to destroy a JMS SIB topic.
* **destroyVerb** : STRING = Destroy
  The word that is used to prefix a step description for the destroy operation.
* **discoverOrder** : INTEGER = 50
  The order in which a discover step will be executed.
* **discoverScript** : STRING = was/jms/discover-inspect-sib-topic.py
  Python wsadmin script invoked to inspect a JMS SIB topic.
* **libraryScripts** : LIST_OF_STRING = [was/jms/discover-inspect-sib-lib.py]
  Library Scripts
* **modifyOrder** : INTEGER = 60
  The order in which a modify step will be executed.
* **modifyVerb** : STRING = Modify
  The word that is used to prefix a step description for the modify operation.
* **standardPropertiesNotToExpose** : STRING = id, type, properties, deployable, container, createOrder, createScript, createVerb, syncAfterCreateOrder, modifyOrder, modifyScript, modifyVerb, syncAfterModifyOrder, destroyOrder, destroyScript, securityPermissions, inheritPermissions, exposeDeployedApplication, destroyVerb, syncAfterDestroyOrder, startOrder, startScript, startVerb, stopOrder, stopScript, stopVerb, discoverScript, inspectScript, discoverOrder, libraryScripts
  Standard properties that are not exposed to any python wsadmin script.
* **startOrder** : INTEGER = 50
  The order in which a start step will be executed.
* **startVerb** : STRING = Start
  The word that is used to prefix a step description for the start operation.
* **stopOrder** : INTEGER = 50
  The order in which a stop step will be executed.
* **stopVerb** : STRING = Stop
  The word that is used to prefix a step description for the stop operation.
* **syncAfterCreateOrder** : INTEGER = 65
  The order in which a synchronize after create step will be executed.
* **syncAfterDestroyOrder** : INTEGER = 45
  The order in which a synchronize after destroy step will be executed.
* **syncAfterModifyOrder** : INTEGER = 65
  The order in which a synchronize after modify step will be executed.
* **wasType** : STRING = SIBJMSTopic
  WAS config type of SIB topic.

exposeDeployedApplication : BOOLEAN = false
flag to indicate whether the deployed application CI is to be injected to the python script execution context.

modifyScript : STRING
Python script invoked to upgrade a Java EE artifact or modify a Java EE resource

startScript : STRING
Python script invoked to start a Java EE artifact or Java EE resource

stopScript : STRING
Python script invoked to stop a Java EE artifact or Java EE resource

was.SibTopicConnectionFactory

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Type Hierarchy	was.SibConnectionFactory >> was.JmsResource >> was.Resource >> was.ExtensibleDeployedResource >> was.ExtensibleDeployed >> python.PythonManagedDeployed >> udm.BaseDeployed >> udm.BaseConfigurationItem
Interfaces	udm.Deployed, udm.ConfigurationItem

JMS topic connection factory is used to create connections to the associated JMS provider of JMS topics, for publish/subscribe messaging. Use topic connection factory administrative objects to manage JMS topic connection factories for the default messaging provider.

Parent

* **container** : CI<udm.Container>
The container on which this deployed runs.

Public Properties

* **busName** : STRING
Name of the bus on which the queue connection factory resides

* **jndiName** : STRING
JNDI name for the resource

deployable : CI<udm.Deployable>
The deployable that this deployed is derived from.

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Hidden Properties

* **additionalPropertiesNotToExpose** : STRING = sibType, wasType
  Properties that are not exposed to any python wsadmin script.
* **createOrder** : INTEGER = 60
  The order in which a create step will be executed.
* **createScript** : STRING = was/jms/create-sib-connection-factory.py
  Python wsadmin script invoked to create a JMS SIB queue connection factory.
* **createVerb** : STRING = Create
  The word that is used to prefix a step description for the create operation.
* **destroyOrder** : INTEGER = 40
  The order in which a destroy step will be executed.
* **destroyScript** : STRING = was/jms/destroy-sib-connection-factory.py
  Python wsadmin script invoked to destroy a JMS SIB queue connection factory.
* **destroyVerb** : STRING = Destroy
  The word that is used to prefix a step description for the destroy operation.
* **discoverOrder** : INTEGER = 50
  The order in which a discover step will be executed.
* **discoverScript** : STRING = was/jms/discover-inspect-sib-connection-factory.py
  Python wsadmin script invoked to inspect a JMS SIB queue connection factory.
* **libraryScripts** : LIST_OF_STRING = [was/jms/discover-inspect-sib-lib.py]
  Library Scripts
* **modifyOrder** : INTEGER = 60
  The order in which a modify step will be executed.
* **modifyVerb** : STRING = Modify
  The word that is used to prefix a step description for the modify operation.
* **sibType** : STRING = Topic
  SIB type of SIB connection factory
* **standardPropertiesNotToExpose** : STRING = id, type, properties, deployable, container, createOrder, createScript, createVerb, syncAfterCreateOrder, modifyOrder, modifyScript, modifyVerb, syncAfterModifyOrder, destroyOrder, destroyScript, securityPermissions, inheritPermissions, exposeDeployedApplication, destroyVerb, syncAfterDestroyOrder, startOrder, startScript, startVerb, stopOrder, stopScript, stopVerb, discoverScript, inspectScript, discoverOrder, libraryScripts
  Standard properties that are not exposed to any python wsadmin script.
* **startOrder** : INTEGER = 50
  The order in which a start step will be executed.
* **startVerb** : STRING = Start
  The word that is used to prefix a step description for the start operation.
* **stopOrder** : INTEGER = 50
  The order in which a stop step will be executed.
* **stopVerb** : STRING = Stop
  The word that is used to prefix a step description for the stop operation.
* **syncAfterCreateOrder** : INTEGER = 65
  The order in which a synchronize after create step will be executed.
* **syncAfterDestroyOrder** : INTEGER = 45
  The order in which a synchronize after destroy step will be executed.
* **syncAfterModifyOrder** : INTEGER = 65
  The order in which a synchronize after modify step will be executed.
* **wasType** : STRING = SIBJMSTopicConnectionFactory
  WAS config type of SIB topic connnection factory.

exposeDeployedApplication : BOOLEAN = false
flag to indicate whether the deployed application CI is to be injected to the python script execution context.

modifyScript : STRING
Python script invoked to upgrade a Java EE artifact or modify a Java EE resource

startScript : STRING
Python script invoked to start a Java EE artifact or Java EE resource

stopScript : STRING
Python script invoked to stop a Java EE artifact or Java EE resource

was.SibTopicConnectionFactorySpec

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Type Hierarchy	jee.TopicConnectionFactorySpec >> jee.JndiResourceSpec >> jee.ResourceSpec >> udm.BaseDeployable >> udm.BaseConfigurationItem
Interfaces	udm.Taggable, udm.Deployable, udm.ConfigurationItem

Specification of a SIB topic connection factory.

Public Properties

busName : STRING
Name of the bus on which the queue connection factory resides (string)

jndiName : STRING
JNDI name for the resource (string)

tags : SET_OF_STRING
If set, this deployable will only be mapped automatically to containers with the same tag.

was.SibTopicSpaceDestination

Type Hierarchy	was.SibDestination >> was.Resource >> was.ExtensibleDeployedResource >> was.ExtensibleDeployed >> python.PythonManagedDeployed >> udm.BaseDeployed >> udm.BaseConfigurationItem
Interfaces	udm.Deployed, udm.ConfigurationItem

Topic space is a location for publish/subscribe messaging.

Parent

* **container** : CI<udm.Container>
The container on which this deployed runs.

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Hidden Properties

* **additionalPropertiesNotToExpose** : STRING = sibType, busName
  Properties that are not exposed to any python wsadmin script.
* **createOrder** : INTEGER = 58
  The order in which a create step will be executed.
* **createScript** : STRING = was/jms/create-sib-topic-space-destination.py
  Python wsadmin script invoked to create a JMS SIB topic space destination.
* **createVerb** : STRING = Create
  The word that is used to prefix a step description for the create operation.
* **destroyOrder** : INTEGER = 42
  The order in which a destroy step will be executed.
* **destroyScript** : STRING = was/jms/destroy-sib-destination.py
  Python wsadmin script invoked to destroy a JMS SIB topic space destination.
* **destroyVerb** : STRING = Destroy
  The word that is used to prefix a step description for the destroy operation.
* **discoverOrder** : INTEGER = 45
  Discover Order
* **discoverScript** : STRING = was/jms/discover-inspect-sib-topic-space-destination.py
  Discover Script
* **libraryScripts** : LIST_OF_STRING = [was/jms/discover-inspect-sib-lib.py]
  Library Scripts
* **modifyOrder** : INTEGER = 60
  The order in which a modify step will be executed.
* **modifyVerb** : STRING = Modify
  The word that is used to prefix a step description for the modify operation.
* **standardPropertiesNotToExpose** : STRING = id, type, properties, deployable, container, createOrder, createScript, createVerb, syncAfterCreateOrder, modifyOrder, modifyScript, modifyVerb, syncAfterModifyOrder, destroyOrder, destroyScript, securityPermissions, inheritPermissions, exposeDeployedApplication, destroyVerb, syncAfterDestroyOrder, startOrder, startScript, startVerb, stopOrder, stopScript, stopVerb, discoverScript, inspectScript, discoverOrder, libraryScripts
  Standard properties that are not exposed to any python wsadmin script.
* **startOrder** : INTEGER = 50
  The order in which a start step will be executed.
* **startVerb** : STRING = Start
  The word that is used to prefix a step description for the start operation.
* **stopOrder** : INTEGER = 50
  The order in which a stop step will be executed.
* **stopVerb** : STRING = Stop
  The word that is used to prefix a step description for the stop operation.
* **syncAfterCreateOrder** : INTEGER = 65
  The order in which a synchronize after create step will be executed.
* **syncAfterDestroyOrder** : INTEGER = 45
  The order in which a synchronize after destroy step will be executed.
* **syncAfterModifyOrder** : INTEGER = 65
  The order in which a synchronize after modify step will be executed.
* **exposeDeployedApplication** : BOOLEAN = false
  flag to indicate whether the deployed application CI is to be injected to the python script execution context.
* **modifyScript** : STRING
  Python script invoked to upgrade a Java EE artifact or modify a Java EE resource
* **startScript** : STRING
  Python script invoked to start a Java EE artifact or Java EE resource
* **stopScript** : STRING
  Python script invoked to stop a Java EE artifact or Java EE resource

was.SibTopicSpaceDestinationSpec

Type Hierarchy	jee.TopicSpec >> jee.JndiResourceSpec >> jee.ResourceSpec >> udm.BaseDeployable >> udm.BaseConfigurationItem
Interfaces	udm.Taggable, udm.Deployable, udm.ConfigurationItem

Specification of a SIB topic space destination.

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Public Properties
busName : STRING Name of the bus on which the topic resides (string)
jndiName : STRING Name used to lookup this resource in JNDI
tags : SET_OF_STRING If set, this deployable will only be mapped automatically to containers with the same tag.

was.SibTopicSpec

Type Hierarchy was.Deployable >> udm.BaseDeployable >> udm.BaseConfigurationItem
Interfaces udm.Taggable, udm.Deployable, udm.ConfigurationItem

Specification of a SIB topic.

Public Properties
busName : STRING Name of the bus on which the topic resides (string)
jndiName : STRING JNDI name for the resource (string)
tags : SET_OF_STRING If set, this deployable will only be mapped automatically to containers with the same tag.
topicName : STRING Topic to be used inside the topic space (for example, stock/IBM) (string)

was.UnmanagedServer

Type Hierarchy was.BaseCell >> udm.BaseContainer >> udm.BaseConfigurationItem
Interfaces was.WasAppContainer, udm.Taggable, python.PythonManagingContainer, was.Server, python.PythonManagedContainer, was.WasContainer, udm.ConfigurationItem, was.Cell, was.Node, udm.Container, overthere.HostContainer

An unmanaged WebSphere Applicaton Server (WAS Base/SA)

Parent
host : CI<overthere.Host> Host on which the unmanaged WAS server runs
Children
webServers : SET_OF_CI<was.ManagedWebServer > WebSphere web servers in the node

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Hidden Properties	
*	**deployedsToDiscover** : SET_OF_STRING = [was.VirtualHost, was.SharedLibrary] Deployeds To Discover
*	**inspectScript** : STRING = was/container/discover-inspect-topology.py Inspect script for Cell
	libraryScripts : LIST_OF_STRING = [was/container/discover-inspect-topology-lib.py] List of scripts to appended to runtime script
	runWithDaemon : BOOLEAN = true Set to true to execute commands with the Python daemon

was.V5DefaultQueue

Type Hierarchy	was.JmsResource >> was.Resource >> was.ExtensibleDeployedResource >> was.ExtensibleDeployed >> python.PythonManagedDeployed >> udm.BaseDeployed >> udm.BaseConfigurationItem
Interfaces	udm.Deployed, udm.ConfigurationItem

Queue destinations provided for point-to-point messaging by the internal WebSphere JMS provider. Use WebSphere Queue Destination administrative objects to manage queue destinations for the internal WebSphere JMS provider. NOTE: The queue name must also be added to the list of queue names in the configuration of the JMS server(s) where the queue is to be hosted.

Parent	
*	**container** : CI<udm.Container> The container on which this deployed runs.
Public Properties	
*	**jndiName** : STRING JNDI name for the resource
	deployable : CI<udm.Deployable> The deployable that this deployed is derived from.

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Hidden Properties

* **additionalPropertiesNotToExpose** : STRING = jmsProvider, wasType
  Properties that are not exposed to any python wsadmin script.
* **createOrder** : INTEGER = 60
  The order in which a create step will be executed.
* **createScript** : STRING = was/jms/create-jms-object.py
  Python wsadmin script invoked to create a JMS resource.
* **createVerb** : STRING = Create
  The word that is used to prefix a step description for the create operation.
* **destroyOrder** : INTEGER = 40
  The order in which a destroy step will be executed.
* **destroyScript** : STRING = was/jms/destroy-jms-object.py
  Python wsadmin script invoked to destroy a JMS resource.
* **destroyVerb** : STRING = Destroy
  The word that is used to prefix a step description for the destroy operation.
* **discoverOrder** : INTEGER = 50
  The order in which a discover step will be executed.
* **discoverScript** : STRING = was/jms/discover-inspect-jms-objects.py
  Python wsadmin script invoked to inspect a JMS resource.
* **jmsProvider** : STRING = WebSphere JMS Provider
  JMS provider for V5 default queue.
* **libraryScripts** : LIST_OF_STRING = [was/jms/discover-inspect-jms-objects-lib.py]
  Additional scripts to be included in the runtime
* **modifyOrder** : INTEGER = 60
  The order in which a modify step will be executed.
* **modifyVerb** : STRING = Modify
  The word that is used to prefix a step description for the modify operation.
* **standardPropertiesNotToExpose** : STRING = id, type, properties, deployable, container, createOrder, createScript, createVerb, syncAfterCreateOrder, modifyOrder, modifyScript, modifyVerb, syncAfterModifyOrder, destroyOrder, destroyScript, securityPermissions, inheritPermissions, exposeDeployedApplication, destroyVerb, syncAfterDestroyOrder, startOrder, startScript, startVerb, stopOrder, stopScript, stopVerb, discoverScript, inspectScript, discoverOrder, libraryScripts
  Standard properties that are not exposed to any python wsadmin script.
* **startOrder** : INTEGER = 50
  The order in which a start step will be executed.
* **startVerb** : STRING = Start
  The word that is used to prefix a step description for the start operation.
* **stopOrder** : INTEGER = 50
  The order in which a stop step will be executed.
* **stopVerb** : STRING = Stop
  The word that is used to prefix a step description for the stop operation.
* **syncAfterCreateOrder** : INTEGER = 65
  The order in which a synchronize after create step will be executed.
* **syncAfterDestroyOrder** : INTEGER = 45
  The order in which a synchronize after destroy step will be executed.
* **syncAfterModifyOrder** : INTEGER = 65
  The order in which a synchronize after modify step will be executed.
* **wasType** : STRING = WASQueue
  WAS config type of V5 default queue.

exposeDeployedApplication : BOOLEAN = false
flag to indicate whether the deployed application CI is to be injected to the python script execution context.

modifyScript : STRING
Python script invoked to upgrade a Java EE artifact or modify a Java EE resource

startScript : STRING
Python script invoked to start a Java EE artifact or Java EE resource

stopScript : STRING
Python script invoked to stop a Java EE artifact or Java EE resource

was.V5DefaultQueueConnectionFactory

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Type Hierarchy	was.JmsResource >> was.Resource >> was.ExtensibleDeployedResource >> was.ExtensibleDeployed >> python.PythonManagedDeployed >> udm.BaseDeployed >> udm.BaseConfigurationItem
Interfaces	udm.Deployed, udm.ConfigurationItem

Specifies a topic connection factory, which is used to create connections to the associated JMS provider of JMS queue destinations for point-to-point messaging. Use WebSphere queue connection factory administrative objects to manage queue connection factories for the internal WebSphere JMS provider.

Parent

* **container** : CI<udm.Container>
  The container on which this deployed runs.

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Hidden Properties

* **additionalPropertiesNotToExpose** : STRING = jmsProvider, wasType
  Properties that are not exposed to any python wsadmin script.
* **createOrder** : INTEGER = 60
  The order in which a create step will be executed.
* **createScript** : STRING = was/jms/create-jms-object.py
  Python wsadmin script invoked to create a JMS resource.
* **createVerb** : STRING = Create
  The word that is used to prefix a step description for the create operation.
* **destroyOrder** : INTEGER = 40
  The order in which a destroy step will be executed.
* **destroyScript** : STRING = was/jms/destroy-jms-object.py
  Python wsadmin script invoked to destroy a JMS resource.
* **destroyVerb** : STRING = Destroy
  The word that is used to prefix a step description for the destroy operation.
* **discoverOrder** : INTEGER = 50
  The order in which a discover step will be executed.
* **discoverScript** : STRING = was/jms/discover-inspect-jms-objects.py
  Python wsadmin script invoked to inspect a JMS resource.
* **jmsProvider** : STRING = WebSphere JMS Provider
  JMS provider for V5 default queue connection factory.
* **libraryScripts** : LIST_OF_STRING = [was/jms/discover-inspect-jms-objects-lib.py]
  Additional scripts to be included in the runtime
* **modifyOrder** : INTEGER = 60
  The order in which a modify step will be executed.
* **modifyVerb** : STRING = Modify
  The word that is used to prefix a step description for the modify operation.
* **standardPropertiesNotToExpose** : STRING = id, type, properties, deployable, container, createOrder, createScript, createVerb, syncAfterCreateOrder, modifyOrder, modifyScript, modifyVerb, syncAfterModifyOrder, destroyOrder, destroyScript, securityPermissions, inheritPermissions, exposeDeployedApplication, destroyVerb, syncAfterDestroyOrder, startOrder, startScript, startVerb, stopOrder, stopScript, stopVerb, discoverScript, inspectScript, discoverOrder, libraryScripts
  Standard properties that are not exposed to any python wsadmin script.
* **startOrder** : INTEGER = 50
  The order in which a start step will be executed.
* **startVerb** : STRING = Start
  The word that is used to prefix a step description for the start operation.
* **stopOrder** : INTEGER = 50
  The order in which a stop step will be executed.
* **stopVerb** : STRING = Stop
  The word that is used to prefix a step description for the stop operation.
* **syncAfterCreateOrder** : INTEGER = 65
  The order in which a synchronize after create step will be executed.
* **syncAfterDestroyOrder** : INTEGER = 45
  The order in which a synchronize after destroy step will be executed.
* **syncAfterModifyOrder** : INTEGER = 65
  The order in which a synchronize after modify step will be executed.
* **wasType** : STRING = WASQueueConnectionFactory
  JMS type of V5 default queue connection factory.

exposeDeployedApplication : BOOLEAN = false
flag to indicate whether the deployed application CI is to be injected to the python script execution context.

modifyScript : STRING
Python script invoked to upgrade a Java EE artifact or modify a Java EE resource

startScript : STRING
Python script invoked to start a Java EE artifact or Java EE resource

stopScript : STRING
Python script invoked to stop a Java EE artifact or Java EE resource

was.V5DefaultQueueConnectionFactorySpec

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Type Hierarchy	jee.QueueConnectionFactorySpec >> jee.JndiResourceSpec >> jee.ResourceSpec >> udm.BaseDeployable >> udm.BaseConfigurationItem
Interfaces	udm.Taggable, udm.Deployable, udm.ConfigurationItem

Specification of a V5 default queue connection factory.

Public Properties
jndiName : STRING JNDI name for the resource (string)
tags : SET_OF_STRING If set, this deployable will only be mapped automatically to containers with the same tag.

was.V5DefaultQueueSpec

Type Hierarchy	jee.QueueSpec >> jee.JndiResourceSpec >> jee.ResourceSpec >> udm.BaseDeployable >> udm.BaseConfigurationItem
Interfaces	udm.Taggable, udm.Deployable, udm.ConfigurationItem

Specification of a V5 default queue.

Public Properties
jndiName : STRING JNDI name for the resource (string)
tags : SET_OF_STRING If set, this deployable will only be mapped automatically to containers with the same tag.

was.V5DefaultTopic

Type Hierarchy	was.JmsResource >> was.Resource >> was.ExtensibleDeployedResource >> was.ExtensibleDeployed >> python.PythonManagedDeployed >> udm.BaseDeployed >> udm.BaseConfigurationItem
Interfaces	udm.Deployed, udm.ConfigurationItem

Specifies the topic destinations for publish and subscribe messaging by the internal WebSphere JMS provider. Use WebSphere topic destination administrative objects to manage topic destinations for the internal WebSphere JMS provider.

Parent
* **container** : CI<udm.Container> The container on which this deployed runs.

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Hidden Properties

* **additionalPropertiesNotToExpose** : STRING = jmsProvider, wasType
  Properties that are not exposed to any python wsadmin script.
* **createOrder** : INTEGER = 60
  The order in which a create step will be executed.
* **createScript** : STRING = was/jms/create-jms-object.py
  Python wsadmin script invoked to create a JMS resource.
* **createVerb** : STRING = Create
  The word that is used to prefix a step description for the create operation.
* **destroyOrder** : INTEGER = 40
  The order in which a destroy step will be executed.
* **destroyScript** : STRING = was/jms/destroy-jms-object.py
  Python wsadmin script invoked to destroy a JMS resource.
* **destroyVerb** : STRING = Destroy
  The word that is used to prefix a step description for the destroy operation.
* **discoverOrder** : INTEGER = 50
  The order in which a discover step will be executed.
* **discoverScript** : STRING = was/jms/discover-inspect-jms-objects.py
  Python wsadmin script invoked to inspect a JMS resource.
* **jmsProvider** : STRING = WebSphere JMS Provider
  JMS provider for V5 default topic.
* **libraryScripts** : LIST_OF_STRING = [was/jms/discover-inspect-jms-objects-lib.py]
  Additional scripts to be included in the runtime
* **modifyOrder** : INTEGER = 60
  The order in which a modify step will be executed.
* **modifyVerb** : STRING = Modify
  The word that is used to prefix a step description for the modify operation.
* **standardPropertiesNotToExpose** : STRING = id, type, properties, deployable, container, createOrder, createScript, createVerb, syncAfterCreateOrder, modifyOrder, modifyScript, modifyVerb, syncAfterModifyOrder, destroyOrder, destroyScript, securityPermissions, inheritPermissions, exposeDeployedApplication, destroyVerb, syncAfterDestroyOrder, startOrder, startScript, startVerb, stopOrder, stopScript, stopVerb, discoverScript, inspectScript, discoverOrder, libraryScripts
  Standard properties that are not exposed to any python wsadmin script.
* **startOrder** : INTEGER = 50
  The order in which a start step will be executed.
* **startVerb** : STRING = Start
  The word that is used to prefix a step description for the start operation.
* **stopOrder** : INTEGER = 50
  The order in which a stop step will be executed.
* **stopVerb** : STRING = Stop
  The word that is used to prefix a step description for the stop operation.
* **syncAfterCreateOrder** : INTEGER = 65
  The order in which a synchronize after create step will be executed.
* **syncAfterDestroyOrder** : INTEGER = 45
  The order in which a synchronize after destroy step will be executed.
* **syncAfterModifyOrder** : INTEGER = 65
  The order in which a synchronize after modify step will be executed.
* **wasType** : STRING = WASTopic
  WAS config type of V5 default topic.

exposeDeployedApplication : BOOLEAN = false
flag to indicate whether the deployed application CI is to be injected to the python script execution context.

modifyScript : STRING
Python script invoked to upgrade a Java EE artifact or modify a Java EE resource

startScript : STRING
Python script invoked to start a Java EE artifact or Java EE resource

stopScript : STRING
Python script invoked to stop a Java EE artifact or Java EE resource

was.V5DefaultTopicConnectionFactory

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Type Hierarchy	was.JmsResource >> was.Resource >> was.ExtensibleDeployedResource >> was.ExtensibleDeployed >> python.PythonManagedDeployed >> udm.BaseDeployed >> udm.BaseConfigurationItem
Interfaces	udm.Deployed, udm.ConfigurationItem

Specifies a topic connection factory, which is used to create connections to the associated JMS provider of JMS topic destinations for publish and subscribe messaging. Use WebSphere topic connection factory administrative objects to manage topic connection factories for the internal WebSphere JMS provider.

Parent

* **container** : CI<udm.Container>
The container on which this deployed runs.

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Hidden Properties

* **additionalPropertiesNotToExpose** : STRING = jmsProvider, wasType
  Properties that are not exposed to any python wsadmin script.
* **createOrder** : INTEGER = 60
  The order in which a create step will be executed.
* **createScript** : STRING = was/jms/create-jms-object.py
  Python wsadmin script invoked to create a JMS resource.
* **createVerb** : STRING = Create
  The word that is used to prefix a step description for the create operation.
* **destroyOrder** : INTEGER = 40
  The order in which a destroy step will be executed.
* **destroyScript** : STRING = was/jms/destroy-jms-object.py
  Python wsadmin script invoked to destroy a JMS resource.
* **destroyVerb** : STRING = Destroy
  The word that is used to prefix a step description for the destroy operation.
* **discoverOrder** : INTEGER = 50
  The order in which a discover step will be executed.
* **discoverScript** : STRING = was/jms/discover-inspect-jms-objects.py
  Python wsadmin script invoked to inspect a JMS resource.
* **jmsProvider** : STRING = WebSphere JMS Provider
  JMS provider for V5 default topic connection factory.
* **libraryScripts** : LIST_OF_STRING = [was/jms/discover-inspect-jms-objects-lib.py]
  Additional scripts to be included in the runtime
* **modifyOrder** : INTEGER = 60
  The order in which a modify step will be executed.
* **modifyVerb** : STRING = Modify
  The word that is used to prefix a step description for the modify operation.
* **standardPropertiesNotToExpose** : STRING = id, type, properties, deployable, container, createOrder, createScript, createVerb, syncAfterCreateOrder, modifyOrder, modifyScript, modifyVerb, syncAfterModifyOrder, destroyOrder, destroyScript, securityPermissions, inheritPermissions, exposeDeployedApplication, destroyVerb, syncAfterDestroyOrder, startOrder, startScript, startVerb, stopOrder, stopScript, stopVerb, discoverScript, inspectScript, discoverOrder, libraryScripts
  Standard properties that are not exposed to any python wsadmin script.
* **startOrder** : INTEGER = 50
  The order in which a start step will be executed.
* **startVerb** : STRING = Start
  The word that is used to prefix a step description for the start operation.
* **stopOrder** : INTEGER = 50
  The order in which a stop step will be executed.
* **stopVerb** : STRING = Stop
  The word that is used to prefix a step description for the stop operation.
* **syncAfterCreateOrder** : INTEGER = 65
  The order in which a synchronize after create step will be executed.
* **syncAfterDestroyOrder** : INTEGER = 45
  The order in which a synchronize after destroy step will be executed.
* **syncAfterModifyOrder** : INTEGER = 65
  The order in which a synchronize after modify step will be executed.
* **wasType** : STRING = WASTopicConnectionFactory
  WAS config type of V5 default topic connection factory.

exposeDeployedApplication : BOOLEAN = false
flag to indicate whether the deployed application CI is to be injected to the python script execution context.

modifyScript : STRING
Python script invoked to upgrade a Java EE artifact or modify a Java EE resource

startScript : STRING
Python script invoked to start a Java EE artifact or Java EE resource

stopScript : STRING
Python script invoked to stop a Java EE artifact or Java EE resource

was.V5DefaultTopicConnectionFactorySpec

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Type Hierarchy	jee.TopicConnectionFactorySpec >> jee.JndiResourceSpec >> jee.ResourceSpec >> udm.BaseDeployable >> udm.BaseConfigurationItem
Interfaces	udm.Taggable, udm.Deployable, udm.ConfigurationItem

Specification of a V5 default topic connection factory.

Public Properties

jndiName : STRING
JNDI name for the resource (string)

tags : SET_OF_STRING
If set, this deployable will only be mapped automatically to containers with the same tag.

was.V5DefaultTopicSpec

Type Hierarchy	jee.TopicSpec >> jee.JndiResourceSpec >> jee.ResourceSpec >> udm.BaseDeployable >> udm.BaseConfigurationItem
Interfaces	udm.Taggable, udm.Deployable, udm.ConfigurationItem

Specification of a V5 default topic.

Public Properties

jndiName : STRING
JNDI name for the resource (string)

tags : SET_OF_STRING
If set, this deployable will only be mapped automatically to containers with the same tag.

topic : STRING
String value used to identify the topic (string)

was.VirtualHost

Type Hierarchy	was.Resource >> was.ExtensibleDeployedResource >> was.ExtensibleDeployed >> python.PythonManagedDeployed >> udm.BaseDeployed >> udm.BaseConfigurationItem
Interfaces	udm.Deployed, udm.ConfigurationItem

Virtual host with a unique set of Web access ports. Such a configuration lets a single host machine resemble multiple host machines. Each virtual host has a logical name and a list of one or more domain name system (DNS) aliases by which it is known.

Parent

* **container** : CI<udm.Container>
The container on which this deployed runs.

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Hidden Properties

* **createOrder** : INTEGER = 60
  The order in which a create step will be executed.
* **createScript** : STRING = was/virtualhost/create-virtual-host.py
  Python wsadmin script invoked to create a virtual host.
* **createVerb** : STRING = Create
  The word that is used to prefix a step description for the create operation.
* **destroyOrder** : INTEGER = 40
  The order in which a destroy step will be executed.
* **destroyScript** : STRING = was/virtualhost/destroy-virtual-host.py
  Python wsadmin script invoked to destroy a virtual host.
* **destroyVerb** : STRING = Destroy
  The word that is used to prefix a step description for the destroy operation.
* **discoverOrder** : INTEGER = 45
  Discover Order
* **discoverScript** : STRING = was/virtualhost/discover-inspect-virtual-host.py
  Python wsadmin script invoked to inspect a virtual host.
* **modifyOrder** : INTEGER = 60
  The order in which a modify step will be executed.
* **modifyVerb** : STRING = Modify
  The word that is used to prefix a step description for the modify operation.
* **standardPropertiesNotToExpose** : STRING = id, type, properties, deployable, container, createOrder, createScript, createVerb, syncAfterCreateOrder, modifyOrder, modifyScript, modifyVerb, syncAfterModifyOrder, destroyOrder, destroyScript, securityPermissions, inheritPermissions, exposeDeployedApplication, destroyVerb, syncAfterDestroyOrder, startOrder, startScript, startVerb, stopOrder, stopScript, stopVerb, discoverScript, inspectScript, discoverOrder, libraryScripts
  Standard properties that are not exposed to any python wsadmin script.
* **startOrder** : INTEGER = 50
  The order in which a start step will be executed.
* **startVerb** : STRING = Start
  The word that is used to prefix a step description for the start operation.
* **stopOrder** : INTEGER = 50
  The order in which a stop step will be executed.
* **stopVerb** : STRING = Stop
  The word that is used to prefix a step description for the stop operation.
* **syncAfterCreateOrder** : INTEGER = 65
  The order in which a synchronize after create step will be executed.
* **syncAfterDestroyOrder** : INTEGER = 45
  The order in which a synchronize after destroy step will be executed.
* **syncAfterModifyOrder** : INTEGER = 65
  The order in which a synchronize after modify step will be executed.

exposeDeployedApplication : BOOLEAN = false
flag to indicate whether the deployed application CI is to be injected to the python script execution context.

libraryScripts : LIST_OF_STRING
List of scripts to appended to the the deployeds runtime script

modifyScript : STRING
Python script invoked to upgrade a Java EE artifact or modify a Java EE resource

startScript : STRING
Python script invoked to start a Java EE artifact or Java EE resource

stopScript : STRING
Python script invoked to stop a Java EE artifact or Java EE resource

was.VirtualHostSpec

Type Hierarchy was.Deployable >> udm.BaseDeployable >> udm.BaseConfigurationItem
Interfaces udm.Taggable, udm.Deployable, udm.ConfigurationItem

Specification of a virtual host.

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Public Properties	
aliases : SET_OF_STRING Virtual host aliases - enter alias as: hostname:port (set_of_string)	
tags : SET_OF_STRING If set, this deployable will only be mapped automatically to containers with the same tag.	

was.War

Type Hierarchy	jee.War >> udm.BaseDeployableArchiveArtifact >> udm.BaseDeployableFileArtifact >> udm.BaseDeployableArtifact >> udm.BaseDeployable >> udm.BaseConfigurationItem
Interfaces	udm.Taggable, udm.Deployable, udm.SourceArtifact, udm.ArchiveArtifact, udm.Artifact, udm.DeployableArtifact, udm.ConfigurationItem, udm.FileArtifact

Java EE WAR archive

Public Properties	
contextRoot : STRING Specifies the context root of the Web application (WAR). (string)	
excludeFileNamesRegex : STRING Regular expression that matches file names that must be excluded from scanning	
placeholders : SET_OF_STRING Placeholders detected in this artifact	
preCompileJsps : STRING Specify whether to precompile JavaServer Pages (JSP) files as a part of installation. The default is not to precompile JSP files. (boolean)	
roleMappings : MAP_STRING_STRING Security role to user/group mapping (map_string_string)	
scanPlaceholders : BOOLEAN = false Whether to scan this artifact for placeholders when it is imported	
startingWeight : STRING Specifies the order in which modules are started when the server starts. The module with the lowest starting weight is started first. (integer)	
tags : SET_OF_STRING If set, this deployable will only be mapped automatically to containers with the same tag.	
Hidden Properties	
* **textFileNamesRegex** : STRING = .+\.(cfg | conf | config | ini | properties | props | txt | asp | aspx | htm | html | jsf | jsp | xht | xhtml | sql | xml | xsd | xsl | xslt) Regular expression that matches file names of text files	

was.WarModule

Type Hierarchy	was.Module >> was.ExtensibleDeployedArtifact >> was.ExtensibleDeployed >> python.PythonManagedDeployed >> udm.BaseDeployed >> udm.BaseConfigurationItem
Interfaces	udm.Artifact, udm.Deployed, udm.ConfigurationItem, udm.DerivedArtifact

WAR with values configured for a deployment.

Parent	
* **container** : CI<udm.Container> The container on which this deployed runs.	

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Public Properties
* **contextRoot** : STRING Specifies the context root of the Web application (WAR).
deployable : CI<udm.Deployable> The deployable that this deployed is derived from.
placeholders : MAP_STRING_STRING A Map containing all the placeholders mapped to their values. Special values are or
preCompileJsps : BOOLEAN = false Specify whether to precompile JavaServer Pages (JSP) files as a part of installation. The default is not to precompile JSP files.
roleMappings : MAP_STRING_STRING Security role to user/group mapping
sharedLibraries : SET_OF_CI<was.SharedLibrary > Shared libraries used by this application
startingWeight : INTEGER = 1 Specifies the order in which modules are started when the server starts. The module with the lowest starting weight is started first.
virtualHost : CI<was.VirtualHost > Specify the virtual host where you want to install the Web modules that are contained in your application. You can install Web modules on the same virtual host or disperse them among several hosts.
webServers : SET_OF_CI<was.ManagedWebServer > Specify the Web servers as targets that serve as routers for requests to this application.

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Hidden Properties

* **createOrder** : INTEGER = 70
  The order in which a create step will be executed.
* **createScript** : STRING = was/application/deploy-application.py
  Python wsadmin script invoked to create a Java EE artifact.
* **createVerb** : STRING = Deploy
  The word is used to prefix a step description for the create operation.
* **destroyOrder** : INTEGER = 30
  The order in which a destroy step will be executed.
* **destroyScript** : STRING = was/application/undeploy-application.py
  Python wsadmin script invoked to destroy a Java EE artifact.
* **destroyVerb** : STRING = Undeploy
  The word is used to prefix a step description for the destroy operation.
* **discoverOrder** : INTEGER = 50
  The order in which a discover step will be executed.
* **discoverScript** : STRING = was/application/discover-inspect-war-module.py
  Python wsadmin script invoked to inspect a JMS resource.
* **libraryScripts** : LIST_OF_STRING = [was/application/discover-app-module-lib.py]
  Additional scripts to be included in the runtime
* **modifyOrder** : INTEGER = 70
  The order in which a modify step will be executed.
* **modifyVerb** : STRING = Upgrade
  The word is used to prefix a step description for the modify operation.
* **standardPropertiesNotToExpose** : STRING = id, type, properties, deployable, container, createOrder, createScript, createVerb, syncAfterCreateOrder, modifyOrder, modifyScript, modifyVerb, syncAfterModifyOrder, destroyOrder, destroyScript, securityPermissions, inheritPermissions, exposeDeployedApplication, destroyVerb, syncAfterDestroyOrder, startOrder, startScript, startVerb, stopOrder, stopScript, stopVerb, discoverScript, inspectScript, discoverOrder, libraryScripts
  Standard properties that are not exposed to any python wsadmin script.
* **startOrder** : INTEGER = 90
  The order in which a start step will be executed.
* **startScript** : STRING = was/application/start-application.py
  Python wsadmin script invoked to start running a Java EE artifact
* **startVerb** : STRING = Start
  The word that is used to prefix a step description for the start operation.
* **stopOrder** : INTEGER = 10
  The order in which a stop step will be executed.
* **stopScript** : STRING = was/application/stop-application.py
  Python wsadmin script invoked to stop running a Java EE artifact.
* **stopVerb** : STRING = Stop
  The word that is used to prefix a step description for the stop operation.
* **syncAfterCreateOrder** : INTEGER = 75
  The order in which a synchronize after create step will be executed.
* **syncAfterDestroyOrder** : INTEGER = 35
  Sync After Destroy Order
* **syncAfterModifyOrder** : INTEGER = 75
  The order in which a synchronize after modify step will be executed.

exposeDeployedApplication : BOOLEAN = false
flag to indicate whether the deployed application CI is to be injected to the python script execution context.

modifyScript : STRING
Python script invoked to upgrade a Java EE artifact or modify a Java EE resource

was.WmqQueue

Type Hierarchy	was.JmsResource >> was.Resource >> was.ExtensibleDeployedResource >> was.ExtensibleDeployed >> python.PythonManagedDeployed >> udm.BaseDeployed >> udm.BaseConfigurationItem
Interfaces	udm.Deployed, udm.ConfigurationItem

Queue destinations provided for point-to-point messaging by the WebSphere MQ JMS

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

provider. Use WebSphere MQ queue destination administrative objects to manage queue destinations for the WebSphere MQ JMS provider.

Parent	
*	**container** : CI<udm.Container> The container on which this deployed runs.
Public Properties	
*	**baseQueueName** : STRING Name of the queue to which messages are sent
*	**jndiName** : STRING JNDI name for the resource
	deployable : CI<udm.Deployable> The deployable that this deployed is derived from.

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Hidden Properties

* **additionalPropertiesNotToExpose** : STRING = jmsProvider, wasType
  Properties that are not exposed to any python wsadmin script.
* **createOrder** : INTEGER = 60
  The order in which a create step will be executed.
* **createScript** : STRING = was/jms/create-jms-object.py
  Python wsadmin script invoked to create a JMS resource.
* **createVerb** : STRING = Create
  The word that is used to prefix a step description for the create operation.
* **destroyOrder** : INTEGER = 40
  The order in which a destroy step will be executed.
* **destroyScript** : STRING = was/jms/destroy-jms-object.py
  Python wsadmin script invoked to destroy a JMS resource.
* **destroyVerb** : STRING = Destroy
  The word that is used to prefix a step description for the destroy operation.
* **discoverOrder** : INTEGER = 50
  The order in which a discover step will be executed.
* **discoverScript** : STRING = was/jms/discover-inspect-jms-objects.py
  Python wsadmin script invoked to inspect a JMS resource.
* **jmsProvider** : STRING = WebSphere MQ JMS Provider
  JMS provider for WebSphere MQ queue.
* **libraryScripts** : LIST_OF_STRING = [was/jms/discover-inspect-jms-objects-lib.py]
  Additional scripts to be included in the runtime
* **modifyOrder** : INTEGER = 60
  The order in which a modify step will be executed.
* **modifyVerb** : STRING = Modify
  The word that is used to prefix a step description for the modify operation.
* **standardPropertiesNotToExpose** : STRING = id, type, properties, deployable, container, createOrder, createScript, createVerb, syncAfterCreateOrder, modifyOrder, modifyScript, modifyVerb, syncAfterModifyOrder, destroyOrder, destroyScript, securityPermissions, inheritPermissions, exposeDeployedApplication, destroyVerb, syncAfterDestroyOrder, startOrder, startScript, startVerb, stopOrder, stopScript, stopVerb, discoverScript, inspectScript, discoverOrder, libraryScripts
  Standard properties that are not exposed to any python wsadmin script.
* **startOrder** : INTEGER = 50
  The order in which a start step will be executed.
* **startVerb** : STRING = Start
  The word that is used to prefix a step description for the start operation.
* **stopOrder** : INTEGER = 50
  The order in which a stop step will be executed.
* **stopVerb** : STRING = Stop
  The word that is used to prefix a step description for the stop operation.
* **syncAfterCreateOrder** : INTEGER = 65
  The order in which a synchronize after create step will be executed.
* **syncAfterDestroyOrder** : INTEGER = 45
  The order in which a synchronize after destroy step will be executed.
* **syncAfterModifyOrder** : INTEGER = 65
  The order in which a synchronize after modify step will be executed.
* **wasType** : STRING = MQQueue
  WAS config type of WebSphere MQ queue.

exposeDeployedApplication : BOOLEAN = false
flag to indicate whether the deployed application CI is to be injected to the python script execution context.

modifyScript : STRING
Python script invoked to upgrade a Java EE artifact or modify a Java EE resource

startScript : STRING
Python script invoked to start a Java EE artifact or Java EE resource

stopScript : STRING
Python script invoked to stop a Java EE artifact or Java EE resource

was.WmqQueueConnectionFactory

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Type Hierarchy	was.JmsResource >> was.Resource >> was.ExtensibleDeployedResource >> was.ExtensibleDeployed >> python.PythonManagedDeployed >> udm.BaseDeployed >> udm.BaseConfigurationItem
Interfaces	udm.Deployed, udm.ConfigurationItem

Queue connection factory is used to create connections to the associated JMS provider of JMS queue destinations, for point-to-point messaging. Use WebSphere MQ queue connection factory administrative objects to manage queue connection factories for the WebSphere MQ JMS provider.

Parent

* **container** : CI<udm.Container>
The container on which this deployed runs.

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Hidden Properties

* **additionalPropertiesNotToExpose** : STRING = jmsProvider, wasType
  Properties that are not exposed to any python wsadmin script.
* **createOrder** : INTEGER = 60
  The order in which a create step will be executed.
* **createScript** : STRING = was/jms/create-jms-object.py
  Python wsadmin script invoked to create a JMS resource.
* **createVerb** : STRING = Create
  The word that is used to prefix a step description for the create operation.
* **destroyOrder** : INTEGER = 40
  The order in which a destroy step will be executed.
* **destroyScript** : STRING = was/jms/destroy-jms-object.py
  Python wsadmin script invoked to destroy a JMS resource.
* **destroyVerb** : STRING = Destroy
  The word that is used to prefix a step description for the destroy operation.
* **discoverOrder** : INTEGER = 50
  The order in which a discover step will be executed.
* **discoverScript** : STRING = was/jms/discover-inspect-jms-objects.py
  Python wsadmin script invoked to inspect a JMS resource.
* **jmsProvider** : STRING = WebSphere MQ JMS Provider
  JMS provider for WebSphere MQ queue connection factory
* **libraryScripts** : LIST_OF_STRING = [was/jms/discover-inspect-jms-objects-lib.py]
  Additional scripts to be included in the runtime
* **modifyOrder** : INTEGER = 60
  The order in which a modify step will be executed.
* **modifyVerb** : STRING = Modify
  The word that is used to prefix a step description for the modify operation.
* **standardPropertiesNotToExpose** : STRING = id, type, properties, deployable, container, createOrder, createScript, createVerb, syncAfterCreateOrder, modifyOrder, modifyScript, modifyVerb, syncAfterModifyOrder, destroyOrder, destroyScript, securityPermissions, inheritPermissions, exposeDeployedApplication, destroyVerb, syncAfterDestroyOrder, startOrder, startScript, startVerb, stopOrder, stopScript, stopVerb, discoverScript, inspectScript, discoverOrder, libraryScripts
  Standard properties that are not exposed to any python wsadmin script.
* **startOrder** : INTEGER = 50
  The order in which a start step will be executed.
* **startVerb** : STRING = Start
  The word that is used to prefix a step description for the start operation.
* **stopOrder** : INTEGER = 50
  The order in which a stop step will be executed.
* **stopVerb** : STRING = Stop
  The word that is used to prefix a step description for the stop operation.
* **syncAfterCreateOrder** : INTEGER = 65
  The order in which a synchronize after create step will be executed.
* **syncAfterDestroyOrder** : INTEGER = 45
  The order in which a synchronize after destroy step will be executed.
* **syncAfterModifyOrder** : INTEGER = 65
  The order in which a synchronize after modify step will be executed.
* **wasType** : STRING = MQQueueConnectionFactory
  WAS config type of WebSphere MQ queue connection factory.

exposeDeployedApplication : BOOLEAN = false
flag to indicate whether the deployed application CI is to be injected to the python script execution context.

modifyScript : STRING
Python script invoked to upgrade a Java EE artifact or modify a Java EE resource

startScript : STRING
Python script invoked to start a Java EE artifact or Java EE resource

stopScript : STRING
Python script invoked to stop a Java EE artifact or Java EE resource

was.WmqQueueConnectionFactorySpec

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Type Hierarchy	jee.QueueConnectionFactorySpec >> jee.JndiResourceSpec >> jee.ResourceSpec >> udm.BaseDeployable >> udm.BaseConfigurationItem
Interfaces	udm.Taggable, udm.Deployable, udm.ConfigurationItem

Specification of a WMQ queue connection factory.

Public Properties

jndiName : STRING
JNDI name for the resource (string)

tags : SET_OF_STRING
If set, this deployable will only be mapped automatically to containers with the same tag.

was.WmqQueueSpec

Type Hierarchy	jee.QueueSpec >> jee.JndiResourceSpec >> jee.ResourceSpec >> udm.BaseDeployable >> udm.BaseConfigurationItem
Interfaces	udm.Taggable, udm.Deployable, udm.ConfigurationItem

Specification of a WMQ queue.

Public Properties

baseQueueName : STRING
Name of the queue to which messages are sent (string)

jndiName : STRING
JNDI name for the resource (string)

tags : SET_OF_STRING
If set, this deployable will only be mapped automatically to containers with the same tag.

was.WmqTopic

Type Hierarchy	was.JmsResource >> was.Resource >> was.ExtensibleDeployedResource >> was.ExtensibleDeployed >> python.PythonManagedDeployed >> udm.BaseDeployed >> udm.BaseConfigurationItem
Interfaces	udm.Deployed, udm.ConfigurationItem

Topic destinations provided for publish and subscribe messaging by the WebSphere MQ JMS provider. Use WebSphere MQ topic destination administrative objects to manage topic destinations for the WebSphere MQ JMS provider.

Parent

* **container** : CI<udm.Container>
The container on which this deployed runs.

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Hidden Properties

* **additionalPropertiesNotToExpose** : STRING = jmsProvider, wasType
  Properties that are not exposed to any python wsadmin script.
* **createOrder** : INTEGER = 60
  The order in which a create step will be executed.
* **createScript** : STRING = was/jms/create-jms-object.py
  Python wsadmin script invoked to create a JMS resource.
* **createVerb** : STRING = Create
  The word that is used to prefix a step description for the create operation.
* **destroyOrder** : INTEGER = 40
  The order in which a destroy step will be executed.
* **destroyScript** : STRING = was/jms/destroy-jms-object.py
  Python wsadmin script invoked to destroy a JMS resource.
* **destroyVerb** : STRING = Destroy
  The word that is used to prefix a step description for the destroy operation.
* **discoverOrder** : INTEGER = 50
  The order in which a discover step will be executed.
* **discoverScript** : STRING = was/jms/discover-inspect-jms-objects.py
  Python wsadmin script invoked to inspect a JMS resource.
* **jmsProvider** : STRING = WebSphere MQ JMS Provider
  JMS provider for WebSphere MQ topic.
* **libraryScripts** : LIST_OF_STRING = [was/jms/discover-inspect-jms-objects-lib.py]
  Additional scripts to be included in the runtime
* **modifyOrder** : INTEGER = 60
  The order in which a modify step will be executed.
* **modifyVerb** : STRING = Modify
  The word that is used to prefix a step description for the modify operation.
* **standardPropertiesNotToExpose** : STRING = id, type, properties, deployable, container, createOrder, createScript, createVerb, syncAfterCreateOrder, modifyOrder, modifyScript, modifyVerb, syncAfterModifyOrder, destroyOrder, destroyScript, securityPermissions, inheritPermissions, exposeDeployedApplication, destroyVerb, syncAfterDestroyOrder, startOrder, startScript, startVerb, stopOrder, stopScript, stopVerb, discoverScript, inspectScript, discoverOrder, libraryScripts
  Standard properties that are not exposed to any python wsadmin script.
* **startOrder** : INTEGER = 50
  The order in which a start step will be executed.
* **startVerb** : STRING = Start
  The word that is used to prefix a step description for the start operation.
* **stopOrder** : INTEGER = 50
  The order in which a stop step will be executed.
* **stopVerb** : STRING = Stop
  The word that is used to prefix a step description for the stop operation.
* **syncAfterCreateOrder** : INTEGER = 65
  The order in which a synchronize after create step will be executed.
* **syncAfterDestroyOrder** : INTEGER = 45
  The order in which a synchronize after destroy step will be executed.
* **syncAfterModifyOrder** : INTEGER = 65
  The order in which a synchronize after modify step will be executed.
* **wasType** : STRING = MQTopic
  WAS config type of WebSphere MQ topic.

exposeDeployedApplication : BOOLEAN = false
flag to indicate whether the deployed application CI is to be injected to the python script execution context.

modifyScript : STRING
Python script invoked to upgrade a Java EE artifact or modify a Java EE resource

startScript : STRING
Python script invoked to start a Java EE artifact or Java EE resource

stopScript : STRING
Python script invoked to stop a Java EE artifact or Java EE resource

was.WmqTopicConnectionFactory

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Type Hierarchy	was.JmsResource >> was.Resource >> was.ExtensibleDeployedResource >> was.ExtensibleDeployed >> python.PythonManagedDeployed >> udm.BaseDeployed >> udm.BaseConfigurationItem
Interfaces	udm.Deployed, udm.ConfigurationItem

Topic connection factory is used to create connections to the associated JMS provider of JMS topic destinations, for publish and subscribe messaging. Use WebSphere MQ topic connection factory administrative objects to manage topic connection factories for the WebSphere MQ JMS provider.

Parent

* **container** : CI<udm.Container>
The container on which this deployed runs.

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Hidden Properties

* **additionalPropertiesNotToExpose** : STRING = jmsProvider, wasType
  Properties that are not exposed to any python wsadmin script.
* **createOrder** : INTEGER = 60
  The order in which a create step will be executed.
* **createScript** : STRING = was/jms/create-jms-object.py
  Python wsadmin script invoked to create a JMS resource.
* **createVerb** : STRING = Create
  The word that is used to prefix a step description for the create operation.
* **destroyOrder** : INTEGER = 40
  The order in which a destroy step will be executed.
* **destroyScript** : STRING = was/jms/destroy-jms-object.py
  Python wsadmin script invoked to destroy a JMS resource.
* **destroyVerb** : STRING = Destroy
  The word that is used to prefix a step description for the destroy operation.
* **discoverOrder** : INTEGER = 50
  The order in which a discover step will be executed.
* **discoverScript** : STRING = was/jms/discover-inspect-jms-objects.py
  Python wsadmin script invoked to inspect a JMS resource.
* **jmsProvider** : STRING = WebSphere MQ JMS Provider
  JMS type of WebSphere MQ topic connection factory.
* **libraryScripts** : LIST_OF_STRING = [was/jms/discover-inspect-jms-objects-lib.py]
  Additional scripts to be included in the runtime
* **modifyOrder** : INTEGER = 60
  The order in which a modify step will be executed.
* **modifyVerb** : STRING = Modify
  The word that is used to prefix a step description for the modify operation.
* **standardPropertiesNotToExpose** : STRING = id, type, properties, deployable, container, createOrder, createScript, createVerb, syncAfterCreateOrder, modifyOrder, modifyScript, modifyVerb, syncAfterModifyOrder, destroyOrder, destroyScript, securityPermissions, inheritPermissions, exposeDeployedApplication, destroyVerb, syncAfterDestroyOrder, startOrder, startScript, startVerb, stopOrder, stopScript, stopVerb, discoverScript, inspectScript, discoverOrder, libraryScripts
  Standard properties that are not exposed to any python wsadmin script.
* **startOrder** : INTEGER = 50
  The order in which a start step will be executed.
* **startVerb** : STRING = Start
  The word that is used to prefix a step description for the start operation.
* **stopOrder** : INTEGER = 50
  The order in which a stop step will be executed.
* **stopVerb** : STRING = Stop
  The word that is used to prefix a step description for the stop operation.
* **syncAfterCreateOrder** : INTEGER = 65
  The order in which a synchronize after create step will be executed.
* **syncAfterDestroyOrder** : INTEGER = 45
  The order in which a synchronize after destroy step will be executed.
* **syncAfterModifyOrder** : INTEGER = 65
  The order in which a synchronize after modify step will be executed.
* **wasType** : STRING = MQTopicConnectionFactory
  WAS config type of WebSphere MQ topic connection factory.

exposeDeployedApplication : BOOLEAN = false
flag to indicate whether the deployed application CI is to be injected to the python script execution context.

modifyScript : STRING
Python script invoked to upgrade a Java EE artifact or modify a Java EE resource

startScript : STRING
Python script invoked to start a Java EE artifact or Java EE resource

stopScript : STRING
Python script invoked to stop a Java EE artifact or Java EE resource

was.WmqTopicConnectionFactorySpec

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.

Type Hierarchy	jee.TopicConnectionFactorySpec >> jee.JndiResourceSpec >> jee.ResourceSpec >> udm.BaseDeployable >> udm.BaseConfigurationItem
Interfaces	udm.Taggable, udm.Deployable, udm.ConfigurationItem

Specification of a WMQ topic connection factory.

Public Properties

jndiName : STRING
JNDI name for the resource (string)

tags : SET_OF_STRING
If set, this deployable will only be mapped automatically to containers with the same tag.

was.WmqTopicSpec

Type Hierarchy	jee.TopicSpec >> jee.JndiResourceSpec >> jee.ResourceSpec >> udm.BaseDeployable >> udm.BaseConfigurationItem
Interfaces	udm.Taggable, udm.Deployable, udm.ConfigurationItem

Specification of a WMQ topic.

Public Properties

baseTopicName : STRING
Name of the topic to which messages are sent (string)

jndiName : STRING
JNDI name for the resource (string)

tags : SET_OF_STRING
If set, this deployable will only be mapped automatically to containers with the same tag.

Copyright XebiaLabs B.V. © 2008-2012. All rights reserved.