

Deployit Webserver Plugin Manual

Version 3.7.3

Table of Contents

Table of Contents	2
Preface	3
Overview	3
Features	3
Requirements	3
Usage in Deployment Packages	3
Using the deployables and deployed	3
Deployable vs. Container table	3
Deployed Actions Table	3
CI Reference	4
Configuration Item Overview	4
Deployable Configuration Items	4
Deployed Configuration Items	4
Topology Configuration Items	4
Configuration Item Details	4
www.ApacheConfFragment	4
www.ApacheConfFragmentSpec	5
www.ApacheHttpdServer	5
www.ApacheVirtualHost	6
www.ApacheVirtualHostSpec	7
www.PublishedWebContent	8
www.WebContent	9

Preface

This document describes the functionality provided by the Webserver plugin.

See the **Deployit Reference Manual** for background information on Deployit and deployment concepts.

Overview

The webserver-plugin is a Deployit plugin that supports deployment of web content and webserver configuration to a webserver.

Features

- Runs on Deployit 3.6 and up.
- Supports deployment to Apache and IHS webserver.
- Deploys and undeploys webserver artifacts:
 - Web content (HTML pages, images, etc.)
 - Virtual host configuration
 - Any configuration fragment
- Supports starting, stopping and restarting of webserver as control tasks.

Requirements

- **Deployit requirements**
 - **Deployit:** version 3.6+
 - **Other Deployit Plugins:** None
- **Infrastructural requirements**
 - **User credentials** for accessing the webserver executables on the host running the webserver.

Usage in Deployment Packages

The following is a manifest snippet that shows how web content and a virtual host can be included in a deployment package. The web content CI refers to a folder, *html*, included in the deployment package.

```
Manifest-Version: 1.0
Deployit-Package-Format-Version: 1.3
CI-Application: PetClinic-ear
CI-Version: 2.0

Name: PetClinic-2.0.ear
CI-Type: jee.Ear
CI-Name: PetClinic

Name: html
CI-Type: www.WebContent
CI-Name: PetClinic-html

Name: PetClinic-vh
CI-Type: www.ApacheVirtualHostSpec
CI-host: *
CI-port: 8080
```

Using the deployables and deployed

The following table describes which deployable/container combinations are possible.

Deployable vs. Container table

Deployable	Container	Generated deployed
www.WebContent	www.ApacheHttpdServer	www.PublishedWebContent
www.ApacheVirtualHostSpec	www.ApacheHttpdServer	www.ApacheVirtualHost
www.ApacheConfFragmentSpec	www.ApacheHttpdServer	www.ApacheConfFragment

The following table describes the effect a deployed has on it's container.

Deployed Actions Table

Deployed	Actions performed for operations
----------	----------------------------------

	Create	Destroy	Modify
www.PublishedWebContent	<ul style="list-style-type: none"> Create target path on webserver, if needed Copy web content to target path on webserver 	<ul style="list-style-type: none"> Delete web content from host 	<ul style="list-style-type: none"> Delete existing web content from webserver Copy modified web content to target path on webserver
www.ApacheVirtualHost	<ul style="list-style-type: none"> Copy virtual host configuration to webserver 	<ul style="list-style-type: none"> Delete virtual host configuration from webserver 	<ul style="list-style-type: none"> Delete virtual host configuration from webserver Copy new virtual host configuration to webserver
www.ApacheConfFragment	<ul style="list-style-type: none"> Copy configuration fragment to webserver 	<ul style="list-style-type: none"> Delete configuration fragment from webserver 	<ul style="list-style-type: none"> Delete configuration fragment from webserver Copy new configuration fragment to webserver

CI Reference

Configuration Item Overview

Deployable Configuration Items

CI	Description
www.ApacheConfFragmentSpec	Specification for an Apache configuration fragment
www.ApacheVirtualHostSpec	Specification for an Apache virtual host
www.WebContent	Folder containing web content (HTML pages, images, etc)

Deployed Configuration Items

CI	Description
www.ApacheConfFragment	Apache configuration fragment
www.ApacheVirtualHost	Apache virtual host
www.PublishedWebContent	Web content on the webserver

Topology Configuration Items

CI	Description
www.ApacheHttpdServer	Apache HTTPD web server


Configuration Item Details

www.ApacheConfFragment

Hierarchy generic.ProcessedTemplate >> generic.AbstractDeployedArtifact >> generic.AbstractDeployed >> udm.BaseDeployed >> udm.BaseConfigurationItem

Interfaces udm.Deployed, udm.ConfigurationItem

Apache configuration fragment

Public Properties	
 container : CI<udm.Container>	
The container on which this deployed runs.	
deployable : CI<udm.Deployable>	
The deployable that this deployed is derived from.	

Hidden Properties	
createOrder : INTEGER = 50	
The order of the step in the step list for the create operation.	
createVerb : STRING = Create	
Create Verb	
destroyOrder : INTEGER = 40	
The order of the step in the step list for the destroy operation.	
destroyVerb : STRING = Destroy	
Destroy Verb	

modifyOrder	: INTEGER = 50
The order of the step in the step list for the modify operation.	
modifyVerb	: STRING = Modify
Modify Verb	
noopOrder	: INTEGER = 50
The order of the step in the step list for the noop operation.	
noopVerb	: STRING = Modify
Noop Verb	
targetDirectory	: STRING = \${deployed.container.configurationFragmentDirectory}
Target directory name	
targetFile	: STRING = \${deployed.name}.conf
Target file name	
template	: STRING = www/apache/\${deployed.type}.conf.ftl
Configuration fragment template file name.	
createTargetDirectory	: BOOLEAN = false
Create the target directory on the generic server if it does not exist.	
inspectClasspathResources	: SET_OF_STRING
Additional classpath resources that should be uploaded to the working directory before executing the inspect script.	
inspectScript	: STRING
Classpath to the script used to inspect the generic container.	
inspectTemplateClasspathResources	: SET_OF_STRING
Additional template classpath resources that should be uploaded to the working directory before executing the inspect script. The template is first rendered and the rendered content copied to a file, with the same name as the template, in the working directory.	
restartRequired	: BOOLEAN = true
Restart Required	
restartRequiredForNoop	: BOOLEAN = false
The generic container requires a restart for the NOOP action performed by this deployed.	
targetDirectoryShared	: BOOLEAN = true
Is the target directory shared by others on the generic server. When true, the target directory is not deleted during a destroy operation; only the artifacts copied to it.	

www.ApacheConfFragmentSpec

Hierarchy generic.Resource >> udm.BaseDeployable >> udm.BaseConfigurationItem

Interfaces udm.Taggable, udm.Deployable, udm.ConfigurationItem

Specification for an Apache configuration fragment.

Public Properties

tags : **SET_OF_STRING**

The tags to map deployables to containers.

www.ApacheHttpdServer

Hierarchy generic.Container >> udm.BaseContainer >> udm.BaseConfigurationItem

Interfaces udm.Taggable, udm.ConfigurationItem, generic.GenericContainer, udm.Container, overthere.HostContainer

Apache HTTPD web server

Public Properties

configurationFragmentDirectory : **STRING**

The directory into which Apache configuration files (for virtual host definitions) should be written

defaultDocumentRoot : **STRING**

The directory in which document roots for virtual hosts should be created. Web content deployed without a virtual host will also be copied into this directory



host : **CI<overthere.Host>**

Host upon which the container resides

restartWaitTime : **INTEGER** = 10

Duration (in secs) to wait after the restart server step has been executed

startCommand : **STRING**

The command to start Apache. Arguments containing spaces are not supported
startWaitTime : INTEGER = 10
Duration (in secs) to wait after the start server step has been executed
stopCommand : STRING
The command to stop Apache. Arguments containing spaces are not supported
stopWaitTime : INTEGER = 10
Duration (in secs) to wait after the stop server step has been executed
deploymentGroup : INTEGER
The deployment group of this container.
envVars : MAP_STRING_STRING
Environment variables for container
restartCommand : STRING
The command to restart Apache. If left blank, reload command is used. If reload command is also blank than the sequence 'stop, start' is used. Arguments containing spaces are not supported
tags : SET_OF_STRING
The tags to map deployables to containers.

Hidden Properties

restartOrder : INTEGER = 90
The order of the restart container step in the step list.
restartScript : STRING = <code><#assign restart=(container.restartCommand)!"><#if restart != ">www/apache/restart</code>
The command to restart or reload Apache. If left blank, the sequence 'stop, start' is used. Arguments containing spaces are not supported
startOrder : INTEGER = 90
The order of the start container step in the step list.
startScript : STRING = <code>www/apache/start</code>
The command to start Apache. Arguments containing spaces are not supported
stopOrder : INTEGER = 10
The order of the stop container step in the step list.
stopScript : STRING = <code>www/apache/stop</code>
The command to stop Apache. Arguments containing spaces are not supported
inspectClasspathResources : SET_OF_STRING
Additional classpath resources that should be uploaded to the working directory before executing the inspect script.
inspectScript : STRING
Classpath to the script used to inspect the generic container.
inspectTemplateClasspathResources : SET_OF_STRING
Additional template classpath resources that should be uploaded to the working directory before executing the inspect script. The template is first rendered and the rendered content copied to a file, with the same name as the template, in the working directory.

Control Tasks

restart

Restart Apache

start

Start Apache

stop

Stop Apache

www.ApacheVirtualHost

Hierarchy [www.ApacheConfFragment](#) >> generic.ProcessedTemplate >> generic.AbstractDeployedArtifact >> generic.AbstractDeployed >> udm.BaseDeployed >> udm.BaseConfigurationItem

Interfaces udm.Deployed, udm.ConfigurationItem

Apache virtual host

Public Properties



container : **CI**<udm.Container>

The container on which this deployed runs.

host : **STRING**

The virtual host name. Use '*' to match all hosts
port : STRING
The virtual host port. Use '*' to match all ports
deployable : CI<udm.Deployable>
The deployable that this deployed is derived from.
documentRoot : STRING
The document root for web content using this virtual host. If left blank, a directory is created in the web server's document root

Hidden Properties

createOrder : INTEGER = 50
The order of the step in the step list for the create operation.
createVerb : STRING = Create
Create Verb
destroyOrder : INTEGER = 40
The order of the step in the step list for the destroy operation.
destroyVerb : STRING = Destroy
Destroy Verb
modifyOrder : INTEGER = 50
The order of the step in the step list for the modify operation.
modifyVerb : STRING = Modify
Modify Verb
noopOrder : INTEGER = 50
The order of the step in the step list for the noop operation.
noopVerb : STRING = Modify
Noop Verb
targetDirectory : STRING = \${deployed.container.configurationFragmentDirectory}
Target directory name
targetFile : STRING = \${deployed.name}.conf
Target file name
template : STRING = www/apache/\${deployed.type}.conf.ftl
Configuration fragment template file name.
createTargetDirectory : BOOLEAN = false
Create the target directory on the generic server if it does not exist.
inspectClasspathResources : SET_OF_STRING
Additional classpath resources that should be uploaded to the working directory before executing the inspect script.
inspectScript : STRING
Classpath to the script used to inspect the generic container.
inspectTemplateClasspathResources : SET_OF_STRING
Additional template classpath resources that should be uploaded to the working directory before executing the inspect script. The template is first rendered and the rendered content copied to a file, with the same name as the template, in the working directory.
restartRequired : BOOLEAN = true
Restart Required
restartRequiredForNoop : BOOLEAN = false
The generic container requires a restart for the NOOP action performed by this deployed.
targetDirectoryShared : BOOLEAN = true
Is the target directory shared by others on the generic server. When true, the target directory is not deleted during a destroy operation; only the artifacts copied to it.

www.ApacheVirtualHostSpec

Hierarchy generic.Resource >> udm.BaseDeployable >> udm.BaseConfigurationItem
Interfaces udm.Tagable, udm.Deployable, udm.ConfigurationItem

Specification for an Apache virtual host

Public Properties

documentRoot : STRING
The document root for web content using this virtual host. If left blank, a directory is created in the web server's document root (string)
host : STRING

The virtual host name. Use `***` to match all hosts (string)

port : `STRING`

The virtual host port. Use `***` to match all ports (string)

tags : `SET_OF_STRING`

The tags to map deployables to containers.


www.PublishedWebContent

Hierarchy generic.CopiedArtifact >> generic.AbstractDeployedArtifact >>
generic.AbstractDeployed >> udm.BaseDeployed >>
udm.BaseConfigurationItem

Interfaces udm.Artifact, udm.Deployed, udm.ConfigurationItem, udm.DerivedArtifact

Web content on the webserver

Public Properties

 **container** : `CI<udm.Container>`

The container on which this deployed runs.

deployable : `CI<udm.Deployable>`

The deployable that this deployed is derived from.

placeholders : `MAP_STRING_STRING`

A Map containing all the placeholders mapped to their values. Special values are `<ignore>` or `<empty>`

virtualHost : `CI<www.ApacheVirtualHost>`

Virtual host which this web content maps to.

Hidden Properties

createOrder : `INTEGER = 50`

The order of the step in the step list for the create operation.

createVerb : `STRING = Create`

Create Verb

destroyOrder : `INTEGER = 40`

The order of the step in the step list for the destroy operation.

destroyVerb : `STRING = Destroy`

Destroy Verb

modifyOrder : `INTEGER = 50`

The order of the step in the step list for the modify operation.

modifyVerb : `STRING = Modify`

Modify Verb

noopOrder : `INTEGER = 50`

The order of the step in the step list for the noop operation.

noopVerb : `STRING = Modify`

Noop Verb

targetDirectory : `STRING = <#assign
target=(deployed.virtualHost.documentRoot)!"/><#if target !=
>${target}<#else>${deployed.container.defaultDocumentRoot}`

Target directory name

createTargetDirectory : `BOOLEAN = false`

Create the target directory on the generic server if it does not exist.

inspectClasspathResources : `SET_OF_STRING`

Additional classpath resources that should be uploaded to the working directory before executing the inspect script.

inspectScript : `STRING`

Classpath to the script used to inspect the generic container.

inspectTemplateClasspathResources : `SET_OF_STRING`

Additional template classpath resources that should be uploaded to the working directory before executing the inspect script. The template is first rendered and the rendered content copied to a file, with the same name as the template, in the working directory.

restartRequired : `BOOLEAN = false`

Restart Required

restartRequiredForNoop : `BOOLEAN = false`

The generic container requires a restart for the NOOP action performed by this deployed.

targetDirectoryShared : `BOOLEAN = true`

Is the target directory shared by others on the generic server. When true, the target directory

is not deleted during a destroy operation; only the artifacts copied to it.
targetFile : STRING
Target File

www.WebContent

Hierarchy generic.Folder >> udm.BaseDeployableFolderArtifact >> udm.BaseDeployableArtifact >> udm.BaseDeployable >> udm.BaseConfigurationItem

Interfaces udm.Taggable, udm.Deployable, udm.SourceArtifact, udm.Artifact, udm.DeployableArtifact, udm.ConfigurationItem, udm.FolderArtifact

Folder containing web content (HTML pages, images, etc)

Public Properties
excludeFileNamesRegex : STRING
Regular expression that matches file names that must be excluded from scanning
placeholders : SET_OF_STRING
Placeholders detected in this artifact
scanPlaceholders : BOOLEAN = true
Scan Placeholders
tags : SET_OF_STRING
The tags to map deployables to containers.
Hidden Properties
textFileNamesRegex : STRING = .+\. (cfg conf config ini properties props txt asp aspx htm html jsf jsp xht xhtml sql xml xsd xsl xslt)
Regular expression that matches file names of text files