

Deployit JEE Plugin Manual

Version 3.7.2

Table of Contents

Table of Contents	2
CI Reference	3
Configuration Item Overview	3
Deployable Configuration Items	3
Virtual Deployable Configuration Items	3
Configuration Item Details	3
jee.DataSourceSpec	3
jee.Ear	3
jee.EjbJar	4
jee.JndiResourceSpec	5
jee.MailSessionSpec	5
jee.QueueConnectionFactorySpec	5
jee.QueueSpec	5
jee.ResourceSpec	6
jee.TopicConnectionFactorySpec	6
jee.TopicSpec	6
jee.War	7

CI Reference

Configuration Item Overview

Deployable Configuration Items

CI	Description
jee.DataSourceSpec	Deployable Java EE DataSource accessible via JNDI
jee.Ear	Deployable EAR artifact
jee.EjbJar	Deployable EJB JAR artifact
jee.MailSessionSpec	Deployable Java EE Mail Session accessible via JNDI
jee.QueueConnectionFactorySpec	Deployable Java EE JMS QueueConnectionFactory accessible via JNDI
jee.QueueSpec	Deployable Java EE JMS Queue accessible via JNDI
jee.TopicConnectionFactorySpec	Deployable Java EE JMS TopicConnectionFactory accessible via JNDI
jee.TopicSpec	Deployable Java EE JMS Topic accessible via JNDI
jee.War	Deployable WAR artifact

Virtual Deployable Configuration Items

CI	Description
jee.JndiResourceSpec	Deployable Java EE Resource accessible via JNDI
jee.ResourceSpec	Description unavailable

Configuration Item Details

jee.DataSourceSpec

Hierarchy [jee.JndiResourceSpec](#) >> [jee.ResourceSpec](#) >> [udm.BaseDeployable](#) >> [udm.BaseConfigurationItem](#)

Interfaces [udm.Taggable](#), [udm.Deployable](#), [udm.ConfigurationItem](#)

Deployable Java EE DataSource accessible via JNDI.

Public Properties
jndiName : STRING
Name used to lookup this resource in JNDI
tags : SET_OF_STRING
The tags to map deployables to containers.

jee.Ear

Hierarchy [udm.BaseDeployableArchiveArtifact](#) >> [udm.BaseDeployableFileArtifact](#) >>

udm.BaseDeployableArtifact >> udm.BaseDeployable >> udm.BaseConfigurationItem

Interfaces udm.Taggable, udm.Deployable, udm.SourceArtifact, udm.ArchiveArtifact, udm.Artifact, udm.DeployableArtifact, udm.ConfigurationItem, udm.FileArtifact

Deployable EAR artifact.

Public Properties
excludeFileNamesRegex : STRING Regular expression that matches file names that must be excluded from scanning
placeholders : SET_OF_STRING Placeholders detected in this artifact
scanPlaceholders : BOOLEAN = true Scan Placeholders
tags : SET_OF_STRING The tags to map deployables to containers.

Hidden Properties
textFileNamesRegex : STRING = .+\. (cfg conf config ini properties props txt asp aspx htm html jsf jsp xht xhtml sql xml xsd xsl xslt) Regular expression that matches file names of text files

jee.EjbJar

Hierarchy udm.BaseDeployableArchiveArtifact >> udm.BaseDeployableFileArtifact >>

udm.BaseDeployableArtifact >> udm.BaseDeployable >> udm.BaseConfigurationItem

Interfaces udm.Taggable, udm.Deployable, udm.SourceArtifact, udm.ArchiveArtifact, udm.Artifact, udm.DeployableArtifact, udm.ConfigurationItem, udm.FileArtifact

Deployable EJB JAR artifact.

Public Properties
excludeFileNamesRegex : STRING Regular expression that matches file names that must be excluded from scanning
placeholders : SET_OF_STRING Placeholders detected in this artifact
scanPlaceholders : BOOLEAN = true Scan Placeholders
tags : SET_OF_STRING The tags to map deployables to containers.

Hidden Properties
textFileNamesRegex : STRING = .+\. (cfg conf config ini properties props txt asp aspx htm html jsf jsp xht xhtml sql xml xsd xsl xslt) Regular expression that matches file names of text files

jee.JndiResourceSpec

Hierarchy [jee.ResourceSpec](#) >> udm.BaseDeployable >> udm.BaseConfigurationItem

Interfaces udm.Taggable, udm.Deployable, udm.ConfigurationItem

Deployable Java EE Resource accessible via JNDI.

Public Properties
jndiName : STRING Name used to lookup this resource in JNDI
tags : SET_OF_STRING The tags to map deployables to containers.

jee.MailSessionSpec

Hierarchy [jee.JndiResourceSpec](#) >> [jee.ResourceSpec](#) >> udm.BaseDeployable >> udm.BaseConfigurationItem

Interfaces udm.Taggable, udm.Deployable, udm.ConfigurationItem

Deployable Java EE Mail Session accessible via JNDI.

Public Properties
jndiName : STRING Name used to lookup this resource in JNDI
tags : SET_OF_STRING The tags to map deployables to containers.

jee.QueueConnectionFactorySpec

Hierarchy [jee.JndiResourceSpec](#) >> [jee.ResourceSpec](#) >> udm.BaseDeployable >> udm.BaseConfigurationItem

Interfaces udm.Taggable, udm.Deployable, udm.ConfigurationItem

Deployable Java EE JMS QueueConnectionFactory accessible via JNDI.

Public Properties
jndiName : STRING Name used to lookup this resource in JNDI
tags : SET_OF_STRING The tags to map deployables to containers.

jee.QueueSpec

Hierarchy [jee.JndiResourceSpec](#) >> [jee.ResourceSpec](#) >> udm.BaseDeployable >> udm.BaseConfigurationItem

Interfaces udm.Taggable, udm.Deployable, udm.ConfigurationItem

Deployable Java EE JMS Queue accessible via JNDI.

Public Properties
jndiName : <code>STRING</code>
Name used to lookup this resource in JNDI
tags : <code>SET_OF_STRING</code>
The tags to map deployables to containers.

jee.ResourceSpec

Hierarchy `udm.BaseDeployable >> udm.BaseConfigurationItem`

Interfaces `udm.Taggable, udm.Deployable, udm.ConfigurationItem`

Description unavailable

Public Properties
tags : <code>SET_OF_STRING</code>
The tags to map deployables to containers.

jee.TopicConnectionFactorySpec

Hierarchy `jee.JndiResourceSpec >> jee.ResourceSpec >> udm.BaseDeployable >> udm.BaseConfigurationItem`

Interfaces `udm.Taggable, udm.Deployable, udm.ConfigurationItem`

Deployable Java EE JMS TopicConnectionFactory accessible via JNDI.

Public Properties
jndiName : <code>STRING</code>
Name used to lookup this resource in JNDI
tags : <code>SET_OF_STRING</code>
The tags to map deployables to containers.

jee.TopicSpec

Hierarchy `jee.JndiResourceSpec >> jee.ResourceSpec >> udm.BaseDeployable >> udm.BaseConfigurationItem`

Interfaces `udm.Taggable, udm.Deployable, udm.ConfigurationItem`

Deployable Java EE JMS Topic accessible via JNDI.

Public Properties
jndiName : <code>STRING</code>
Name used to lookup this resource in JNDI
tags : <code>SET_OF_STRING</code>
The tags to map deployables to containers.

jee.War

Hierarchy udm.BaseDeployableArchiveArtifact >> udm.BaseDeployableFileArtifact >>
 udm.BaseDeployableArtifact >> udm.BaseDeployable >> udm.BaseConfigurationItem

Interfaces udm.Taggable, udm.Deployable, udm.SourceArtifact, udm.ArchiveArtifact, udm.Artifact,
 udm.DeployableArtifact, udm.ConfigurationItem, udm.FileArtifact

Deployable WAR artifact.

Public Properties

excludeFileNamesRegex : **STRING**

Regular expression that matches file names that must be excluded from scanning

placeholders : **SET_OF_STRING**

Placeholders detected in this artifact

scanPlaceholders : **BOOLEAN** = **true**

Scan Placeholders

tags : **SET_OF_STRING**

The tags to map deployables to containers.

Hidden Properties

textFileNamesRegex : **STRING** = **+.\\.(cfg | conf | config | ini | properties | props | txt | asp | aspx | htm | html | jsf | jsp | xht | xhtml | sql | xml | xsd | xsl | xslt)**

Regular expression that matches file names of text files